



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp®_rate2006 = 37.5

Servidor Itautec MX221 (Intel Xeon E5410)

SPECfp_rate_base2006 = 36.4

CPU2006 license: 9001


Test sponsor: Itautec

Tested by: Itautec

Test date: Mar-2008

Hardware Availability: Dec-2007

Software Availability: Jan-2008



Hardware

CPU Name: Intel Xeon E5410
 CPU Characteristics:
 CPU MHz: 2330
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ and Fortran Compiler 10.1 for Linux Build 20080112 Package ID: l_cc_p_10.1.012, l_fc_p_10.1.012
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Run Level 3 (multi-user)
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp_rate2006 = 37.5

Servidor Itaotec MX221 (Intel Xeon E5410)

SPECfp_rate_base2006 = 36.4

CPU2006 license: 9001
Test sponsor: Itaotec
Tested by: Itaotec

Test date: Mar-2008
Hardware Availability: Dec-2007
Software Availability: Jan-2008

L3 Cache: None
Other Cache: None
Memory: 16 GB (8 * 2 GB PC2-5300 FBDIMM, CL-5-5-5, ECC)
Disk Subsystem: 1 x SCSI, 73GB, 15000 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.17.10.50

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	<u>2339</u>	<u>23.2</u>	2334	23.3	2339	23.2	2	1204	22.6	1210	22.5	<u>1204</u>	<u>22.6</u>
416.gamess	4	1143	68.5	1147	68.3	<u>1144</u>	<u>68.4</u>	4	1123	69.7	1126	69.6	<u>1124</u>	<u>69.7</u>
433.milc	4	1730	21.2	1723	21.3	<u>1729</u>	<u>21.2</u>	4	<u>1726</u>	<u>21.3</u>	1725	21.3	1727	21.3
434.zeusmp	4	875	41.6	898	40.5	<u>897</u>	<u>40.6</u>	4	<u>897</u>	<u>40.6</u>	869	41.9	898	40.6
435.gromacs	4	<u>483</u>	<u>59.2</u>	483	59.1	483	59.2	4	477	59.9	<u>477</u>	<u>59.9</u>	477	59.9
436.cactusADM	4	996	48.0	997	47.9	<u>996</u>	<u>48.0</u>	1	<u>198</u>	<u>60.2</u>	198	60.4	200	59.7
437.leslie3d	4	<u>2230</u>	<u>16.9</u>	2220	16.9	2245	16.7	2	1133	16.6	<u>1133</u>	<u>16.6</u>	1129	16.7
444.namd	4	<u>651</u>	<u>49.3</u>	651	49.3	655	49.0	4	646	49.6	646	49.7	<u>646</u>	<u>49.6</u>
447.dealII	4	<u>669</u>	<u>68.4</u>	685	66.8	668	68.5	4	637	71.8	<u>639</u>	<u>71.6</u>	641	71.4
450.soplex	4	1440	23.2	<u>1441</u>	<u>23.2</u>	1448	23.0	4	1156	28.9	1159	28.8	<u>1156</u>	<u>28.9</u>
453.povray	4	<u>278</u>	<u>76.6</u>	278	76.5	273	77.9	4	229	93.1	229	92.9	<u>229</u>	<u>92.9</u>
454.calculix	4	676	48.8	667	49.5	<u>676</u>	<u>48.8</u>	4	467	70.7	<u>467</u>	<u>70.7</u>	473	69.7
459.GemsFDTD	4	<u>2424</u>	<u>17.5</u>	2450	17.3	2423	17.5	4	2410	17.6	2418	17.6	<u>2415</u>	<u>17.6</u>
465.tonto	4	704	55.9	<u>705</u>	<u>55.8</u>	709	55.5	4	<u>687</u>	<u>57.3</u>	686	57.4	692	56.9
470.lbm	4	<u>3000</u>	<u>18.3</u>	3000	18.3	3001	18.3	2	1914	14.4	1913	14.4	<u>1913</u>	<u>14.4</u>
481.wrf	4	1458	30.6	1453	30.8	<u>1455</u>	<u>30.7</u>	4	1448	30.8	<u>1450</u>	<u>30.8</u>	1457	30.7
482.sphinx3	4	2394	32.6	2371	32.9	<u>2381</u>	<u>32.7</u>	2	1666	23.4	1678	23.2	<u>1669</u>	<u>23.4</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

OMP_NUM_THREADS set to number of cores
KMP_STACK_SIZE set to 64M
KMP_AFFINITY set to physical,0

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run.
'/usr/bin/taskset' used to bind benchmark copies to processors.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp_rate2006 = 37.5

Servidor Itaotec MX221 (Intel Xeon E5410)

SPECfp_rate_base2006 = 36.4

CPU2006 license: 9001
Test sponsor: Itaotec
Tested by: Itaotec

Test date: Mar-2008
Hardware Availability: Dec-2007
Software Availability: Jan-2008

Platform Notes

BIOS configuration:
Hardware Prefetch Disabled

General Notes

This result was measured on the Servidor Itaotec MX201.
The Servidor Itaotec MX221 and the Servidor Itaotec MX201 are electronically equivalent.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp_rate2006 = 37.5

Servidor Itautec MX221 (Intel Xeon E5410)

SPECfp_rate_base2006 = 36.4

CPU2006 license: 9001
Test sponsor: Itautec
Tested by: Itautec

Test date: Mar-2008
Hardware Availability: Dec-2007
Software Availability: Jan-2008

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

Peak Compiler Invocation

C benchmarks (except as noted below):
/opt/intel/cc/10.1.012/bin/icc -L/opt/intel/cc/10.1.012/lib
-I/opt/intel/cc/10.1.012/include

433.milc: icc

C++ benchmarks (except as noted below):
icpc

450.soplex: /opt/intel/cc/10.1.012/bin/icpc -L/opt/intel/cc/10.1.012/lib
-I/opt/intel/cc/10.1.012/include

Fortran benchmarks (except as noted below):
ifort

437.leslie3d: /opt/intel/fc/10.1.012/bin/ifort -L/opt/intel/fc/10.1.012/lib
-I/opt/intel/fc/10.1.012/include

Benchmarks using both Fortran and C:
icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp_rate2006 = 37.5

Servidor Itaotec MX221 (Intel Xeon E5410)

SPECfp_rate_base2006 = 36.4

CPU2006 license: 9001
Test sponsor: Itaotec
Tested by: Itaotec

Test date: Mar-2008
Hardware Availability: Dec-2007
Software Availability: Jan-2008

Peak Portability Flags (Continued)

453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp_rate2006 = 37.5

Servidor Itautec MX221 (Intel Xeon E5410)

SPECfp_rate_base2006 = 36.4

CPU2006 license: 9001

Test sponsor: Itautec

Tested by: Itautec

Test date: Mar-2008

Hardware Availability: Dec-2007

Software Availability: Jan-2008

Peak Optimization Flags (Continued)

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Itautec-ic10.1-FP-intel64-linux-flags.20090713.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Itautec-ic10.1-FP-intel64-linux-flags.20090713.00.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.
Report generated on Tue Jul 22 18:30:52 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 April 2008.