

# SPEC<sup>®</sup> CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint<sup>®</sup>\_rate2006 = **NC**

PowerEdge R905 (AMD Opteron 8354, 2.20 GHz)

SPECint\_rate\_base2006 = **NC**

CPU2006 license: 55

Test date: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Apr-2008

Tested by: Dell Inc.

Software Availability: May-2008

**SPEC has determined that this result was not compliant with the SPEC CPU2006 run and reporting rules. Specifically, not all of the benchmark workloads validated, as required in Rule 3.3 "Continuous Run Requirement". In SPEC's opinion, the violation was primarily due to a problem in the SPEC-supplied toolset. A bug in SPEC CPU2006 caused some failures not to be displayed on reports at the time that this result was generated. The bug is fixed in CPU2006 V1.1.**

	Copies
400.perlbench	
401.bzip2	
403.gcc	
429.mcf	
445.gobmk	
456.hmmer	
458.sjeng	
462.libquantum	
471.omnibench	
473.astar	
483.xalanbmk	

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = **NC**

PowerEdge R905 (AMD Opteron 8354, 2.20 GHz)

SPECint\_rate\_base2006 = **NC**

CPU2006 license: 55

Test dates: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Apr-2008

Tested by: Dell Inc.

Software Availability: May-2008

**SPEC has determined that this result was not compliant with the SPEC CPU2006 run and reporting rules. Specifically, not all of the benchmark workloads validated, as required in Rule 3.3 "Continuous Run Requirement". In SPEC's opinion, the violation was primarily due to a problem in the SPEC-supplied toolset. A bug in SPEC CPU2006 caused some failures not to be displayed on reports at the time that this result was generated.**

**The bug is fixed in CPU2006 V1.1.**

## Hardware

CPU Name: AMD Opteron 8354  
CPU Characteristics:  
CPU MHz: 2200  
FPU: Integrated  
CPU(s) enabled: 16 cores, 4 chips, 4 cores/chip  
CPU(s) orderable: 2,4 chips  
Primary Cache: 64 KB I + 64 KB D on chip per core  
Secondary Cache: 512 KB I+D on chip per core  
L3 Cache: 2 MB I+D on chip per chip  
Other Cache: None  
Memory: 32 GB (16 x 2GB, DDR2-667, CL5, Reg, Dual Rank)  
Disk Subsystem: 2 x 73 GB 10000 RPM SAS (RAID 0)  
Other Hardware: None

## Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
Compiler: PGI Server Complete Version 7.2 PathScale Compiler Suite Version 3.1  
Auto Parallel: No  
File System: ReiserFS  
System State: Run Level 3 (multi-user)  
Base Pointers: 32/64-bit  
Peak Pointers: 32/64-bit  
Other Software: SmartHeap 8.0 32-bit Library for Linux

## Errors

Run of 429.mf (base) was not valid; status is RE

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = **NC**

PowerEdge R905 (AMD Opteron 8354, 2.20 GHz)

SPECint\_rate\_base2006 = **NC**

CPU2006 license: 55

Test dates: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Apr-2008

Tested by: Dell Inc.

Software Availability: May-2008

**SPEC has determined that this result was not compliant with the SPEC CPU2006 run and reporting rules. Specifically, not all of the benchmark workloads validated, as required in Rule 3.3 "Continuous Run Requirement". In SPEC's opinion, the violation was primarily due to a problem in the SPEC-supplied toolset. A bug in SPEC CPU2006 caused some failures not to be displayed on reports at the time that this result was generated. The bug is fixed in CPU2006 V1.1.**

## Result Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
400.perlbench	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
401.bzip2	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
403.gcc	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
429.mcf	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
445.gobmk	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
456.hmmer	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
458.sjeng	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
462.libquantum	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
464.h264ref	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
471.omnetpp	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
473.astar	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
483.ges	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
'numactl' was used to bind copies to the cores
Environment variable PGI_HUGE_PAGES set to 150
'ulimit -s unlimited' was used to set environment stack size
'ulimit -l 4915200' was used to set environment locked pages in memory quantity
Set vm/nr_hugepages=2400 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages
```

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = **NC**

PowerEdge R905 (AMD Opteron 8354, 2.20 GHz)

SPECint\_rate\_base2006 = **NC**

CPU2006 license: 55

Test dates: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Apr-2008

Tested by: Dell Inc.

Software Availability: May-2008

**SPEC has determined that this result was not compliant with the SPEC CPU2006 run and reporting rules. Specifically, not all of the benchmark workloads validated, as required in Rule 3.3 "Continuous Run Requirement". In SPEC's opinion, the violation was primarily due to a problem in the SPEC-supplied toolset. A bug in SPEC CPU2006 caused some failures not to be displayed on reports at the time that this result was generated.**

**The bug is fixed in CPU2006 V1.1.**

## Base Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgcpp

## Base Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
45.gobmk: -DSPEC_CPU_LP64
45c.bmminer: -DSPEC_CPU_LP64
458.sng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:

```
-fast -Mipa=jobs:4 -Mipa=fast -Mipa=inline -Mfprelaxed
-Msmartalloc=huge:150 -tp barcelona-64 -Bstatic_pgi
```

Continued on next page

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = NC

PowerEdge R905 (AMD Opteron 8354, 2.20 GHz)

SPECint\_rate\_base2006 = NC

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test dates: Mar-2008

Hardware Availability: Apr-2008

Software Availability: May-2008

**SPEC has determined that this result was not compliant with the SPEC CPU2006 run and reporting rules. Specifically, not all of the benchmark workloads validated, as required in Rule 3.3 "Continuous Run Requirement". In SPEC's opinion, the violation was primarily due to a problem in the SPEC-supplied toolset. A bug in SPEC CPU2006 caused some failures not to be displayed on reports at the time that this result was generated. The bug is fixed in CPU2006 V1.1.**

## Base Optimization Flags (Continued)

C++ benchmarks:

-fastsse -Mipa=jobs:4 -Mipa=fast -Mipa=inline -Mfprelaxed  
-Msmartalloc=huge:150 -Mseh -tp=parcelona -Bstatic\_pgi

## Base Other Flags

C benchmarks:

-w

C++ benchmarks:

-w

## Peak Compiler Invocation

(as noted below):

pgcc

400.perlbench: pathcc

403.gcc: pathcc

445.gobmk: pathcc

C++ benchmarks (except as noted below):

pathCC

Continued on next page

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = **NC**

PowerEdge R905 (AMD Opteron 8354, 2.20 GHz)

SPECint\_rate\_base2006 = **NC**

CPU2006 license: 55

Test dates: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Apr-2008

Tested by: Dell Inc.

Software Availability: May-2008

**SPEC has determined that this result was not compliant with the SPEC CPU2006 run and reporting rules. Specifically, not all of the benchmark workloads validated, as required in Rule 3.3 "Continuous Run Requirement". In SPEC's opinion, the violation was primarily due to a problem in the SPEC-supplied toolset. A bug in SPEC CPU2006 caused some failures not to be displayed on reports at the time that this result was generated. The bug is fixed in CPU2006 V1.1.**

## Peak Compiler Invocation (Continued)

471.omnetpp: pgcpp

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_X64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64  
445.gobmk: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -march=barcelona -fb\_create fbdata(pass 1)  
-fb\_opt fbdata(pass 2) -Ofast -IPA:plimit=20000 -LNO:opt=0  
-WOPT:if\_conv=0 -CG:local\_sched\_alg=1  
401.bzip2: -Mpfi(pass 1) -Mpfo(pass 2) -fast -O4  
-Msmartalloc=huge:150 -Mnounroll -tp barcelona-64  
-Bstatic\_pgi

Continued on next page

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = **NC**

PowerEdge R905 (AMD Opteron 8354, 2.20 GHz)

SPECint\_rate\_base2006 = **NC**

CPU2006 license: 55

Test dates: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Apr-2008

Tested by: Dell Inc.

Software Availability: May-2008

**SPEC has determined that this result was not compliant with the SPEC CPU2006 run and reporting rules. Specifically, not all of the benchmark workloads validated, as required in Rule 3.3 "Continuous Run Requirement". In SPEC's opinion, the violation was primarily due to a problem in the SPEC-supplied toolset. A bug in SPEC CPU2006 caused some failures not to be displayed on reports at the time that this result was generated.**

**The bug is fixed in CPU2006 V1.1.**

## Peak Optimization Flags (Continued)

403.gcc: -march=barcelona -fb\_create fbdata(pass 1)  
-fb\_opt fbdata(pass 2) -m32 -O3 -OPT:Ofast

429.mcf: -fastsse -Mipa=jobs:4 -Mipa=fast -Mipa=inline:1  
-Msmartalloc=huge:150 -tp barcelona -Bstatic\_pgi

445.gobmk: -march=barcelona -fb\_create fbdata(pass 1)  
-fb\_opt fbdata(pass 2) -O3 -OPT:alias=restrict -LNO:opt=0  
-CG:parallelism

456.hmmer: -fastsse -Munroll=n:8 -Msmartalloc=huge:150 -Mfprefaxed  
-Mmact=partial -Msafeptr -Mipa=jobs:4 -Mipa=const  
-Mipa=opt -Mipa=arg -Mipa=inline -tp barcelona-64  
-Bstatic\_pgi

458.sjeng: -mpfi(pass 1) -Mipa=jobs:4(pass 2) -Mipa=fast(pass 2)  
-Mipa=inline:1(pass 2) -Mipa=noarg(pass 2) -Mpfo(pass 2)  
-fastsse -Msmartalloc=huge:150 -Mfprefaxed  
-tp barcelona-64 -Bstatic\_pgi

463.libquantum: -fastsse -Mfprefaxed -Msmartalloc=huge:150 -Munroll=m:8  
-Mipa=jobs:4 -Mipa=fast -Mipa=inline -Mipa=noarg  
-tp barcelona-64 -Bstatic\_pgi

464.h264ref: -Mpfi=indirect(pass 1) -Mipa=jobs:4(pass 2)  
-Mipa=fast(pass 2) -Mipa=inline(pass 2)  
-Mpfo=indirect(pass 2) -fastsse -Msmartalloc=huge:150  
-Mfprefaxed -tp barcelona-64 -Bstatic\_pgi

Continued on next page

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = **NC**

PowerEdge R905 (AMD Opteron 8354, 2.20 GHz)

SPECint\_rate\_base2006 = **NC**

CPU2006 license: 55

Test dates: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Apr-2008

Tested by: Dell Inc.

Software Availability: May-2008

**SPEC has determined that this result was not compliant with the SPEC CPU2006 run and reporting rules. Specifically, not all of the benchmark workloads validated, as required in Rule 3.3 "Continuous Run Requirement". In SPEC's opinion, the violation was primarily due to a problem in the SPEC-supplied toolset. A bug in SPEC CPU2006 caused some failures not to be displayed on reports at the time that this result was generated.**

**The bug is fixed in CPU2006 V1.1.**

## Peak Optimization Flags (Continued)

C++ benchmarks:

```
471.omnetpp: basepeak = yes
473.astar: -march=barcelona -Ofast -TENV:frame_pointer=off
          -WOPT:if_conv -GRA:optimize_boundary=on -IPA:plimit=525
          -m32 -lsmartleap
483.xalancbmk: -march=barcelona -Ofast -m32 -OPT:unroll_times_max=8
              -CG:flush_pipeline_saved_regs=off -CG:ptr_load_use=0
              -lsmartleap
```

## Peak Other Flags

C benchmarks (except as noted below):

```
-w
400.perlbench: No flags used
403.gcc: No flags used
445.gobmk: No flags used
```

C++ benchmarks (except as noted below):

```
-L/root/work/cpu2006/amd123GH.libs/32
471.omnetpp: -w
```



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = NC

PowerEdge R905 (AMD Opteron 8354, 2.20 GHz)

SPECint\_rate\_base2006 = NC

CPU2006 license: 55

Test date: Mar-2008

Test sponsor: Dell Inc.

Hardware Availability: Apr-2008

Tested by: Dell Inc.

Software Availability: May-2008

**SPEC has determined that this result was not compliant with the SPEC CPU2006 run and reporting rules. Specifically, not all of the benchmark workloads validated, as required in Rule 3.3 "Continuous Run Requirement". In SPEC's opinion, the violation was primarily due to a problem in the SPEC-supplied toolset. A bug in SPEC CPU2006 caused some failures not to be displayed on reports at the time that this result was generated.**

**The bug is fixed in CPU2006 V1.1.**

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/amd123GH-flags.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/amd123GH-flags.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 18:08:09 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 7 May 2008.