



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS


NovaScale R460 E1
(Intel Xeon X5470, 3.33 GHz)

SPECint®2006 = 30.2

SPECint_base2006 = 26.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: NEC Corporation

Test date: Oct-2008
Hardware Availability: Oct-2008
Software Availability: Nov-2008



Hardware

CPU Name: Intel Xeon X5470
 CPU Characteristics: 3.33 GHz, 2x6 MB L2 shared, 1333 MHz system bus
 CPU MHz: 3333
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2 GB PC2-5300F, 2 rank, CL5-5-5, ECC)
 Disk Subsystem: 1x146.5 GB SAS, 15000RPM
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16.60-0.21-smp
 Compiler: Intel C++ Compiler 11.0 for Linux Build 20080730 Package ID: l_cproc_b_11.0.044
 Auto Parallel: Yes
 File System: ext2
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.1 Binutils 2.18.50.0.7.20080502



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460 E1
(Intel Xeon X5470, 3.33 GHz)

SPECint2006 = 30.2

SPECint_base2006 = 26.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: NEC Corporation

Test date: Oct-2008
Hardware Availability: Oct-2008
Software Availability: Nov-2008

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	<u>437</u>	<u>22.3</u>	438	22.3	435	22.5	<u>347</u>	<u>28.2</u>	346	28.2	348	28.1
401.bzip2	523	18.4	<u>525</u>	<u>18.4</u>	531	18.2	485	19.9	<u>484</u>	<u>19.9</u>	483	20.0
403.gcc	520	15.5	517	15.6	<u>519</u>	<u>15.5</u>	373	21.6	372	21.6	<u>372</u>	<u>21.6</u>
429.mcf	318	28.7	317	28.7	<u>317</u>	<u>28.7</u>	<u>317</u>	<u>28.8</u>	317	28.7	317	28.8
445.gobmk	469	22.4	469	22.4	<u>469</u>	<u>22.4</u>	431	24.3	431	24.3	<u>431</u>	<u>24.3</u>
456.hammer	<u>495</u>	<u>18.8</u>	496	18.8	495	18.8	322	29.0	<u>322</u>	<u>29.0</u>	322	29.0
458.sjeng	<u>552</u>	<u>21.9</u>	552	21.9	552	21.9	526	23.0	<u>526</u>	<u>23.0</u>	526	23.0
462.libquantum	<u>72.7</u>	<u>285</u>	72.8	285	72.3	286	<u>72.7</u>	<u>285</u>	72.8	285	72.3	286
464.h264ref	708	31.2	702	31.5	<u>707</u>	<u>31.3</u>	568	38.9	566	39.1	<u>568</u>	<u>39.0</u>
471.omnetpp	397	15.7	<u>396</u>	<u>15.8</u>	396	15.8	360	17.4	<u>359</u>	<u>17.4</u>	359	17.4
473.astar	430	16.3	<u>431</u>	<u>16.3</u>	431	16.3	375	18.7	374	18.8	<u>374</u>	<u>18.7</u>
483.xalancbmk	247	27.9	248	27.8	<u>248</u>	<u>27.9</u>	247	27.9	248	27.8	<u>248</u>	<u>27.9</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to "physical,0"

Platform Notes

Bios settings:
Hardware Prefetcher: Enabled
Adjacent Cache Line Prefetch: Enabled

General Notes

The NEC Express5800/120Rh-1(Intel Xeon X5470),
the NEC Express5800/120Rj-2(Intel Xeon X5470),
the Bull NovaScale R440 E1(Intel Xeon X5470, 3.33 GHz) and
the Bull NovaScale R460 E1(Intel Xeon X5470, 3.33 GHz) models are electronically equivalent.
The results have been measured on a NEC Express5800/120Rj-2(Intel Xeon X5470) model.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460 E1
(Intel Xeon X5470, 3.33 GHz)

SPECint2006 = 30.2

SPECint_base2006 = 26.3

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Oct-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel
-par-runtime-control -opt-prefetch

C++ benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/opt/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/Compiler/11.0/044/bin/intel64/icc
-L/opt/intel/Compiler/11.0/044/ipp/em64t/lib
-I/opt/intel/Compiler/11.0/044/ipp/em64t/include

456.hmmer: /opt/intel/Compiler/11.0/044/bin/intel64/icc
-L/opt/intel/Compiler/11.0/044/ipp/em64t/lib
-I/opt/intel/Compiler/11.0/044/ipp/em64t/include

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460 E1
(Intel Xeon X5470, 3.33 GHz)

SPECint2006 = 30.2

SPECint_base2006 = 26.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: NEC Corporation

Test date: Oct-2008
Hardware Availability: Oct-2008
Software Availability: Nov-2008

Peak Portability Flags (Continued)

462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -ansi-alias -opt-prefetch
401.bzp2: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -auto-ilp32 -opt-prefetch
-ansi-alias
403.gcc: -xSSE4.1 -ipo -O3 -no-prec-div -static -inline-alloc
-opt-malloc-options=3
429.mcf: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -O2 -ipo
-no-prec-div -ansi-alias
456.hmmer: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2
-ansi-alias -auto-ilp32
458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll4
462.libquantum: basepeak = yes
464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmarheap
473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmarheap
483.xalancbmk: basepeak = yes



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460 E1
(Intel Xeon X5470, 3.33 GHz)

SPECint2006 = 30.2

SPECint_base2006 = 26.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: NEC Corporation

Test date: Oct-2008
Hardware Availability: Oct-2008
Software Availability: Nov-2008

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revD.20090713.html>
<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revD.20090713.xml>
<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 22:50:30 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 January 2009.