



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp®2006 = 34.0

NovaScale R410 F2 (Intel Xeon X3450, 2.66 GHz)

SPECfp\_base2006 = 33.3

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Dell Inc.

Test date: Oct-2009

Hardware Availability: Dec-2009

Software Availability: Jul-2009



**Hardware**

CPU Name: Intel Xeon X3450  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.20 GHz  
 CPU MHz: 2667  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

**Software**

Operating System: Red Hat Enterprise Linux Server release 5.3, Kernel 2.6.18-128.el5  
 Compiler: Intel Fortran Compiler and Intel C++ Compiler Professional Edition 11.1 For Linux Build 20090511 Package ID: l\_cproc\_p\_11.1.040, l\_cprof\_p\_11.1.040  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run level 3 (multi-user)

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp2006 = 34.0

NovaScale R410 F2 (Intel Xeon X3450, 2.66 GHz)

SPECfp\_base2006 = 33.3

CPU2006 license: 20

Test date: Oct-2009

Test sponsor: Bull SAS

Hardware Availability: Dec-2009

Tested by: Dell Inc.

Software Availability: Jul-2009

L3 Cache: 8 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 8 GB (4 x 2 GB DDR3-1333 DR UDIMM)  
 Disk Subsystem: 1 x 160 GB 7200 RPM SATA  
 Other Hardware: None

Base Pointers: 64-bit  
 Peak Pointers: 64-bit  
 Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	195	69.6	<b>196</b>	<b>69.5</b>	196	69.4	197	69.1	195	69.6	<b>196</b>	<b>69.5</b>
416.gamess	893	21.9	<b>892</b>	<b>21.9</b>	892	22.0	863	22.7	<b>863</b>	<b>22.7</b>	864	22.7
433.milc	198	46.4	232	39.5	<b>198</b>	<b>46.3</b>	230	39.8	231	39.8	<b>231</b>	<b>39.8</b>
434.zeusmp	276	32.9	<b>277</b>	<b>32.9</b>	277	32.9	<b>276</b>	<b>33.0</b>	276	33.0	277	32.9
435.gromacs	333	21.4	331	21.5	<b>332</b>	<b>21.5</b>	<b>358</b>	<b>19.9</b>	358	19.9	357	20.0
436.cactusADM	131	91.3	<b>131</b>	<b>91.3</b>	131	91.5	121	99.0	<b>120</b>	<b>99.3</b>	120	100
437.leslie3d	335	28.0	<b>337</b>	<b>27.9</b>	337	27.9	335	28.0	<b>337</b>	<b>27.9</b>	337	27.9
444.namd	433	18.5	432	18.6	<b>432</b>	<b>18.6</b>	433	18.5	432	18.6	<b>432</b>	<b>18.6</b>
447.dealII	337	34.0	369	31.0	<b>337</b>	<b>34.0</b>	343	33.4	<b>343</b>	<b>33.4</b>	343	33.4
450.soplex	315	26.4	<b>315</b>	<b>26.5</b>	315	26.5	315	26.4	<b>315</b>	<b>26.5</b>	315	26.5
453.povray	200	26.6	201	26.5	<b>200</b>	<b>26.6</b>	167	31.9	165	32.2	<b>166</b>	<b>32.1</b>
454.calculix	323	25.6	<b>322</b>	<b>25.6</b>	321	25.7	318	25.9	<b>319</b>	<b>25.9</b>	319	25.9
459.GemsFDTD	<b>315</b>	<b>33.7</b>	314	33.8	315	33.7	300	35.4	<b>300</b>	<b>35.4</b>	300	35.4
465.tonto	459	21.4	458	21.5	<b>458</b>	<b>21.5</b>	<b>374</b>	<b>26.3</b>	374	26.3	374	26.3
470.lbm	274	50.1	<b>276</b>	<b>49.9</b>	276	49.8	274	50.1	<b>276</b>	<b>49.9</b>	276	49.8
481.wrf	<b>306</b>	<b>36.5</b>	306	36.5	306	36.5	306	36.5	<b>306</b>	<b>36.5</b>	305	36.6
482.sphinx3	479	40.7	<b>480</b>	<b>40.6</b>	526	37.0	479	40.7	<b>480</b>	<b>40.6</b>	526	37.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

BIOS Settings:  
Power Management = Maximum Performance (Default = Active Power Controller)



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp2006 = 34.0

NovaScale R410 F2 (Intel Xeon X3450, 2.66 GHz)

SPECfp\_base2006 = 33.3

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Dell Inc.

Test date: Oct-2009  
Hardware Availability: Dec-2009  
Software Availability: Jul-2009

## General Notes

OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to granularity=fine,scatter  
KMP\_STACKSIZE set to 200M  
The Dell PowerEdge R210 (Intel Xeon X3450, 2.66 GHz) and the Bull NovaScale R410 F2 (Intel Xeon X3450, 2.66 GHz) models are electronically equivalent. The results have been measured on a Dell PowerEdge R210 (Intel Xeon X3450, 2.66 GHz) model.

## Base Compiler Invocation

C benchmarks:  
icc -m64

C++ benchmarks:  
icpc -m64

Fortran benchmarks:  
ifort -m64

Benchmarks using both Fortran and C:  
icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.lelie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECfp2006 = 34.0**

NovaScale R410 F2 (Intel Xeon X3450, 2.66 GHz)

**SPECfp\_base2006 = 33.3**

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Dell Inc.

**Test date:** Oct-2009

**Hardware Availability:** Dec-2009

**Software Availability:** Jul-2009

## Base Optimization Flags (Continued)

C++ benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch`

Fortran benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -parallel`

Benchmarks using both Fortran and C:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -parallel`

## Peak Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

`433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias`

`470.lbm: basepeak = yes`

`482.sphinx3: basepeak = yes`

C++ benchmarks:

`444.namd: basepeak = yes`

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECfp2006 = 34.0**

NovaScale R410 F2 (Intel Xeon X3450, 2.66 GHz)

**SPECfp\_base2006 = 33.3**

**CPU2006 license:** 20

**Test date:** Oct-2009

**Test sponsor:** Bull SAS

**Hardware Availability:** Dec-2009

**Tested by:** Dell Inc.

**Software Availability:** Jul-2009

## Peak Optimization Flags (Continued)

447.dealII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias -scalar-rep- -opt-prefetch

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch  
-parallel

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: Same as 410.bwaves

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -opt-prefetch -parallel

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -auto

### Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32

436.cactusADM: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -opt-prefetch -parallel -auto-ilp32

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch  
-parallel -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-fp-linux64-revA.html>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECfp2006 = 34.0**

NovaScale R410 F2 (Intel Xeon X3450, 2.66 GHz)

**SPECfp\_base2006 = 33.3**

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Dell Inc.

**Test date:** Oct-2009

**Hardware Availability:** Dec-2009

**Software Availability:** Jul-2009

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-fp-linux64-revA.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 03:46:08 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 22 December 2009.