



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp®2006 = **62.2**

PRIMERGY TX300 S6, Intel Xeon X5675, 3.07 GHz

SPECfp\_base2006 = **58.2**

CPU2006 license: 19


Test date: Mar-2011

Test sponsor: Fujitsu

Hardware Availability: Feb-2011

Tested by: Fujitsu

Software Availability: Apr-2011



### Hardware

CPU Name: Intel Xeon X5675  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.47 GHz  
 CPU MHz: 3067  
 FPU: Integrated  
 CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64) with SP1, Kernel 2.6.32.12-0.7-default  
 Compiler: Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0 Update 3  
 Auto Parallel: Yes  
 File System: ext3  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp2006 = **62.2**

PRIMERGY TX300 S6, Intel Xeon X5675, 3.07 GHz

SPECfp\_base2006 = **58.2**

CPU2006 license: 19

Test date: Mar-2011

Test sponsor: Fujitsu

Hardware Availability: Feb-2011

Tested by: Fujitsu

Software Availability: Apr-2011

L3 Cache: 12 MB I+D on chip per chip  
Other Cache: None  
Memory: 48 GB (12 x 4 GB 2Rx4 PC3-10600R-9, ECC)  
Disk Subsystem: 1 x SAS, 300 GB, 10000 RPM  
Other Hardware: --

Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>77.3</u>	<u>176</u>	78.1	174	77.1	176	<u>77.3</u>	<u>176</u>	78.1	174	77.1	176
416.gamess	796	24.6	<u>799</u>	<u>24.5</u>	801	24.4	679	28.8	678	28.9	<u>678</u>	<u>28.9</u>
433.milc	167	54.9	<u>168</u>	<u>54.8</u>	168	54.8	<u>166</u>	<u>55.5</u>	166	55.4	165	55.5
434.zeusmp	79.9	114	78.7	116	<u>78.7</u>	<u>116</u>	79.9	114	78.7	116	<u>78.7</u>	<u>116</u>
435.gromacs	311	22.9	<u>313</u>	<u>22.8</u>	313	22.8	293	24.4	<u>293</u>	<u>24.4</u>	293	24.3
436.cactusADM	41.7	286	41.3	289	<u>41.7</u>	<u>286</u>	41.7	286	41.3	289	<u>41.7</u>	<u>286</u>
437.leslie3d	87.2	108	<u>83.4</u>	<u>113</u>	79.4	118	87.2	108	<u>83.4</u>	<u>113</u>	79.4	118
444.namd	396	20.3	<u>396</u>	<u>20.3</u>	397	20.2	<u>389</u>	<u>20.6</u>	389	20.6	389	20.6
447.dealII	<u>272</u>	<u>42.0</u>	272	42.0	273	41.9	<u>272</u>	<u>42.0</u>	272	42.0	273	41.9
450.soplex	244	34.2	244	34.2	<u>244</u>	<u>34.2</u>	244	34.2	244	34.2	<u>244</u>	<u>34.2</u>
453.povray	165	32.2	165	32.2	<u>165</u>	<u>32.2</u>	131	40.7	<u>131</u>	<u>40.5</u>	131	40.5
454.calculix	269	30.7	<u>268</u>	<u>30.8</u>	265	31.1	238	34.7	<u>238</u>	<u>34.7</u>	238	34.7
459.GemsFDTD	122	86.6	126	84.2	<u>123</u>	<u>86.4</u>	114	93.4	<u>113</u>	<u>93.9</u>	111	95.3
465.tonto	380	25.9	377	26.1	<u>379</u>	<u>26.0</u>	284	34.6	<u>284</u>	<u>34.6</u>	284	34.7
470.lbm	47.2	291	49.4	278	<u>49.4</u>	<u>278</u>	47.2	291	49.4	278	<u>49.4</u>	<u>278</u>
481.wrf	228	49.0	<u>220</u>	<u>50.7</u>	216	51.6	228	49.0	<u>220</u>	<u>50.7</u>	216	51.6
482.sphinx3	350	55.7	<u>353</u>	<u>55.3</u>	355	54.9	<u>309</u>	<u>63.1</u>	309	63.1	319	61.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'nudev /mnt/hugepages hugetlbfs defaults 0 0' added to /etc/fstab
echo 900 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

## Platform Notes

BIOS configuration:  
Data Reuse Optimization = Disable  
Intel HT Technology = Disable



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 62.2**

PRIMERGY TX300 S6, Intel Xeon X5675, 3.07 GHz

**SPECfp\_base2006 = 58.2**

**CPU2006 license:** 19

**Test date:** Mar-2011

**Test sponsor:** Fujitsu

**Hardware Availability:** Feb-2011

**Tested by:** Fujitsu

**Software Availability:** Apr-2011

## General Notes

OMP\_NUM\_THREADS set to number of cores

This result was measured on the PRIMERGY TX300 S6. The PRIMERGY TX300 S6 and the PRIMERGY RX300 S6 are electronically equivalent.

For information about Fujitsu please visit: <http://www.fujitsu.com>

Binaries were compiled on RHEL5.5 with binutils-2.17.50.0.6-14.el5

Submitted\_by: "Klassen, Peter" <peter.klassen@ts.fujitsu.com>

Submitted: Mon Mar 28 12:08:25 EDT 2011

Submission: cpu2006-20110328-15211.sub

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 450.soplex: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
 482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 62.2**

PRIMERGY TX300 S6, Intel Xeon X5675, 3.07 GHz

**SPECfp\_base2006 = 58.2**

**CPU2006 license:** 19

**Test date:** Mar-2011

**Test sponsor:** Fujitsu

**Hardware Availability:** Feb-2011

**Tested by:** Fujitsu

**Software Availability:** Apr-2011

## Base Optimization Flags

C benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias`

C++ benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias`

Fortran benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch`

Benchmarks using both Fortran and C:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias`

## Peak Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32  
-ansi-alias`

470.lbm: `basepeak = yes`

482.sphinx3: `-xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias  
-parallel`

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 62.2**

PRIMERGY TX300 S6, Intel Xeon X5675, 3.07 GHz

**SPECfp\_base2006 = 58.2**

CPU2006 license: 19

Test date: Mar-2011

Test sponsor: Fujitsu

Hardware Availability: Feb-2011

Tested by: Fujitsu

Software Availability: Apr-2011

## Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32  
-ansi-alias

436.cactusADM: basepeak = yes

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

**SPECfp2006 = 62.2**

PRIMERGY TX300 S6, Intel Xeon X5675, 3.07 GHz

**SPECfp\_base2006 = 58.2**

**CPU2006 license:** 19

**Test sponsor:** Fujitsu

**Tested by:** Fujitsu

**Test date:** Mar-2011

**Hardware Availability:** Feb-2011

**Software Availability:** Apr-2011

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110316.html>

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revA.20110316.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110316.xml>

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revA.20110316.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 19:49:51 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 20 April 2011.