



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3755 M3
(AMD Opteron 6234)

SPECfp®_rate2006 = 312

SPECfp_rate_base2006 = 292

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Mar-2012

Hardware Availability: Dec-2011

Software Availability: Jul-2011



Hardware

CPU Name: AMD Opteron 6234
CPU Characteristics: AMD Turbo CORE technology up to 3.00 GHz
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 24 cores, 2 chips, 12 cores/chip
CPU(s) orderable: 1,2 chips

Software

Operating System: Red Hat Enterprise Linux Server release 6.1, Kernel 2.6.32-131.0.15.el6.x86_64
Compiler: C/C++/Fortran: Version 4.2.5.2 of x86 Open64 Compiler Suite (from AMD)
Auto Parallel: No
File System: ext3
System State: Run level 3 (Full multiuser with network)
Base Pointers: 64-bit
Peak Pointers: 32/64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3755 M3
(AMD Opteron 6234)

SPECfp_rate2006 = 312

SPECfp_rate_base2006 = 292

CPU2006 license: 11

Test date: Mar-2012

Test sponsor: IBM Corporation

Hardware Availability: Dec-2011

Tested by: IBM Corporation

Software Availability: Jul-2011

Primary Cache:	384 KB I on chip per chip, 64 KB I shared / 2 cores; 16 KB D on chip per core	Other Software:	None
Secondary Cache:	12 MB I+D on chip per chip, 2 MB shared / 2 cores		
L3 Cache:	16 MB I+D on chip per chip, 8 MB shared / 6 cores		
Other Cache:	None		
Memory:	128 GB (16 x 8 GB 2Rx4 PC3-10600R-9, ECC)		
Disk Subsystem:	1 x 600 GB SATA, 15000 RPM		
Other Hardware:	None		

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	24	1114	293	1109	294	<u>1109</u>	<u>294</u>	24	1087	300	1088	300	<u>1087</u>	<u>300</u>
416.gamess	24	1919	245	1922	245	<u>1920</u>	<u>245</u>	24	1850	254	1847	254	<u>1848</u>	<u>254</u>
433.milc	24	924	239	922	239	<u>923</u>	<u>239</u>	24	778	283	<u>778</u>	<u>283</u>	778	283
434.zeusmp	24	719	304	716	305	<u>716</u>	<u>305</u>	24	706	310	708	309	<u>705</u>	310
435.gromacs	24	<u>587</u>	<u>292</u>	586	292	587	292	24	<u>575</u>	<u>298</u>	579	296	<u>575</u>	298
436.cactusADM	24	785	365	786	365	<u>786</u>	<u>365</u>	24	702	408	<u>703</u>	<u>408</u>	703	408
437.leslie3d	24	1134	199	<u>1135</u>	<u>199</u>	1135	199	24	951	237	<u>951</u>	<u>237</u>	950	238
444.namd	24	780	247	<u>780</u>	<u>247</u>	780	247	24	<u>765</u>	<u>252</u>	767	251	<u>759</u>	254
447.dealII	24	<u>510</u>	<u>538</u>	508	541	518	530	24	510	538	504	545	<u>507</u>	<u>542</u>
450.soplex	24	908	220	<u>908</u>	<u>220</u>	909	220	24	854	234	<u>791</u>	<u>253</u>	791	253
453.povray	24	<u>409</u>	<u>312</u>	409	312	409	312	24	365	350	364	351	<u>364</u>	<u>351</u>
454.calculix	24	<u>482</u>	<u>411</u>	482	411	483	410	24	466	425	466	425	<u>466</u>	<u>425</u>
459.GemsFDTD	24	1373	185	<u>1373</u>	<u>185</u>	1374	185	24	1276	200	<u>1276</u>	<u>200</u>	1275	200
465.tonto	24	825	286	<u>823</u>	<u>287</u>	822	287	24	<u>752</u>	<u>314</u>	755	313	<u>752</u>	314
470.lbm	24	869	379	868	380	<u>869</u>	<u>379</u>	24	867	380	868	380	<u>868</u>	<u>380</u>
481.wrf	24	813	330	820	327	<u>818</u>	<u>328</u>	24	<u>818</u>	<u>328</u>	815	329	820	327
482.sphinx3	24	1568	298	1574	297	<u>1568</u>	<u>298</u>	24	1442	324	1439	325	<u>1440</u>	<u>325</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
'numactl' was used to bind copies to the cores.
See the configuration file for details.

Operating System Notes

'ulimit -s unlimited' was used to set environment stack size
'ulimit -l 2097152' was used to set environment locked pages in memory limit

Set transparent_hugepage=never as a boot parameter in /boot/grub/menu.lst
Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3755 M3
(AMD Opteron 6234)

SPECfp_rate2006 = 312

SPECfp_rate_base2006 = 292

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Mar-2012

Hardware Availability: Dec-2011

Software Availability: Jul-2011

Operating System Notes (Continued)

Set kernel/randomize_va_space=0 in /etc/sysctl.conf

Set vm/nr_hugepages=21504 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages

Platform Notes

BIOS settings:

Operating Mode set to Performance Mode

General Notes

Environment variables set by runspec before the start of the run:

HUGETLB_LIMIT = "896"

LD_LIBRARY_PATH = "/root/speccpu-rate-rev1104B1/amd1104-rate-libs-revB/32:/root/speccpu-rate-rev1104B1/amd1104-rate-libs-revB/64"

The x86 Open64 Compiler Suite is only available from (and supported by) AMD at
<http://developer.amd.com/cpu/open64>

Binaries were compiled on a system with 2x AMD Opteron 6282SE chips + 64GB Memory using RHEL 6.1

Base Compiler Invocation

C benchmarks:
opencc

C++ benchmarks:
openCC

Fortran benchmarks:
openf95

Benchmarks using both Fortran and C:
opencc openf95

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64 -fno-second-underscore
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3755 M3
(AMD Opteron 6234)

SPECfp_rate2006 = 312

SPECfp_rate_base2006 = 292

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Mar-2012

Hardware Availability: Dec-2011

Software Availability: Jul-2011

Base Portability Flags (Continued)

```
447.deallI: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LINUX -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LP64
        -fno-second-underscore
482.sphinx3: -DSPEC_CPU_LP64
```

Base Optimization Flags

C benchmarks:

```
-march=bdver1 -Ofast -OPT:malloc_alg=1 -HP:bd=2m:heap=2m
-IPA:plimit=8000 -IPA:small_pu=100 -mso
```

C++ benchmarks:

```
-march=bdver1 -Ofast -static -CG:load_exe=0 -OPT:malloc_alg=1
-INLINE:aggressive=on -HP:bd=2m:heap=2m -D__OPEN64_FAST_SET
```

Fortran benchmarks:

```
-march=bdver1 -Ofast -LNO:blocking=off -OPT:rsqrt=2
-OPT:unroll_size=256 -HP:bd=2m:heap=2m -mso
```

Benchmarks using both Fortran and C:

```
-march=bdver1 -Ofast -OPT:malloc_alg=1 -HP:bd=2m:heap=2m
-IPA:plimit=8000 -IPA:small_pu=100 -mso -LNO:blocking=off
-OPT:rsqrt=2 -OPT:unroll_size=256
```

Peak Compiler Invocation

C benchmarks:
opencc

C++ benchmarks:
openCC

Fortran benchmarks:
openf95

Benchmarks using both Fortran and C:
opencc openf95



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3755 M3
(AMD Opteron 6234)

SPECfp_rate2006 = 312

SPECfp_rate_base2006 = 292

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Mar-2012

Hardware Availability: Dec-2011

Software Availability: Jul-2011

Peak Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
    433.milc: -DSPEC_CPU_LP64
    434.zeusmp: -DSPEC_CPU_LP64
    435.gromacs: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64 -fno-second-underscore
437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
    453.povray: -DSPEC_CPU_LP64
    454.calculix: -DSPEC_CPU_LP64
459.GemsFDTD: -DSPEC_CPU_LP64
    465.tonto: -DSPEC_CPU_LP64
    470.lbm: -DSPEC_CPU_LP64
    481.wrf: -DSPEC_CPU_LINUX -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LP64
        -fno-second-underscore
482.sphinx3: -DSPEC_CPU_LP64

```

Peak Optimization Flags

C benchmarks:

```

433.milc: -march=bdver1 -Ofast -CG:movnti=1 -CG:locs_best=on
    -HP:bdt=2m:heap=2m -IPA:plimit=7000 -IPA:callee_limit=1200
    -OPT:struct_array_copy=2 -OPT:alias=field_sensitive -mso

470.lbm: -march=bdver1 -Ofast -CG:cmp_peep=on
    -OPT:unroll_times_max=8 -OPT:unroll_size=256
    -OPT:unroll_level=2 -OPT:keep_ext=on -HP:bdt=2m:heap=2m
    -IPA:plimit=8000 -IPA:small_pu=100 -mso

482.sphinx3: -march=bdver1 -fb_create fbdata(pass 1)
    -fb_opt fbdata(pass 2) -Ofast -OPT:malloc_alg=2
    -CG:cmp_peep=on -CG:local_sched_alg=2 -INLINE:aggressive=on
    -LNO:prefetch=2 -LNO:prefetch_ahead=4 -mso

```

C++ benchmarks:

```

444.namd: -march=bdver1 -fb_create fbdata(pass 1)
    -fb_opt fbdata(pass 2) -Ofast -LNO:ignore_feedback=off
    -CG:local_sched_alg=2 -CG:load_exe=0 -OPT:unroll_size=256
    -fno-exceptions -HP:bdt=2m:heap=2m

447.dealII: -march=bdver1 -Ofast -D__OPEN64_FAST_SET -static
    -INLINE:aggressive=on -LNO:opt=0 -LNO:simd=0
    -fno-emit-exceptions -m32 -OPT:unroll_times_max=8
    -OPT:unroll_size=256 -OPT:unroll_level=2 -HP:bdt=2m:heap=2m
    -GRA:unspill=on -CG:cmp_peep=on -CG:movext_icmp=off
    -TENV:frame_pointer=off

```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3755 M3
(AMD Opteron 6234)

SPECfp_rate2006 = 312

SPECfp_rate_base2006 = 292

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Mar-2012

Hardware Availability: Dec-2011

Software Availability: Jul-2011

Peak Optimization Flags (Continued)

```
450.soplex: -march=bdver1 -fb_create fbdata(pass 1)
             -fb_opt fbdata(pass 2) -O3 -INLINE:aggressive=on -OPT:RO=1
             -OPT:IEEE_arith=3 -OPT:IEEE_NaN_Inf=off
             -OPT:fold_unsigned_relops=on -fno-exceptions -m32
             -HP:bdt=2m:heap=2m -WOPT:sib=on
```

```
453.povray: -march=bdver1 -fb_create fbdata(pass 1)
             -fb_opt fbdata(pass 2) -Ofast -CG:pre_local_sched=off
             -INLINE:aggressive=on -HP:bdt=2m:heap=2m -OPT:transform=2
             -OPT:alias=disjoint -WOPT:aggcm=0
```

Fortran benchmarks:

```
410.bwaves: -march=bdver1 -fb_create fbdata(pass 1)
             -fb_opt fbdata(pass 2) -Ofast -OPT:Ofast -OPT:treeheight=on
             -LNO:blocking=off -LNO:ignore_feedback=off -LNO:fu=4
             -LNO:loop_model_simd=on -LNO:simd_rm_unity_remainder=on
             -WOPT:aggstr=0 -HP:bdt=2m:heap=2m -CG:cmp_peep=on
```

```
416.gamess: -march=bdver1 -fb_create fbdata(pass 1)
             -fb_opt fbdata(pass 2) -O3 -LNO:fu=6 -LNO:blocking=0
             -LNO:simd=0 -OPT:Ofast -OPT:ro=3 -OPT:unroll_size=256
             -OPT:unroll_times_max=2 -CG:local_sched_alg=1
             -HP:bdt=2m:heap=2m -WOPT:sib=on
```

```
434.zeusmp: -march=bdver1 -Ofast -LNO:blocking=off -LNO:interchange=off
             -HP:bdt=2m:heap=2m
```

```
437.leslie3d: -march=bdver1 -Ofast -CG:pre_minreg_level=2 -LNO:simd=0
               -LNO:fusion=2 -HP:bdt=2m:heap=2m -mso
```

```
459.GemsFDTD: -march=bdver1 -Ofast -OPT:unroll_size=0 -LNO:fission=2
                -CG:load_exe=0 -CG:local_sched_alg=2 -HP
```

```
465.tonto: -march=bdver1 -Ofast -OPT:alias=no_f90_pointer_alias
             -LNO:blocking=off -CG:load_exe=1 -IPA:plimit=525
             -HP:bdt=2m:heap=2m
```

Benchmarks using both Fortran and C:

```
435.gromacs: -march=bdver1 -fb_create fbdata(pass 1)
              -fb_opt fbdata(pass 2) -Ofast -OPT:rsqrt=2
              -HP:bdt=2m:heap=2m
```

```
436.cactusADM: -march=bdver1 -fb_create fbdata(pass 1)
                 -fb_opt fbdata(pass 2) -Ofast -LNO:blocking=off
                 -LNO:prefetch=2 -HP -CG:locs_shallow_depth=1 -CG:load_exe=0
                 -WOPT:sib=on
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3755 M3
(AMD Opteron 6234)

SPECfp_rate2006 = 312

SPECfp_rate_base2006 = 292

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Mar-2012

Hardware Availability: Dec-2011

Software Availability: Jul-2011

Peak Optimization Flags (Continued)

454.calculix: -march=bdver1 -Ofast -OPT:unroll_size=256
-GRA:optimize_boundary=on -HP:bdt=2m:heap=2m

481.wrf: -march=bdver1 -Ofast -LNO:blocking=off -LANG:copyinout=off
-IPA:callee_limit=5000 -GRA:prioritize_by_density=on
-CG:load_exe=1 -HP -WOPT:sib=on

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/amd-platform-rate-revB.20120103.html>

<http://www.spec.org/cpu2006/flags/x86-open64-425-flags-rate-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/amd-platform-rate-revB.20120103.xml>

<http://www.spec.org/cpu2006/flags/x86-open64-425-flags-rate-revB.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Mon Sep 22 18:50:19 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 10 April 2012.