



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro A+ Server 2022TG-HTRF  
(H8DGT-HF, AMD Opteron 6272)

**SPECfp<sup>®</sup>\_rate2006 = 362**

**SPECfp\_rate\_base2006 = 338**

CPU2006 license: 001176


Test date: Feb-2012

Test sponsor: Supermicro

Hardware Availability: Nov-2011

Tested by: Supermicro

Software Availability: Dec-2011



### Hardware

CPU Name: AMD Opteron 6272  
CPU Characteristics: AMD Turbo CORE technology up to 3.00 GHz  
CPU MHz: 2100  
FPU: Integrated  
CPU(s) enabled: 32 cores, 2 chips, 16 cores/chip  
CPU(s) orderable: 1,2 chips

### Software

Operating System: Red Hat Enterprise Linux Server release 6.2, Kernel 2.6.32-220.el6.x86\_64  
Compiler: C/C++/Fortran: Version 4.2.5.2 of x86 Open64 Compiler Suite (from AMD)  
Auto Parallel: No  
File System: ext3  
System State: Run level 3 (Full multiuser with network)  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro A+ Server 2022TG-HTRF  
(H8DGT-HF, AMD Opteron 6272)

**SPECfp\_rate2006 = 362**

**SPECfp\_rate\_base2006 = 338**

**CPU2006 license:** 001176

**Test date:** Feb-2012

**Test sponsor:** Supermicro

**Hardware Availability:** Nov-2011

**Tested by:** Supermicro

**Software Availability:** Dec-2011

Primary Cache:	512 KB I on chip per chip, 64 KB I shared / 2 cores; 16 KB D on chip per core
Secondary Cache:	16 MB I+D on chip per chip, 2 MB shared / 2 cores
L3 Cache:	16 MB I+D on chip per chip, 8 MB shared / 8 cores
Other Cache:	None
Memory:	128 GB (16 x 8 GB 2Rx4 PC3-12800R-11, ECC)
Disk Subsystem:	1 x 1024 GB SATA, 7200 RPM
Other Hardware:	None

Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	32	1369	318	<u>1358</u>	<u>320</u>	1356	321	32	1338	325	<u>1341</u>	<u>324</u>	1342	324
416.gamess	32	2196	285	<u>2199</u>	<u>285</u>	2205	284	32	2083	301	<u>2079</u>	<u>301</u>	2078	302
433.milc	32	1098	268	<u>1098</u>	<u>268</u>	1097	268	32	937	314	938	313	<u>937</u>	<u>313</u>
434.zeusmp	32	779	374	<u>781</u>	<u>373</u>	785	371	32	752	387	755	386	<u>754</u>	<u>386</u>
435.gromacs	32	667	343	<u>663</u>	<u>344</u>	662	345	32	<u>653</u>	<u>350</u>	653	350	662	345
436.cactusADM	32	<u>871</u>	<u>439</u>	872	438	870	440	32	796	480	<u>800</u>	<u>478</u>	800	478
437.leslie3d	32	<u>1353</u>	<u>222</u>	1353	222	1352	223	32	1079	279	1083	278	<u>1081</u>	<u>278</u>
444.namd	32	885	290	<u>877</u>	<u>293</u>	877	293	32	868	296	<u>863</u>	<u>297</u>	862	298
447.dealII	32	578	634	575	637	<u>576</u>	<u>636</u>	32	548	668	569	643	<u>558</u>	<u>656</u>
450.soplex	32	1210	221	<u>1087</u>	<u>246</u>	1086	246	32	1010	264	<u>958</u>	<u>279</u>	937	285
453.povray	32	462	368	<u>462</u>	<u>368</u>	464	367	32	<u>414</u>	<u>411</u>	413	412	414	411
454.calculix	32	551	479	<u>552</u>	<u>478</u>	552	478	32	534	495	<u>533</u>	<u>495</u>	533	495
459.GemsFDTD	32	<u>1670</u>	<u>203</u>	1670	203	1670	203	32	1534	221	1541	220	<u>1538</u>	<u>221</u>
465.tonto	32	924	341	922	341	<u>923</u>	<u>341</u>	32	843	374	<u>843</u>	<u>374</u>	844	373
470.lbm	32	1005	437	1004	438	<u>1005</u>	<u>438</u>	32	1004	438	1016	433	<u>1005</u>	<u>438</u>
481.wrf	32	934	383	931	384	<u>933</u>	<u>383</u>	32	930	384	<u>931</u>	<u>384</u>	933	383
482.sphinx3	32	1834	340	1823	342	<u>1825</u>	<u>342</u>	32	<u>1637</u>	<u>381</u>	1643	380	1630	383

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
'numactl' was used to bind copies to the cores.  
See the configuration file for details.

## Operating System Notes

'ulimit -s unlimited' was used to set environment stack size  
'ulimit -l 2097152' was used to set environment locked pages in memory limit

Set transparent\_hugepage=never as a boot parameter in /boot/grub/menu.lst  
Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro A+ Server 2022TG-HTRF  
(H8DGT-HF, AMD Opteron 6272)

**SPECfp\_rate2006 = 362**

**SPECfp\_rate\_base2006 = 338**

**CPU2006 license:** 001176

**Test date:** Feb-2012

**Test sponsor:** Supermicro

**Hardware Availability:** Nov-2011

**Tested by:** Supermicro

**Software Availability:** Dec-2011

## Operating System Notes (Continued)

Set kernel/randomize\_va\_space=0 in /etc/sysctl.conf

Set vm/nr\_hugepages=28672 in /etc/sysctl.conf  
mount -t hugetlbfs nodev /mnt/hugepages

## General Notes

Environment variables set by runspec before the start of the run:

HUGETLB\_LIMIT = "896"

LD\_LIBRARY\_PATH = "/usr/cpu2006/amd1104-rate-libs-revB/32:/usr/cpu2006/amd1104-rate-libs-revB/64"

The x86 Open64 Compiler Suite is only available from (and supported by) AMD at  
<http://developer.amd.com/cpu/open64>

Binaries were compiled on a system with 2x AMD Opteron 6282SE chips + 64GB Memory using RHEL 6.1

## Base Compiler Invocation

C benchmarks:  
opencc

C++ benchmarks:  
openCC

Fortran benchmarks:  
openf95

Benchmarks using both Fortran and C:  
opencc openf95

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64  
436.cactusADM: -DSPEC\_CPU\_LP64 -fno-second-underscore  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro A+ Server 2022TG-HTRF  
(H8DGT-HF, AMD Opteron 6272)

**SPECfp\_rate2006 = 362**

**SPECfp\_rate\_base2006 = 338**

**CPU2006 license:** 001176

**Test sponsor:** Supermicro

**Tested by:** Supermicro

**Test date:** Feb-2012

**Hardware Availability:** Nov-2011

**Software Availability:** Dec-2011

## Base Portability Flags (Continued)

```
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LINUX -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LP64
           -fno-second-underscore
482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:

```
-march=bdver1 -Ofast -OPT:malloc_alg=1 -HP:bd=2m:heap=2m
-IPA:plimit=8000 -IPA:small_pu=100 -mso
```

C++ benchmarks:

```
-march=bdver1 -Ofast -static -CG:load_exe=0 -OPT:malloc_alg=1
-INLINE:aggressive=on -HP:bd=2m:heap=2m -D__OPEN64_FAST_SET
```

Fortran benchmarks:

```
-march=bdver1 -Ofast -LNO:blocking=off -OPT:rsqrt=2
-OPT:unroll_size=256 -HP:bd=2m:heap=2m -mso
```

Benchmarks using both Fortran and C:

```
-march=bdver1 -Ofast -OPT:malloc_alg=1 -HP:bd=2m:heap=2m
-IPA:plimit=8000 -IPA:small_pu=100 -mso -LNO:blocking=off
-OPT:rsqrt=2 -OPT:unroll_size=256
```

## Peak Compiler Invocation

C benchmarks:

opencc

C++ benchmarks:

openCC

Fortran benchmarks:

openf95

Benchmarks using both Fortran and C:

opencc openf95

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro A+ Server 2022TG-HTRF  
(H8DGT-HF, AMD Opteron 6272)

**SPECfp\_rate2006 = 362**

**SPECfp\_rate\_base2006 = 338**

**CPU2006 license:** 001176

**Test sponsor:** Supermicro

**Tested by:** Supermicro

**Test date:** Feb-2012

**Hardware Availability:** Nov-2011

**Software Availability:** Dec-2011

## Peak Portability Flags (Continued)

```

434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64 -fno-second-underscore
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LINUX -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LP64
        -fno-second-underscore
482.sphinx3: -DSPEC_CPU_LP64

```

## Peak Optimization Flags

C benchmarks:

```

433.milc: -march=bdver1 -Ofast -CG:movnti=1 -CG:locs_best=on
        -HP:bdt=2m:heap=2m -IPA:plimit=7000 -IPA:callee_limit=1200
        -OPT:struct_array_copy=2 -OPT:alias=field_sensitive -mso

470.lbm: -march=bdver1 -Ofast -CG:cmp_peep=on
        -OPT:unroll_times_max=8 -OPT:unroll_size=256
        -OPT:unroll_level=2 -OPT:keep_ext=on -HP:bdt=2m:heap=2m
        -IPA:plimit=8000 -IPA:small_pu=100 -mso

482.sphinx3: -march=bdver1 -fb_create fbdata(pass 1)
        -fb_opt fbdata(pass 2) -Ofast -OPT:malloc_alg=2
        -CG:cmp_peep=on -CG:local_sched_alg=2 -INLINE:aggressive=on
        -LNO:prefetch=2 -LNO:prefetch_ahead=4 -mso

```

C++ benchmarks:

```

444.namd: -march=bdver1 -fb_create fbdata(pass 1)
        -fb_opt fbdata(pass 2) -Ofast -LNO:ignore_feedback=off
        -CG:local_sched_alg=2 -CG:load_exe=0 -OPT:unroll_size=256
        -fno-exceptions -HP:bdt=2m:heap=2m

447.dealII: -march=bdver1 -Ofast -D__OPEN64_FAST_SET -static
        -INLINE:aggressive=on -LNO:opt=0 -LNO:simd=0
        -fno-emit-exceptions -m32 -OPT:unroll_times_max=8
        -OPT:unroll_size=256 -OPT:unroll_level=2 -HP:bdt=2m:heap=2m
        -GRA:unspill=on -CG:cmp_peep=on -CG:movext_icmp=off
        -TENV:frame_pointer=off

450.soplex: -march=bdver1 -fb_create fbdata(pass 1)
        -fb_opt fbdata(pass 2) -O3 -INLINE:aggressive=on -OPT:RO=1
        -OPT:IEEE_arith=3 -OPT:IEEE_NaN_Inf=off

```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro A+ Server 2022TG-HTRF  
(H8DGT-HF, AMD Opteron 6272)

**SPECfp\_rate2006 = 362**

**SPECfp\_rate\_base2006 = 338**

**CPU2006 license:** 001176

**Test sponsor:** Supermicro

**Tested by:** Supermicro

**Test date:** Feb-2012

**Hardware Availability:** Nov-2011

**Software Availability:** Dec-2011

## Peak Optimization Flags (Continued)

450.soplex (continued):

```
-OPT:fold_unsigned_relops=on -fno-exceptions -m32
-HP:bdt=2m:heap=2m -WOPT:sib=on
```

453.povray: -march=bdver1 -fb\_create fbdata(pass 1)

```
-fb_opt fbdata(pass 2) -Ofast -CG:pre_local_sched=off
-INLINE:aggressive=on -HP:bd=2m:heap=2m -OPT:transform=2
-OPT:alias=disjoint -WOPT:aggcm=0
```

Fortran benchmarks:

410.bwaves: -march=bdver1 -fb\_create fbdata(pass 1)

```
-fb_opt fbdata(pass 2) -Ofast -OPT:Ofast -OPT:treeheight=on
-LNO:blocking=off -LNO:ignore_feedback=off -LNO:fu=4
-LNO:loop_model_simd=on -LNO:simd_rm_unity_remainder=on
-WOPT:aggstr=0 -HP:bdt=2m:heap=2m -CG:cmp_peep=on
```

416.gamess: -march=bdver1 -fb\_create fbdata(pass 1)

```
-fb_opt fbdata(pass 2) -O3 -LNO:fu=6 -LNO:blocking=0
-LNO:simd=0 -OPT:Ofast -OPT:ro=3 -OPT:unroll_size=256
-OPT:unroll_times_max=2 -CG:local_sched_alg=1
-HP:bdt=2m:heap=2m -WOPT:sib=on
```

434.zeusmp: -march=bdver1 -Ofast -LNO:blocking=off -LNO:interchange=off
-HP:bdt=2m:heap=2m

437.leslie3d: -march=bdver1 -Ofast -CG:pre\_minreg\_level=2 -LNO:simd=0
-LNO:fusion=2 -HP:bdt=2m:heap=2m -mso

459.GemsFDTD: -march=bdver1 -Ofast -OPT:unroll\_size=0 -LNO:fission=2
-CG:load\_exe=0 -CG:local\_sched\_alg=2 -HP

465.tonto: -march=bdver1 -Ofast -OPT:alias=no\_f90\_pointer\_alias
-LNO:blocking=off -CG:load\_exe=1 -IPA:plimit=525
-HP:bdt=2m:heap=2m

Benchmarks using both Fortran and C:

435.gromacs: -march=bdver1 -fb\_create fbdata(pass 1)
-fb\_opt fbdata(pass 2) -Ofast -OPT:rsqrt=2
-HP:bdt=2m:heap=2m

436.cactusADM: -march=bdver1 -fb\_create fbdata(pass 1)
-fb\_opt fbdata(pass 2) -Ofast -LNO:blocking=off
-LNO:prefetch=2 -HP -CG:locs\_shallow\_depth=1 -CG:load\_exe=0
-WOPT:sib=on

454.calculix: -march=bdver1 -Ofast -OPT:unroll\_size=256
-GRA:optimize\_boundary=on -HP:bdt=2m:heap=2m

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro A+ Server 2022TG-HTRF  
(H8DGT-HF, AMD Opteron 6272)

**SPECfp\_rate2006 = 362**

**SPECfp\_rate\_base2006 = 338**

**CPU2006 license:** 001176

**Test date:** Feb-2012

**Test sponsor:** Supermicro

**Hardware Availability:** Nov-2011

**Tested by:** Supermicro

**Software Availability:** Dec-2011

## Peak Optimization Flags (Continued)

```
481.wrf: -march=bdver1 -Ofast -LNO:blocking=off -LANG:copyinout=off  
-IPA:callee_limit=5000 -GRA:prioritize_by_density=on  
-CG:load_exe=1 -HP -WOPT:sib=on
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/amd-platform-rate-revB.20120103.html>  
<http://www.spec.org/cpu2006/flags/x86-open64-425-flags-rate-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/amd-platform-rate-revB.20120103.xml>  
<http://www.spec.org/cpu2006/flags/x86-open64-425-flags-rate-revB.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 07:53:58 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 30 April 2012.