



# SPEC® CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## HITACHI

**SPECint®\_rate2006 = 5590**

Compute Blade 520X (Intel Xeon E7-8890 v3)

**SPECint\_rate\_base2006 = 5430**

CPU2006 license: 35


Test date: Jul-2015

Test sponsor: HITACHI

Hardware Availability: Jun-2015

Tested by: HITACHI

Software Availability: Oct-2014



### Hardware

CPU Name: Intel Xeon E7-8890 v3  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.30 GHz  
 CPU MHz: 2500  
 FPU: Integrated  
 CPU(s) enabled: 144 cores, 8 chips, 18 cores/chip, 2 threads/core  
 CPU(s) orderable: 2,4,8 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 45 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 2 TB (128 x 16 GB 2Rx4 PC4-2133P-R, running at 1600 MHz)  
 Disk Subsystem: 2 x 600 GB SAS, 10000 RPM, RAID1  
 Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux Server release 6.6 (Santiago)  
 2.6.32-504.el6.x86\_64  
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux  
 Auto Parallel: No  
 File System: ext4  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V10.0



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## HITACHI

SPECint\_rate2006 = 5590

Compute Blade 520X (Intel Xeon E7-8890 v3)

SPECint\_rate\_base2006 = 5430

CPU2006 license: 35  
Test sponsor: HITACHI  
Tested by: HITACHI

Test date: Jul-2015  
Hardware Availability: Jun-2015  
Software Availability: Oct-2014

### Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	288	<b>611</b>	<b>4600</b>	611	4610	611	4600	288	511	5510	<b>510</b>	<b>5520</b>	507	5550
401.bzip2	288	1014	2740	<b>1009</b>	<b>2750</b>	1008	2760	288	<b>976</b>	<b>2850</b>	976	2850	978	2840
403.gcc	288	<b>596</b>	<b>3890</b>	595	3900	598	3880	288	<b>596</b>	<b>3890</b>	595	3900	598	3880
429.mcf	288	393	6690	<b>391</b>	<b>6720</b>	390	6740	288	393	6690	<b>391</b>	<b>6720</b>	390	6740
445.gobmk	288	790	3820	788	3830	<b>789</b>	<b>3830</b>	288	766	3940	<b>763</b>	<b>3960</b>	762	3960
456.hmmer	288	<b>327</b>	<b>8210</b>	328	8180	327	8220	288	<b>327</b>	<b>8210</b>	328	8180	327	8220
458.sjeng	288	<b>790</b>	<b>4410</b>	788	4420	791	4410	288	761	4580	764	4560	<b>761</b>	<b>4580</b>
462.libquantum	288	<b>113</b>	<b>52800</b>	113	52800	113	52800	288	<b>113</b>	<b>52800</b>	113	52800	113	52800
464.h264ref	288	971	6560	<b>970</b>	<b>6570</b>	962	6620	288	<b>940</b>	<b>6780</b>	941	6770	937	6800
471.omnetpp	288	729	2470	<b>730</b>	<b>2470</b>	732	2460	288	<b>707</b>	<b>2550</b>	705	2550	710	2540
473.astar	288	682	2970	683	2960	<b>682</b>	<b>2960</b>	288	682	2970	683	2960	<b>682</b>	<b>2960</b>
483.xalancbmk	288	353	5630	<b>355</b>	<b>5590</b>	358	5560	288	353	5630	<b>355</b>	<b>5590</b>	358	5560

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

### Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

### Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

### Platform Notes

BIOS configuration:

C-State = Disable  
C1 Enhanced Mode = Disable  
EnergyEfficientTurbo = Disable  
ProcessorPerformanceStates = Disable  
UncoreFrequencyScaling = Disable  
Platform Controlled Type = Maximum Performance  
Memory Power Management = Disable  
Patrol Scrub = Disable

Sysinfo program /home/speccpu2006/cpu2006/config/sysinfo.rev6818  
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191  
running on RHEL6.6 Fri Jul 24 18:32:20 2015

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## HITACHI

SPECint\_rate2006 = 5590

Compute Blade 520X (Intel Xeon E7-8890 v3)

SPECint\_rate\_base2006 = 5430

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Jul-2015

Hardware Availability: Jun-2015

Software Availability: Oct-2014

### Platform Notes (Continued)

```

From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E7-8890 v3 @ 2.50GHz
 8 "physical id"s (chips)
288 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 18
  siblings  : 36
  physical 0: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
  physical 1: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
  physical 2: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
  physical 3: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
  physical 4: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
  physical 5: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
  physical 6: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
  physical 7: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
cache size : 46080 KB

```

```

From /proc/meminfo
MemTotal:      2117096216 kB
HugePages_Total:      0
Hugepagesize:    2048 kB

```

```

/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.6 (Santiago)

```

```

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.6 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.6 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

```

```

uname -a:
Linux RHEL6.6 2.6.32-504.el6.x86_64 #1 SMP Tue Sep 16 01:56:35 EDT 2014
x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 Jul 24 18:03

```

SPEC is set to: /home/speccpu2006/cpu2006
Filesystem      Type Size Used Avail Use% Mounted on
/dev/mapper/vg_rhel6-lv_home
                ext4 496G 7.5G 464G 2% /home

```

```

Additional information from dmidecode:
BIOS HITACHI 09-14 07/09/2015
Memory:
64x NO DIMM Unknown
1x Samsung M39.A2G40DB0-CPB 16 GB 1600 MHz 2 rank
127x Samsung M393A2G40DB0-CPB 16 GB 1600 MHz 2 rank

```

(End of data from sysinfo program)



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## HITACHI

SPECint\_rate2006 = 5590

Compute Blade 520X (Intel Xeon E7-8890 v3)

SPECint\_rate\_base2006 = 5430

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Jul-2015

Hardware Availability: Jun-2015

Software Availability: Oct-2014

## General Notes

Environment variables set by runspec before the start of the run:

LD\_LIBRARY\_PATH = "/home/speccpu2006/cpu2006/libs/32:/home/speccpu2006/cpu2006/libs/64:/home/speccpu2006/cpu2006/sh"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

Filesystem page cache cleared with:

echo 1> /proc/sys/vm/drop\_caches

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

BladeSymphony BS520X, BladeSymphony BS2500 and Hitachi Compute Blade 520X are electronically equivalent.

The results have been measured on a Hitachi Compute Blade 520X.

## Base Compiler Invocation

C benchmarks:

icc -m32

C++ benchmarks:

icpc -m32

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

462.libquantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch

-opt-mem-layout-trans=3

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch

-opt-mem-layout-trans=3 -Wl,-z,muldefs -L/sh -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

**HITACHI**

**SPECint\_rate2006 = 5590**

**Compute Blade 520X (Intel Xeon E7-8890 v3)**

**SPECint\_rate\_base2006 = 5430**

**CPU2006 license:** 35

**Test sponsor:** HITACHI

**Tested by:** HITACHI

**Test date:** Jul-2015

**Hardware Availability:** Jun-2015

**Software Availability:** Oct-2014

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m32

400.perlbench: icc -m64

401.bzip2: icc -m64

458.sjeng: icc -m64

C++ benchmarks:

icpc -m32

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64

401.bzip2: -DSPEC\_CPU\_LP64

458.sjeng: -DSPEC\_CPU\_LP64

462.libquantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32

401.bzip2: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: basepeak = yes

429.mcf: basepeak = yes

445.gobmk: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)  
-ansi-alias -opt-mem-layout-trans=3

456.hmmer: basepeak = yes

458.sjeng: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll14 -auto-ilp32

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## HITACHI

SPECint\_rate2006 = 5590

Compute Blade 520X (Intel Xeon E7-8890 v3)

SPECint\_rate\_base2006 = 5430

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Jul-2015

Hardware Availability: Jun-2015

Software Availability: Oct-2014

## Peak Optimization Flags (Continued)

462.libquantum: basepeak = yes

464.h264ref: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/sh -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.html>

<http://www.spec.org/cpu2006/flags/PlatformHitachi-V1.2.20150729.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.xml>

<http://www.spec.org/cpu2006/flags/PlatformHitachi-V1.2.20150729.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Tue Aug 25 17:53:22 2015 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 25 August 2015.