



SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint®_rate2006 = NC

Huawei 5288 V3 (Intel Xeon E5-2667 v4)

SPECint_rate_base2006 = NC

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Mar-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not
http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2 SPEC CPU run
<https://www.spec.org/osg/policy.html#AppendixC> gener

	Copies
400.perlbench	
401.bzip2	
403.gcc	
429.mcf	
445.gobmk	
456.hmmer	
458.sjeng	
462.libquantum	
464.h264ref	
471.omnetpp	
473.astar	
483.xalancbmk	

Hardware

CPU Name: Intel Xeon E5-2667 v4
 CPU Characteristics: Intel Turbo Boost Technology up to 3.60 GHz
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 16 cores, 2 chips, 8 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 25 MB I+D on chip per chip
 Other Cache: None
 Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2400T-R)
 Disk Subsystem: 1 x 1000 GB SATA, 7200rpm
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux Server release 7.0 (Maipo)
 3.10.0-123.el7.x86_64
 Compiler: C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux
 Auto Parallel: No
 File System: ext4
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V10.2



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint_rate2006 = NC

Huawei 5288 V3 (Intel Xeon E5-2667 v4)

SPECint_rate_base2006 = NC

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Mar-2016
Hardware Availability: Mar-2016
Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2 SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
400.perlbench	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		
401.bzip2	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		
403.gcc	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		
429.mcf	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		
445.gobmk	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		
456.hmmer	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		
458.sjeng	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		
462.libquantum	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		
464.h264ref	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		
471.omnetpp	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		
473.astar	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		
483.xalancbmk	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC		

Results appear in the column in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

BIOS configuration:
Set Power Efficiency Mode to Performance
Set Snoop Mode to ES mode
Set Patrol Scrub to Disable
Baseboard Management Controller used to adjust the fan speed to 100%
Sysinfo program /spec16/config/sysinfo.rev6914
\$Rev: 6914 \$ \$Date:: 2014-06-25 #\$ e3fbb8667b5a285932ceab81e28219e1
running on localhost.localdomain Fri Mar 25 14:27:56 2016

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint_rate2006 = NC

Huawei 5288 V3 (Intel Xeon E5-2667 v4)

SPECint_rate_base2006 = NC

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2 SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

Platform Notes (Continued)

This section contains SUT (System Under Test) information gathered by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.htm#sysinfo>

```
From /proc/cpuinfo
model name      : Intel(R) Xeon(R) CPU E5-2667 v4 @ 3.20GHz
 2 "physical id"s (chips)
 32 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
cpu cores      : 8
siblings       : 16
physical 0:    : cores 0  3  4  8 10 11 12
physical 1:    : cores 0  3  4  8 10 11 12
cache size     : 25600 KB
```

```
From /proc/meminfo
MemTotal:      26356932 kB
HugePages_Total:
Hugepagesize:  2048 kB
```

```
From /etc/*release /etc/*version*
os-release:
NAME="Red Hat Enterprise Linux Server"
VERSION="7.0 (Maipo)"
ID="rhel"
ID_LIKE="fedora"
VERSION_ID="7.0"
PRETTY_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"
ANSI_COLOR="0;31"
CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.0:ga:server
```

```
uname -a:
Linux localhost.localdomain 3.10.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57 EDT 2014 x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 Mar 25 05:47

```
SPEC is set to: /spec16
Filesystem      Type  Size  Used Avail Use% Mounted on
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint_rate2006 = NC

Huawei 5288 V3 (Intel Xeon E5-2667 v4)

SPECint_rate_base2006 = NC

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2 SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

Platform Notes (Continued)

/dev/sda2 ext4 913G 108G 759G 13% /
Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Insyde Corp. 3.09 02/22/2016

Memory:

8x Samsung M393A2G40EB1-CRC 16 GB Rank 2400 MHz
8x Samsung M393A2G40EB1-CRC 16 GB Rank 2400 MHz

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/spec16/libs/32:/spec16/libs/64:/spec16/sh"

Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB memory using RedHat EL 7

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/transparent_hugepage/enabled

Filesystem page cache cleared with:

echo 1 > /proc/sys/vm/drop_caches

runspec command invoked through numactl i.e.:

numactl --in=0 leave=all runspec <etc>

Base Compiler Invocation

C benchmarks:

icc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

C++ benchmarks:

icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint_rate2006 = NC

Huawei 5288 V3 (Intel Xeon E5-2667 v4)

SPECint_rate_base2006 = NC

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2 SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

Base Portability Flags

```

400.perlbench: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX_IA32
401.bzip2: -D_FILE_OFFSET_BITS=64
403.gcc: -D_FILE_OFFSET_BITS=64
429.mcf: -D_FILE_OFFSET_BITS=64
445.gobmk: -D_FILE_OFFSET_BITS=64
456.hmmer: -D_FILE_OFFSET_BITS=64
458.sjeng: -D_FILE_OFFSET_BITS=64
462.libquantum: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX
464.h264ref: -D_FILE_OFFSET_BITS=64
471.omnetpp: -D_FILE_OFFSET_BITS=64
473.astar: -D_FILE_OFFSET_BITS=64
483.xalancbmk: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX

```

Base Optimization Flags

```

C benchmarks:
-xCORE-AVX2 -ipo -O3 -m -prec-div -opt-prefetch
-opt-mem-layout-trans=5

C++ benchmarks:
-xCORE-AVX2 -ipo -O3 -m -prec-div -opt-prefetch
-opt-mem-layout-trans=5 -Wl,-z,muldefs -L/sh -lsmarthearp

```

Base Other Flags

```

C benchmarks:
403.gcc: -Dalloca=_alloca

```

Peak Compiler Invocation

```

C benchmarks (except as noted below):
icc -m32 -I/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

400.perlbench: icc -m64

```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint_rate2006 = NC

Huawei 5288 V3 (Intel Xeon E5-2667 v4)

SPECint_rate_base2006 = NC

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU run up policy on gener

Peak Compiler Invocation (Continued)

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:

icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

Peak Portability Flags

400.perlbench: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64
403.gcc: -D_FILE_OFFSET_BITS=64
429.mcf: -D_FILE_OFFSET_BITS=64
445.gobmk: -D_FILE_OFFSET_BITS=64
456.hmmer: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64
458.sjeng: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64
462.libquantum: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX
464.h264ref: -D_FILE_OFFSET_BITS=64
471.omnetpp: -D_FILE_OFFSET_BITS=64
473.astar: -D_FILE_OFFSET_BITS=64
483.xalanbmk: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX

Peak Optimization Flags

400.perlbench: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -prof-use(pass 2) -auto-ilp32
401.bzip2: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -prof-use(pass 2) -opt-prefetch
-auto-ilp32 -ansi-alias
403.gcc: basepeak = yes

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint_rate2006 = NC

Huawei 5288 V3 (Intel Xeon E5-2667 v4)

SPECint_rate_base2006 = NC

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2 SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 2) -prof-use(pass 2) -par-num-threads=1(pass 1) -ansi-alias -opt-mem-layout-trans=3

456.hmmcr: -xCORE-AVX2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32

458.sjeng: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -par-num-threads=1(pass 1) -prof-use(pass 2) -unroll4 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -par-num-threads=1(pass 1) -prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -par-num-threads=1(pass 1) -prof-use(pass 2) -ansi-alias -opt-mem-layout-trans=3 -region-strategy=block -Wl,-z,muldefs -L/sh -lsmartheap

477.astar: basepeak = yes

482.libquantum: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint_rate2006 = NC

Huawei 5288 V3 (Intel Xeon E5-2667 v4)

SPECint_rate_base2006 = NC

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Mar-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not
a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU run
up policy on gener

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BTW-V1.0.html>

You can also download the XML flags sources by using the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BTW-V1.0.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Oct 21 20:12:18 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 April 2016.