



SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A8-8650 with Radeon R7 Graphics)

SPECint®2006 = 30.7

SPECint_base2006 = 30.0

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2016

Hardware Availability: Dec-2015

Software Availability: Aug-2015



Hardware

CPU Name: AMD A8-8650
 CPU Characteristics: AMD Turbo CORE technology up to 3.80 GHz
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 192 KB I on chip per chip, 96 KB I shared / 2 cores; 16 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip, 2 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 8 GB (2 x 4 GB 2Rx8 PC3-10600U-11)
 Disk Subsystem: Seagate Barracuda 250 GB SATA, 7200 RPM
 Other Hardware: None

Software

Operating System: Microsoft Windows 7 Ultimate 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows;
 Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013
 Auto Parallel: Yes
 File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 11.0 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A8-8650 with Radeon R7 Graphics)

SPECint2006 = 30.7

SPECint_base2006 = 30.0

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2016

Hardware Availability: Dec-2015

Software Availability: Aug-2015

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	<u>412</u>	<u>23.7</u>	411	23.8	412	23.7	349	28.0	<u>349</u>	<u>28.0</u>	350	27.9
401.bzip2	<u>583</u>	<u>16.6</u>	580	16.6	588	16.4	601	16.0	<u>570</u>	<u>16.9</u>	563	17.1
403.gcc	<u>508</u>	<u>15.8</u>	508	15.8	508	15.9	<u>503</u>	<u>16.0</u>	504	16.0	502	16.0
429.mcf	<u>285</u>	<u>32.0</u>	284	32.1	285	32.0	<u>285</u>	<u>32.0</u>	284	32.1	285	32.0
445.gobmk	457	22.9	457	23.0	<u>457</u>	<u>23.0</u>	<u>441</u>	<u>23.8</u>	441	23.8	440	23.9
456.hammer	<u>190</u>	<u>49.1</u>	190	49.1	191	48.9	<u>190</u>	<u>49.1</u>	190	49.1	191	48.9
458.sjeng	560	21.6	<u>560</u>	<u>21.6</u>	559	21.7	560	21.6	<u>560</u>	<u>21.6</u>	559	21.7
462.libquantum	<u>71.9</u>	<u>288</u>	70.6	294	73.1	283	<u>71.9</u>	<u>288</u>	70.6	294	73.1	283
464.h264ref	<u>522</u>	<u>42.4</u>	524	42.2	522	42.4	<u>522</u>	<u>42.4</u>	524	42.2	522	42.4
471.omnetpp	360	17.4	<u>359</u>	<u>17.4</u>	358	17.5	338	18.5	336	18.6	<u>336</u>	<u>18.6</u>
473.astar	350	20.0	350	20.1	<u>350</u>	<u>20.1</u>	350	20.0	350	20.1	<u>350</u>	<u>20.1</u>
483.xalancbmk	272	25.4	<u>271</u>	<u>25.5</u>	270	25.6	272	25.4	<u>271</u>	<u>25.5</u>	270	25.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 16.0 was set up to generate 64-bit binaries with the command:

```
"psxevars.bat intel64" (shortcut provided in the Intel(r) Parallel Studio XE 2016 program folder)
```

Platform Notes

```
Sysinfo program C:\SPEC16.0/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on CltE03F49ACBFDE Thu May 26 04:26:18 2016
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name : Microsoft Windows 7 Ultimate
OS Version : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: System manufacturer
System Model : System Product Name
Processor(s) : 1 Processor(s) Installed.
[01]: AMD64 Family 21 Model 56 Stepping 1 AuthenticAMD ~3200 Mhz
BIOS Version : American Megatrends Inc. 2502, 12/11/2015
Total Physical Memory: 7,108 MB
```

```
Trying 'wmic cpu get /value'
DeviceID : CPU0
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A8-8650 with Radeon R7 Graphics)

SPECint2006 = 30.7

SPECint_base2006 = 30.0

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2016

Hardware Availability: Dec-2015

Software Availability: Aug-2015

Platform Notes (Continued)

L2CacheSize : 25359
L3CacheSize : 0
MaxClockSpeed : 3200
Name : AMD A8-8650 Radeon R7, 10 Compute Cores 4C+6G
NumberOfCores : 2
NumberOfLogicalProcessors: 4

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
+ 64GB memory using Windows 8.1 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

C++ benchmarks:

icl -Qvc12

Base Portability Flags

400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
401.bzip2: -DSPEC_CPU_P64
403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
429.mcf: -DSPEC_CPU_P64
445.gobmk: -DSPEC_CPU_P64
456.hmmer: -DSPEC_CPU_P64
458.sjeng: -DSPEC_CPU_P64
462.libquantum: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_P64 -DWIN32
471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
473.astar: -DSPEC_CPU_P64
483.xalancbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword -DWIN64



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A8-8650 with Radeon R7 Graphics)

SPECint2006 = 30.7

SPECint_base2006 = 30.0

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2016

Hardware Availability: Dec-2015

Software Availability: Aug-2015

Base Optimization Flags

C benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel
-Qauto-ilp32 /F64000000
```

C++ benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
-Qauto-ilp32 /F64000000 shlw64M.lib -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc12 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc12
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
400.perlbench: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F64000000 shlw64M.lib
/F256000000 -link /FORCE:MULTIPLE
```

```
401.bzip2: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias
-Qauto-ilp32 /F64000000
```

```
403.gcc: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qauto-ilp32 /F64000000
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A8-8650 with Radeon R7 Graphics)

SPECint2006 = 30.7

SPECint_base2006 = 30.0

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2016

Hardware Availability: Dec-2015

Software Availability: Aug-2015

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O2 -Qprec-div- -Qansi-alias -Qauto-ilp32
/F64000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F64000000
shlW64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml>



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A8-8650 with Radeon R7 Graphics)

SPECint2006 = 30.7

SPECint_base2006 = 30.0

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2016

Hardware Availability: Dec-2015

Software Availability: Aug-2015

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Sep 20 15:06:40 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 September 2016.