



# SPEC® CPU2017 Integer Rate Result

Copyright 2017-2018 Standard Performance Evaluation Corporation


## Fujitsu Fujitsu SPARC M12-2S

SPECrate2017\_int\_base = 1180

SPECrate2017\_int\_peak = 1420

CPU2017 License: 19  
Test Sponsor: Fujitsu  
Tested by: Fujitsu

Test Date: Nov-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017



### Hardware

CPU Name: SPARC64 XII  
 Max MHz.: 4350  
 Nominal: 4250  
 Enabled: 192 cores, 16 chips, 8 threads/core  
 Orderable: 1 to 16 BBs; each BB contains 1 or 2 CPU chips;  
 2, 3, 4, ... 384 cores  
 Cache L1: 64 KB I + 64 KB D on chip per core  
 L2: 512 KB I+D on chip per core  
 L3: 32 MB I+D on chip per chip  
 Other: None  
 Memory: 8 TB (256 x 32 GB 2Rx4 PC4-2400T-R)  
 Storage: 1 x 600 GB 10K RPM SAS (for system disk)  
 Other: None

### Software

OS: Oracle Solaris 11.3 SRU 24.4  
 Compiler: C/C++/Fortran: Version 12.6 of Oracle Developer Studio  
 Parallel: No  
 Firmware: Fujitsu HCP Version 3040 released Oct-2017  
 File System: tmpfs  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: 32-bit  
 Other: None



# SPEC CPU2017 Integer Rate Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Fujitsu  
Fujitsu SPARC M12-2S

SPECrate2017\_int\_base = 1180

SPECrate2017\_int\_peak = 1420

CPU2017 License: 19  
Test Sponsor: Fujitsu  
Tested by: Fujitsu

Test Date: Nov-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
500.perlbench_r	1536	2143	1140	<b><u>2145</u></b>	<b><u>1140</u></b>			1536	1644	1490	<b><u>1648</u></b>	<b><u>1480</u></b>		
502.gcc_r	1536	<b><u>2383</u></b>	<b><u>913</u></b>	2316	939			1536	<b><u>2013</u></b>	<b><u>1080</u></b>	1955	1110		
505.mcf_r	1536	<b><u>3154</u></b>	<b><u>787</u></b>	3147	789			384	<b><u>634</u></b>	<b><u>979</u></b>	615	1010		
520.omnetpp_r	1536	<b><u>2120</u></b>	<b><u>951</u></b>	2119	951			1536	1859	1080	<b><u>1860</u></b>	<b><u>1080</u></b>		
523.xalancbmk_r	1536	<b><u>1375</u></b>	<b><u>1180</u></b>	1375	1180			1536	999	1620	<b><u>1002</u></b>	<b><u>1620</u></b>		
525.x264_r	1536	2190	1230	<b><u>2194</u></b>	<b><u>1230</u></b>			768	968	1390	<b><u>983</u></b>	<b><u>1370</u></b>		
531.deepsjeng_r	1536	<b><u>1139</u></b>	<b><u>1540</u></b>	1137	1550			1536	<b><u>1074</u></b>	<b><u>1640</u></b>	1070	1640		
541.leela_r	1536	1547	1640	<b><u>1554</u></b>	<b><u>1640</u></b>			1536	<b><u>1397</u></b>	<b><u>1820</u></b>	1391	1830		
548.exchange2_r	1536	<b><u>2302</u></b>	<b><u>1750</u></b>	2301	1750			1536	<b><u>1532</u></b>	<b><u>2630</u></b>	1532	2630		
557.xz_r	1536	1604	1030	<b><u>1605</u></b>	<b><u>1030</u></b>			1536	<b><u>1507</u></b>	<b><u>1100</u></b>	1501	1110		

SPECrate2017\_int\_base = 1180

SPECrate2017\_int\_peak = 1420

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

Processes were assigned to specific processors using 'pbind' commands. The config file option 'submit' was used, along with a list of processors in the 'BIND' variable, to generate the pbind commands. (For details, please see the config file.)

## Operating System Notes

### Shell Environments:

ulimit -s 131072 was used to limit the space consumed by the stack (and therefore make more space available to the heap).

The "Logical Domains Manager" service was turned off using the command "svcadm disable ldmd".

### System Tunables:

(/etc/system parameters)

autoup = 86400

Causes pages older than the listed number of seconds to be written by fsflush.

doiflush = 0

Controls whether file system metadata syncs will be executed during fsflush invocations.

dopageflush = 0

Controls whether memory is examined for modified pages during fsflush invocations.

zfs:zfs\_arc\_max=1073741824

Determines the maximum size of the ZFS Adaptive Replacement Cache (ARC).



# SPEC CPU2017 Integer Rate Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

**Fujitsu**  
**Fujitsu SPARC M12-2S**

SPECrate2017\_int\_base = 1180

SPECrate2017\_int\_peak = 1420

**CPU2017 License:** 19  
**Test Sponsor:** Fujitsu  
**Tested by:** Fujitsu

**Test Date:** Nov-2017  
**Hardware Availability:** Apr-2017  
**Software Availability:** Jul-2017

## General Notes

The Building Block (BB) is just a Fujitsu SPARC M12-2S that is the basic unit to be expanded as if stacking up children's blocks.

File System:

tmpfs: output\_root was used to put run directories in /tmp/cpu2017  
zfs: operating system

Binaries were compiled on a system with 2x SPARC64 XII CPU + 1TB Memory using Oracle Solaris 11.3 SRU 24.4

## Platform Notes

Firmware Settings:

(XSCF operations)

Set High Speed Mode via XSCF command "sethsmode -s on".

Sysinfo program /export/cpu2017/bin/sysinfo

Rev: r5797 of 2017-06-14 96c45e4568ad54c135fd618bcc091c0f

running on H2S-230-D0 Fri Nov 3 08:33:52 2017

SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see

<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /usr/sbin/psrinfo

SPARC64-XII (chipid 0, clock 4250 MHz)  
SPARC64-XII (chipid 1, clock 4250 MHz)  
SPARC64-XII (chipid 10, clock 4250 MHz)  
SPARC64-XII (chipid 11, clock 4250 MHz)  
SPARC64-XII (chipid 12, clock 4250 MHz)  
SPARC64-XII (chipid 13, clock 4250 MHz)  
SPARC64-XII (chipid 14, clock 4250 MHz)  
SPARC64-XII (chipid 15, clock 4250 MHz)  
SPARC64-XII (chipid 2, clock 4250 MHz)  
SPARC64-XII (chipid 3, clock 4250 MHz)  
SPARC64-XII (chipid 4, clock 4250 MHz)  
SPARC64-XII (chipid 5, clock 4250 MHz)  
SPARC64-XII (chipid 6, clock 4250 MHz)  
SPARC64-XII (chipid 7, clock 4250 MHz)  
SPARC64-XII (chipid 8, clock 4250 MHz)  
SPARC64-XII (chipid 9, clock 4250 MHz)

16 chips  
1536 threads  
4250 MHz

From kstat: 192 cores

(Continued on next page)



# SPEC CPU2017 Integer Rate Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

**Fujitsu**  
**Fujitsu SPARC M12-2S**

SPECrate2017\_int\_base = 1180

SPECrate2017\_int\_peak = 1420

**CPU2017 License:** 19  
**Test Sponsor:** Fujitsu  
**Tested by:** Fujitsu

**Test Date:** Nov-2017  
**Hardware Availability:** Apr-2017  
**Software Availability:** Jul-2017

## Platform Notes (Continued)

From prtconf: 8375296 Megabytes

```
/etc/release:
  Oracle Solaris 11.3 SPARC
uname -a:
  SunOS H2S-230-D0 5.11 11.3 sun4v sparc sun4v
```

```
disk: df -h /export/cpu2017
Filesystem      Size      Used    Available Capacity  Mounted on
rpool/export    547G     118G      106G         53%    /export
```

(End of data from sysinfo program)

## Compiler Version Notes

```
=====  
CXXC 520.omnetpp_r(base) 523.xalancbmk_r(base, peak) 531.deepsjeng_r(base)  
541.leela_r(base)
```

```
-----  
CC: Studio 12.6 Sun C++ 5.15 SunOS_sparc 2017/05/30  
-----
```

```
=====  
CXXC 520.omnetpp_r(peak) 531.deepsjeng_r(peak) 541.leela_r(peak)
```

```
-----  
CC: Studio 12.6 Sun C++ 5.15 SunOS_sparc 2017/05/30  
-----
```

```
=====  
CC 500.perlbench_r(base) 502.gcc_r(base) 505.mcf_r(base) 525.x264_r(base)  
557.xz_r(base)
```

```
-----  
cc: Studio 12.6 Sun C 5.15 SunOS_sparc 2017/05/30  
-----
```

```
=====  
CC 500.perlbench_r(peak) 502.gcc_r(peak) 505.mcf_r(peak) 525.x264_r(peak)  
557.xz_r(peak)
```

```
-----  
cc: Studio 12.6 Sun C 5.15 SunOS_sparc 2017/05/30  
-----
```

```
=====  
FC 548.exchange2_r(base)
```

(Continued on next page)



# SPEC CPU2017 Integer Rate Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Fujitsu  
Fujitsu SPARC M12-2S

SPECrate2017\_int\_base = 1180

SPECrate2017\_int\_peak = 1420

CPU2017 License: 19  
Test Sponsor: Fujitsu  
Tested by: Fujitsu

Test Date: Nov-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017

## Compiler Version Notes (Continued)

f90: Studio 12.6 Fortran 95 8.8 SunOS\_sparc 2017/05/30

FC 548.exchange2\_r(peak)

f90: Studio 12.6 Fortran 95 8.8 SunOS\_sparc 2017/05/30

## Base Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

Fortran benchmarks:

f90

## Base Portability Flags

500.perlbenc\_r: -DSPEC\_SOLARIS\_SPARC  
502.gcc\_r: -D\_FILE\_OFFSET\_BITS=64  
505.mcf\_r: -D\_FILE\_OFFSET\_BITS=64  
520.omnetpp\_r: -DSPEC\_GCC\_MANGLE -D\_FILE\_OFFSET\_BITS=64  
523.xalancbmk\_r: -DSPEC\_SOLARIS -D\_FILE\_OFFSET\_BITS=64  
525.x264\_r: -D\_FILE\_OFFSET\_BITS=64  
531.deepsjeng\_r: -D\_FILE\_OFFSET\_BITS=64  
541.leela\_r: -D\_FILE\_OFFSET\_BITS=64  
548.exchange2\_r: -D\_FILE\_OFFSET\_BITS=64  
557.xz\_r: -D\_FILE\_OFFSET\_BITS=64

## Base Optimization Flags

C benchmarks:

-m32 -fast -xtarget=sparc64xii -xipo=2 -xpagesize=4M  
-xsegment\_align=4M -xthroughput -xalias\_level=weak

C++ benchmarks:

-m32 -fast -xtarget=sparc64xii -xipo=2 -xpagesize=4M

(Continued on next page)



# SPEC CPU2017 Integer Rate Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Fujitsu  
Fujitsu SPARC M12-2S

SPECrate2017\_int\_base = 1180

SPECrate2017\_int\_peak = 1420

CPU2017 License: 19  
Test Sponsor: Fujitsu  
Tested by: Fujitsu

Test Date: Nov-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017

## Base Optimization Flags (Continued)

C++ benchmarks (continued):

-xsegment\_align=4M -xthroughput -std=c++03 -lfast

Fortran benchmarks:

-m32 -fast -xtarget=sparc64xii -xipo=2 -xpagesize=4M  
-xsegment\_align=4M -xthroughput

## Base Other Flags

C benchmarks:

-xjobs=8

C++ benchmarks:

-xjobs=8

Fortran benchmarks:

-xjobs=8

## Peak Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

Fortran benchmarks:

f90

## Peak Portability Flags

500.perlbench\_r: -DSPEC\_SOLARIS\_SPARC  
502.gcc\_r: -D\_FILE\_OFFSET\_BITS=64  
505.mcf\_r: -D\_FILE\_OFFSET\_BITS=64  
520.omnetpp\_r: -D\_FILE\_OFFSET\_BITS=64  
523.xalancbmk\_r: -DSPEC\_SOLARIS -D\_FILE\_OFFSET\_BITS=64  
525.x264\_r: -D\_FILE\_OFFSET\_BITS=64  
531.deepsjeng\_r: -D\_FILE\_OFFSET\_BITS=64  
541.leela\_r: -D\_FILE\_OFFSET\_BITS=64

(Continued on next page)



# SPEC CPU2017 Integer Rate Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Fujitsu  
Fujitsu SPARC M12-2S

SPECrate2017\_int\_base = 1180

SPECrate2017\_int\_peak = 1420

CPU2017 License: 19  
Test Sponsor: Fujitsu  
Tested by: Fujitsu

Test Date: Nov-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017

## Peak Portability Flags (Continued)

548.exchange2\_r: -D\_FILE\_OFFSET\_BITS=64  
557.xz\_r: -D\_FILE\_OFFSET\_BITS=64

## Peak Optimization Flags

C benchmarks:

```
500.perlbench_r: -xprofile=collect:./feedback -xprofile=use:./feedback -m32
-fast -xtarget=sparc64xii -xipo=2 -xpagesize=256M
-xsegment_align=256M -xthroughput -xO4
-xalias_level=layout -xinline_param=level:3 -lfast
```

```
502.gcc_r: -xprofile=collect:./feedback -xprofile=use:./feedback -m32
-fast -xtarget=sparc64xii -xipo=2 -xpagesize=256M
-xsegment_align=256M -xthroughput -xtarget=sparc64xplus
-xipo=1 -xinline_param=level:3 -xprefetch=no%auto
-xthroughput=no -lfast
```

```
505.mcf_r: -xprofile=collect:./feedback -xprofile=use:./feedback -m32
-fast -xtarget=sparc64xii -xipo=2 -xpagesize=256M
-xsegment_align=256M -xthroughput -xalias_level=strong
-xprefetch=no%auto -xthroughput=no
```

```
525.x264_r: -xprofile=collect:./feedback -xprofile=use:./feedback -m32
-fast -xtarget=sparc64xii -xipo=2 -xpagesize=256M
-xsegment_align=256M -xthroughput -xunroll=3
-xprefetch=no%auto -W2,-Afully_unroll:always=on
```

```
557.xz_r: -xprofile=collect:./feedback -xprofile=use:./feedback -m32
-fast -xtarget=sparc64xii -xipo=2 -xpagesize=256M
-xsegment_align=256M -xthroughput -xalias_level=std
-xprefetch=latx:0.4
```

C++ benchmarks:

```
520.omnetpp_r: -xprofile=collect:./feedback -xprofile=use:./feedback -m32
-fast -xtarget=sparc64xii -xipo=2 -xpagesize=256M
-xsegment_align=256M -xthroughput -xalias_level=compatible
-xprefetch=latx:0.4 -library=stdcxx4 -template=extdef
-lfast
```

```
523.xalancbmk_r: -m32 -fast -xtarget=sparc64xii -xipo=2 -xpagesize=256M
-xsegment_align=256M -xthroughput -xprefetch=no%auto
-library=stlport4 -lfast
```

(Continued on next page)



# SPEC CPU2017 Integer Rate Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Fujitsu  
Fujitsu SPARC M12-2S

SPECrate2017\_int\_base = 1180

SPECrate2017\_int\_peak = 1420

CPU2017 License: 19  
Test Sponsor: Fujitsu  
Tested by: Fujitsu

Test Date: Nov-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017

## Peak Optimization Flags (Continued)

```
53l.deepsjeng_r: -xprofile=collect:./feedback -xprofile=use:./feedback -m32  
-fast -xtarget=sparc64xii -xipo=2 -xpagesize=256M  
-xsegment_align=256M -xthroughput -xalias_level=compatible  
-xinline_param=level:1 -xunroll=2 -xprefetch=no%auto  
-std=c++03
```

```
54l.leela_r: -xprofile=collect:./feedback -xprofile=use:./feedback -m32  
-fast -xtarget=sparc64xii -xipo=2 -xpagesize=256M  
-xsegment_align=256M -xthroughput  
-xinline_param=max_growth:500 -xprefetch=no%auto  
-xthroughput=no -Wc,-Qiselect-funcalign=4  
-Qoption iropt -Afully_unroll:always=on -std=c++03
```

Fortran benchmarks:

```
-xprofile=collect:./feedback -xprofile=use:./feedback -m32 -fast  
-xtarget=sparc64xii -xipo=2 -xpagesize=256M -xsegment_align=256M  
-xthroughput -xtarget=sparc64xplus -xprefetch=no%auto  
-Qoption iropt -Afully_unroll:always=on
```

## Peak Other Flags

C benchmarks:

```
-xjobs=8
```

C++ benchmarks:

```
-xjobs=8
```

Fortran benchmarks:

```
-xjobs=8
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/Oracle-Developer-Studio12.6.html>

<http://www.spec.org/cpu2017/flags/Fujitsu-M12-2S.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/Oracle-Developer-Studio12.6.xml>

<http://www.spec.org/cpu2017/flags/Fujitsu-M12-2S.xml>





# SPEC CPU2017 Integer Rate Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Fujitsu  
Fujitsu SPARC M12-2S

SPECrate2017\_int\_base = 1180

SPECrate2017\_int\_peak = 1420

**CPU2017 License:** 19  
**Test Sponsor:** Fujitsu  
**Tested by:** Fujitsu

**Test Date:** Nov-2017  
**Hardware Availability:** Apr-2017  
**Software Availability:** Jul-2017

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU2017 v1.0.2 on 2017-11-02 19:33:50-0400.  
Report generated on 2018-10-31 14:03:29 by CPU2017 PDF formatter v6067.  
Originally published on 2017-12-26.