



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation


**Fsas Technologies Inc.**  
(Test Sponsor: Fujitsu)  
PRIMEQUEST 4400E, Intel Xeon Platinum 8580,  
2.00GHz

SPECrate®2017\_int\_base = 1020

SPECrate®2017\_int\_peak = Not Run

**CPU2017 License:** 19  
**Test Sponsor:** Fujitsu  
**Tested by:** Fsas Technologies Inc.

**Test Date:** Jan-2026  
**Hardware Availability:** Mar-2026  
**Software Availability:** May-2025



## Hardware

CPU Name: Intel Xeon Platinum 8580  
Max MHz: 4000  
Nominal: 2000  
Enabled: 120 cores, 2 chips, 2 threads/core  
Orderable: 1,2 chips  
Cache L1: 32 KB I + 48 KB D on chip per core  
L2: 2 MB I+D on chip per core  
L3: 300 MB I+D on chip per chip  
Other: None  
Memory: 1 TB (16 x 64 GB 2Rx4 PC5-5600B-R)  
Storage: 1 x 960 GB M.2 SATA SSD  
Other: CPU Cooling: Air

## Software

OS: Red Hat Enterprise Linux 9.6 (Plow)  
5.14.0-570.12.1.el9\_6.x86\_64  
Compiler: C/C++: Version 2024.1 of Intel oneAPI DPC++/C++  
Compiler for Linux;  
Fortran: Version 2024.1 of Intel Fortran Compiler  
for Linux;  
Parallel: No  
Firmware: Fujitsu BIOS Version V1.0.0.0 R2.9.0 for  
D3986-A1x. Released Mar-2026  
File System: xfs  
System State: Run level 5 (multi-user with GUI)  
Base Pointers: 64-bit  
Peak Pointers: Not Applicable  
Other: None  
Power Management: BIOS set to prefer performance at  
the cost of additional power usage



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Fsas Technologies Inc.

(Test Sponsor: Fujitsu)

PRIMEQUEST 4400E, Intel Xeon Platinum 8580, 2.00GHz

SPECrate®2017\_int\_base = 1020

SPECrate®2017\_int\_peak = Not Run

CPU2017 License: 19

Test Sponsor: Fujitsu

Tested by: Fsas Technologies Inc.

Test Date: Jan-2026

Hardware Availability: Mar-2026

Software Availability: May-2025

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
500.perlbench_r	240	<b>478</b>	<b>800</b>	484	790	477	800							
502.gcc_r	240	<b>416</b>	<b>818</b>	415	818	416	817							
505.mcf_r	240	254	1530	<b>254</b>	<b>1530</b>	254	1530							
520.omnetpp_r	240	<b>503</b>	<b>627</b>	503	626	502	627							
523.xalancbmk_r	240	183	1380	181	1400	<b>181</b>	<b>1400</b>							
525.x264_r	240	<b>193</b>	<b>2170</b>	194	2170	193	2180							
531.deepsjeng_r	240	<b>363</b>	<b>758</b>	363	759	365	754							
541.leela_r	240	551	721	<b>551</b>	<b>721</b>	552	720							
548.exchange2_r	240	<b>281</b>	<b>2240</b>	281	2240	282	2230							
557.xz_r	240	493	526	494	525	<b>493</b>	<b>526</b>							

SPECrate®2017\_int\_base = 1020

SPECrate®2017\_int\_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Notes

SPEC has ruled that the compiler used for this result was performing a compilation that specifically improves the performance of the 523.xalancbmk\_r / 623.xalancbmk\_s benchmarks using a priori knowledge of the SPEC code and dataset to perform a transformation that has narrow applicability.

In order to encourage optimizations that have wide applicability (see rule 1.4 [https://www.spec.org/cpu2017/Docs/runrules.html#rule\\_1.4](https://www.spec.org/cpu2017/Docs/runrules.html#rule_1.4)), SPEC will no longer publish results using this optimization.

This result is left in the SPEC results database for historical reference.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Environment Variables Notes

Environment variables set by runcpu before the start of the run:

```
LD_LIBRARY_PATH =
"/home/benchmark/cpu2017/lib/intel64:/home/benchmark/cpu2017/lib/ia32:/home/benchmark/cpu2017/je5.0.1-32"
MALLOC_CONF = "retain:true"
```



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Fsas Technologies Inc.**

(Test Sponsor: Fujitsu)

PRIMEQUEST 4400E, Intel Xeon Platinum 8580,  
2.00GHz

SPECrate®2017\_int\_base = 1020

SPECrate®2017\_int\_peak = Not Run

**CPU2017 License:** 19

**Test Sponsor:** Fujitsu

**Tested by:** Fsas Technologies Inc.

**Test Date:** Jan-2026

**Hardware Availability:** Mar-2026

**Software Availability:** May-2025

## General Notes

Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM  
 memory using Red Hat Enterprise Linux 8.4  
 Transparent Huge Pages enabled by default  
 Prior to runcpu invocation  
 Filesystem page cache synced and cleared with:  
 sync; echo 3> /proc/sys/vm/drop\_caches  
 runcpu command invoked through numactl i.e.:  
 numactl --interleave=all runcpu <etc>  
 NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)  
 is mitigated in the system as tested and documented.  
 Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)  
 is mitigated in the system as tested and documented.  
 Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)  
 is mitigated in the system as tested and documented.

## Platform Notes

BIOS configuration:  
 DCU Streamer Prefetcher = Disabled  
 UPI Link Frequency Select = 14.4GT/s  
 HWPM Support = Disabled  
 CPU Performance Boost = Aggressive  
 SNC (Sub NUMA) = Enable SNC2

Sysinfo program /home/benchmark/cpu2017/bin/sysinfo  
 Rev: r6732 of 2022-11-07 fe91c89b7ed5c36ae2c92cc097bec197  
 running on localhost.localdomain Tue Jan 6 09:50:16 2026

SUT (System Under Test) info as seen by some common utilities.

-----  
 Table of contents  
 -----

1. uname -a
2. w
3. Username
4. ulimit -a
5. sysinfo process ancestry
6. /proc/cpuinfo
7. lscpu
8. numactl --hardware
9. /proc/meminfo
10. who -r
11. Systemd service manager version: systemd 252 (252-51.el9)
12. Services, from systemctl list-unit-files
13. Linux kernel boot-time arguments, from /proc/cmdline
14. cpupower frequency-info
15. tuned-adm active
16. sysctl
17. /sys/kernel/mm/transparent\_hugepage
18. /sys/kernel/mm/transparent\_hugepage/khugepaged
19. OS release
20. Disk information
21. /sys/devices/virtual/dmi/id
22. dmidecode
23. BIOS

-----  
 -----

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Fsas Technologies Inc.**

(Test Sponsor: Fujitsu)

PRIMEQUEST 4400E, Intel Xeon Platinum 8580,  
2.00GHz

SPECrate®2017\_int\_base = 1020

SPECrate®2017\_int\_peak = Not Run

**CPU2017 License:** 19

**Test Sponsor:** Fujitsu

**Tested by:** Fsas Technologies Inc.

**Test Date:** Jan-2026

**Hardware Availability:** Mar-2026

**Software Availability:** May-2025

## Platform Notes (Continued)

1. `uname -a`  
Linux localhost.localdomain 5.14.0-570.12.1.el9\_6.x86\_64 #1 SMP PREEMPT\_DYNAMIC Fri Apr 4 10:41:31 EDT 2025  
x86\_64 x86\_64 x86\_64 GNU/Linux

2. `w`  
09:50:16 up 4 min, 2 users, load average: 0.25, 0.15, 0.07  
USER TTY LOGIN@ IDLE JCPU PCPU WHAT  
root seat0 09:49 0.00s 0.00s 0.00s /usr/libexec/gdm-wayland-session --register-session  
gnome-session  
root tty2 09:49 4:13 0.03s 0.03s /usr/libexec/gnome-session-binary

3. `Username`  
From environment variable \$USER: root

4. `ulimit -a`  
real-time non-blocking time (microseconds, -R) unlimited  
core file size (blocks, -c) unlimited  
data seg size (kbytes, -d) unlimited  
scheduling priority (-e) 0  
file size (blocks, -f) unlimited  
pending signals (-i) 4124572  
max locked memory (kbytes, -l) 8192  
max memory size (kbytes, -m) unlimited  
open files (-n) 1024  
pipe size (512 bytes, -p) 8  
POSIX message queues (bytes, -q) 819200  
real-time priority (-r) 0  
stack size (kbytes, -s) unlimited  
cpu time (seconds, -t) unlimited  
max user processes (-u) 4124572  
virtual memory (kbytes, -v) unlimited  
file locks (-x) unlimited

5. `sysinfo process ancestry`  
/usr/lib/systemd/systemd rhgb --switched-root --system --deserialize 31  
/usr/lib/systemd/systemd --user  
/usr/libexec/gnome-terminal-server  
bash  
bash  
runcpu --nobuild --action validate --define default-platform-flags --define numcopies=240 -c  
ic2024.1-lin-sapphirerapids-rate-20240308.cfg --define smt-on --define cores=120 --define physicalfirst  
--define invoke\_with\_interleave --define drop\_caches --tune base -o all intrate  
runcpu --nobuild --action validate --define default-platform-flags --define numcopies=240 --configfile  
ic2024.1-lin-sapphirerapids-rate-20240308.cfg --define smt-on --define cores=120 --define physicalfirst  
--define invoke\_with\_interleave --define drop\_caches --tune base --output\_format all --nopower --runmode  
rate --tune base --size reframe intrate --nopreenv --note-preenv --logfile  
\$SPEC/tmp/CPU2017.001/temlogs/preenv.intrate.001.0.log --lognum 001.0 --from\_runcpu 2  
specperl \$SPEC/bin/sysinfo  
\$SPEC = /home/benchmark/cpu2017

6. `/proc/cpuinfo`  
model name : INTEL(R) XEON(R) PLATINUM 8580  
vendor\_id : GenuineIntel  
cpu family : 6  
model : 207

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Fsas Technologies Inc.**

(Test Sponsor: Fujitsu)

**PRIMEQUEST 4400E, Intel Xeon Platinum 8580,  
2.00GHz**

**SPECrate®2017\_int\_base = 1020**

**SPECrate®2017\_int\_peak = Not Run**

**CPU2017 License:** 19

**Test Sponsor:** Fujitsu

**Tested by:** Fsas Technologies Inc.

**Test Date:** Jan-2026

**Hardware Availability:** Mar-2026

**Software Availability:** May-2025

## Platform Notes (Continued)

```

stepping      : 2
microcode     : 0x210002b3
bugs          : spectre_v1 spectre_v2 spec_store_bypass swapgs eibrs_pbrsb bhi
cpu cores     : 60
siblings      : 120
2 physical ids (chips)
240 processors (hardware threads)
physical id 0: core ids 0-59
physical id 1: core ids 0-59
physical id 0: apicids 0-119
physical id 1: apicids 128-247

```

Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for virtualized systems. Use the above data carefully.

### 7. lscpu

From lscpu from util-linux 2.37.4:

```

Architecture:          x86_64
CPU op-mode(s):        32-bit, 64-bit
Address sizes:         46 bits physical, 57 bits virtual
Byte Order:            Little Endian
CPU(s):                240
On-line CPU(s) list:  0-239
Vendor ID:             GenuineIntel
BIOS Vendor ID:       Intel(R) Corporation
Model name:            INTEL(R) XEON(R) PLATINUM 8580
BIOS Model name:      INTEL(R) XEON(R) PLATINUM 8580
CPU family:            6
Model:                 207
Thread(s) per core:   2
Core(s) per socket:   60
Socket(s):             2
Stepping:              2
CPU(s) scaling MHz:   28%
CPU max MHz:           4000.0000
CPU min MHz:           800.0000
BogoMIPS:              4000.00
Flags:                 fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
pdpelgb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good
nopl xtopology nonstop_tsc cpuid aperfmperf tsc_known_freq pni
pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 sse3 sdbg fma cx16
xtpr pdcm pcid dca sse4_1 sse4_2 x2apic movbe popcnt
tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm
3dnowprefetch cpuid_fault epb cat_l3 cat_l2 cdp_l3 intel_ppin cdp_l2
ssbd mba ibrs ibpb stibp ibrs_enhanced tpr_shadow flexpriority ept
vpid ept_ad fsgsbase tsc_adjust bml avx2 smep bmi2 erms invpcid cqm
rdt_a avx512f avx512dq rdseed adx smap avx512ifma clflushopt clwb
intel_pt avx512cd sha_ni avx512bw avx512v1 xsaveopt xsavec xgetbv1
xsave cqm_llc cqm_occup_llc cqm_mbm_total cqm_mbm_local
split_lock_detect avx_vnni avx512_bf16 wbnoinvd dtherm ida arat pln
pts vnni avx512vbmi umip pku ospke waitpkg avx512_vbmi2 gfni vaes
vpclmulqdq avx512_vnni avx512_bitalg tme avx512_vpopcntdq la57 rdpid
bus_lock_detect cldemote movdiri movdir64b enqcmd fsrm md_clear
serialize tsxldtrk pconfig arch_lbr ibt amx_bf16 avx512_fp16 amx_tile
amx_int8 flush_lld arch_capabilities
Virtualization:       VT-x
L1d cache:            5.6 MiB (120 instances)
L1i cache:            3.8 MiB (120 instances)

```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Fsas Technologies Inc.**

(Test Sponsor: Fujitsu)

PRIMEQUEST 4400E, Intel Xeon Platinum 8580, 2.00GHz

SPECrate®2017\_int\_base = 1020

SPECrate®2017\_int\_peak = Not Run

**CPU2017 License:** 19

**Test Sponsor:** Fujitsu

**Tested by:** Fsas Technologies Inc.

**Test Date:** Jan-2026

**Hardware Availability:** Mar-2026

**Software Availability:** May-2025

## Platform Notes (Continued)

```

L2 cache:                240 MiB (120 instances)
L3 cache:                600 MiB (2 instances)
NUMA node(s):           4
NUMA node0 CPU(s):      0-29,120-149
NUMA node1 CPU(s):      30-59,150-179
NUMA node2 CPU(s):      60-89,180-209
NUMA node3 CPU(s):      90-119,210-239
Vulnerability Gather data sampling: Not affected
Vulnerability Itlb multihit:       Not affected
Vulnerability Lltf:                 Not affected
Vulnerability Mds:                   Not affected
Vulnerability Meltdown:              Not affected
Vulnerability Mmio stale data:       Not affected
Vulnerability Reg file data sampling: Not affected
Vulnerability Retbleed:              Not affected
Vulnerability Spec rstack overflow:   Not affected
Vulnerability Spec store bypass:     Mitigation; Speculative Store Bypass disabled via prctl
Vulnerability Spectre v1:            Mitigation; usercopy/swaps barriers and __user pointer sanitization
Vulnerability Spectre v2:           Mitigation; Enhanced / Automatic IBRS; IBPB conditional; RSB filling;
PBRSB-eIBRS SW sequence; BHI BHI_DIS_S
Vulnerability Srbds:                 Not affected
Vulnerability Tsx async abort:       Not affected

```

From lscpu --cache:

NAME	ONE-SIZE	ALL-SIZE	WAYS	TYPE	LEVEL	SETS	PHY-LINE	COHERENCY-SIZE
L1d	48K	5.6M	12	Data	1	64	1	64
L1i	32K	3.8M	8	Instruction	1	64	1	64
L2	2M	240M	16	Unified	2	2048	1	64
L3	300M	600M	20	Unified	3	245760	1	64

8. numactl --hardware

NOTE: a numactl 'node' might or might not correspond to a physical chip.

```

available: 4 nodes (0-3)
node 0 cpus: 0-29,120-149
node 0 size: 257172 MB
node 0 free: 255704 MB
node 1 cpus: 30-59,150-179
node 1 size: 258032 MB
node 1 free: 257074 MB
node 2 cpus: 60-89,180-209
node 2 size: 257987 MB
node 2 free: 256457 MB
node 3 cpus: 90-119,210-239
node 3 size: 258016 MB
node 3 free: 256826 MB
node distances:
node    0    1    2    3
 0:   10   12   21   21
 1:   12   10   21   21
 2:   21   21   10   12
 3:   21   21   12   10

```

9. /proc/meminfo

MemTotal: 1055958092 kB

10. who -r

run-level 5 Jan 6 09:46

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Fsas Technologies Inc.**  
(Test Sponsor: Fujitsu)  
**PRIMEQUEST 4400E, Intel Xeon Platinum 8580,  
2.00GHz**

**SPECrate®2017\_int\_base = 1020**

**SPECrate®2017\_int\_peak = Not Run**

**CPU2017 License:** 19  
**Test Sponsor:** Fujitsu  
**Tested by:** Fsas Technologies Inc.

**Test Date:** Jan-2026  
**Hardware Availability:** Mar-2026  
**Software Availability:** May-2025

## Platform Notes (Continued)

-----  
11. Systemd service manager version: systemd 252 (252-51.el9)  
Default Target Status  
graphical running

-----  
12. Services, from systemctl list-unit-files  
STATE UNIT FILES  
enabled ModemManager NetworkManager NetworkManager-dispatcher NetworkManager-wait-online  
accounts-daemon atd auditd avahi-daemon bluetooth crond cups dbus-broker firewallld gdm  
getty@ insights-client-boot irqbalance iscsi-onboot iscsi-starter kdump libstoragemgmt  
lm\_sensors low-memory-monitor lvm2-monitor mcelog mdmonitor microcode multipathd  
nis-domainname nvme-fc-boot-connections ostree-remount pmcd pmie pmlogger qemu-guest-agent  
rhsmcertd rsyslog rtkit-daemon selinux-autorelabel-mark smartd sshd sssd  
switcheroo-control sysstat systemd-boot-update systemd-network-generator systemd-pstore  
tuned udisks2 upower vgauthd vmtoolsd  
enabled-runtime systemd-remount-fs  
disabled arp-ethers blk-availability brltty canberra-system-bootup canberra-system-shutdown  
canberra-system-shutdown-reboot chrony-wait chronyd chronyd-restricted cni-dhcp  
console-getty cpupower cups-browsed dbus-daemon debug-shell dnf-system-upgrade dnsmasq  
fancontrol grafana-server iprdump iprinit iprupdate iscsi-init iscsid iscsiui kpatch  
kvm\_stat ledmon lvm-devices-import man-db-restart-cache-update netavark-dhcp-proxy  
netavark-firewalld-reload nftables nvme-autoconnect ostree-readonly-sysroot-migration  
ostree-state-overlay@ pcp-geolocate pesign pmfind pmie\_farm pmlogger\_farm pmproxy podman  
podman-auto-update podman-clean-transient podman-kube@ podman-restart postfix powertop  
psacct ras-mc-ctl rasdaemon rdisc rhcd rhsm rhsm-facts rpmbd-rebuild rrdcached  
selinux-check-proper-disable serial-getty@ speech-dispatcherd sshd-keygen@  
systemd-boot-check-no-failures systemd-sysext trace-cmd tuned-ppd wpa\_supplicant  
indirect iscsi spice-vdagentd sssd-autofs sssd-kcm sssd-nss sssd-pac sssd-pam sssd-ssh sssd-sudo  
systemd-sysupdate systemd-sysupdate-reboot

-----  
13. Linux kernel boot-time arguments, from /proc/cmdline  
BOOT\_IMAGE=(hd0,gpt2)/vmlinuz-5.14.0-570.12.1.el9\_6.x86\_64  
root=/dev/mapper/rhel-root  
ro  
crashkernel=1G-4G:192M,4G-64G:256M,64G-:512M  
resume=/dev/mapper/rhel-swap  
rd.lvm.lv=rhel/root  
rd.lvm.lv=rhel/swap  
rhgb  
quiet

-----  
14. cpupower frequency-info  
analyzing CPU 25:  
current policy: frequency should be within 800 MHz and 4.00 GHz.  
The governor "schedutil" may decide which speed to use  
within this range.  
boost state support:  
Supported: yes  
Active: yes

-----  
15. tuned-adm active  
Current active profile: balanced

-----  
16. sysctl

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Fsas Technologies Inc.**

(Test Sponsor: Fujitsu)

PRIMEQUEST 4400E, Intel Xeon Platinum 8580,  
2.00GHz

SPECrate®2017\_int\_base = 1020

SPECrate®2017\_int\_peak = Not Run

**CPU2017 License:** 19

**Test Sponsor:** Fujitsu

**Tested by:** Fsas Technologies Inc.

**Test Date:** Jan-2026

**Hardware Availability:** Mar-2026

**Software Availability:** May-2025

## Platform Notes (Continued)

```

kernel.numa_balancing          1
kernel.randomize_va_space     2
vm.compaction_proactiveness   20
vm.dirty_background_bytes     0
vm.dirty_background_ratio     10
vm.dirty_bytes                 0
vm.dirty_expire_centisecs     3000
vm.dirty_ratio                 20
vm.dirty_writeback_centisecs  500
vm.dirtytime_expire_seconds   43200
vm.extfrag_threshold          500
vm.min_unmapped_ratio         1
vm.nr_hugepages                0
vm.nr_hugepages_mempolicy     0
vm.nr_overcommit_hugepages    0
vm.swappiness                  60
vm.watermark_boost_factor     15000
vm.watermark_scale_factor     10
vm.zone_reclaim_mode          0

```

```

-----
17. /sys/kernel/mm/transparent_hugepage
defrag          always defer defer+advise [advise] never
enabled         [always] advise never
hpage_pmd_size 2097152
shmem_enabled   always within_size advise [never] deny force

```

```

-----
18. /sys/kernel/mm/transparent_hugepage/khugepaged
alloc_sleep_millisecs  60000
defrag                 1
max_ptes_none          511
max_ptes_shared        256
max_ptes_swap          64
pages_to_scan          4096
scan_sleep_millisecs   10000

```

```

-----
19. OS release
From /etc/*-release /etc/*-version
os-release      Red Hat Enterprise Linux 9.6 (Plow)
redhat-release  Red Hat Enterprise Linux release 9.6 (Plow)
system-release  Red Hat Enterprise Linux release 9.6 (Plow)

```

```

-----
20. Disk information
SPEC is set to: /home/benchmark/cpu2017
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/mapper/rhel-home xfs  819G  27G  793G  4% /home

```

```

-----
21. /sys/devices/virtual/dmi/id
Vendor:      FUJITSU
Product:     PRIMEQUEST 4400E
Product Family: SERVER
Serial:      xxxxxxxxxxxx

```

```

-----
22. dmidecode
Additional information from dmidecode 3.6 follows.  WARNING: Use caution when you interpret this section.

```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Fsas Technologies Inc.**  
(Test Sponsor: Fujitsu)  
PRIMEQUEST 4400E, Intel Xeon Platinum 8580,  
2.00GHz

SPECrate®2017\_int\_base = 1020

SPECrate®2017\_int\_peak = Not Run

**CPU2017 License:** 19  
**Test Sponsor:** Fujitsu  
**Tested by:** Fsas Technologies Inc.

**Test Date:** Jan-2026  
**Hardware Availability:** Mar-2026  
**Software Availability:** May-2025

## Platform Notes (Continued)

The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

Memory:  
16x Samsung M321R8GA0PB0-CWMMXH 64 GB 2 rank 5600

-----  
23. BIOS  
(This section combines info from /sys/devices and dmidecode.)  
BIOS Vendor: FUJITSU  
BIOS Version: V1.0.0.0 R2.9.0 for D3986-A1x  
BIOS Date: 08/22/2025  
BIOS Revision: 2.9  
Firmware Revision: 1.91

## Compiler Version Notes

-----  
C | 500.perlbench\_r(base) 502.gcc\_r(base) 505.mcf\_r(base) 525.x264\_r(base) 557.xz\_r(base)  
-----

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2024.1.0 Build 20240308  
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.

-----  
C++ | 520.omnetpp\_r(base) 523.xalancbmk\_r(base) 531.deepsjeng\_r(base) 541.leela\_r(base)  
-----

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2024.1.0 Build 20240308  
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.

-----  
Fortran | 548.exchange2\_r(base)  
-----

Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version 2024.1.0 Build 20240308  
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.

## Base Compiler Invocation

C benchmarks:  
icx

C++ benchmarks:  
icpx

Fortran benchmarks:  
ifx



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Fsas Technologies Inc.**

(Test Sponsor: Fujitsu)

PRIMEQUEST 4400E, Intel Xeon Platinum 8580,  
2.00GHz

SPECrate®2017\_int\_base = 1020

SPECrate®2017\_int\_peak = Not Run

**CPU2017 License:** 19

**Test Sponsor:** Fujitsu

**Tested by:** Fsas Technologies Inc.

**Test Date:** Jan-2026

**Hardware Availability:** Mar-2026

**Software Availability:** May-2025

## Base Portability Flags

```
500.perlbench_r: -DSPEC_LP64 -DSPEC_LINUX_X64
502.gcc_r: -DSPEC_LP64
505.mcf_r: -DSPEC_LP64
520.omnetpp_r: -DSPEC_LP64
523.xalancbmk_r: -DSPEC_LP64 -DSPEC_LINUX
525.x264_r: -DSPEC_LP64
531.deepsjeng_r: -DSPEC_LP64
541.leela_r: -DSPEC_LP64
548.exchange2_r: -DSPEC_LP64
557.xz_r: -DSPEC_LP64
```

## Base Optimization Flags

C benchmarks:

```
-w -std=c11 -m64 -Wl,-z,muldefs -xsapphirerapids -O3 -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-L/opt/intel/oneapi/compiler/2024.1/lib -lqkmalloc
```

C++ benchmarks:

```
-w -std=c++14 -m64 -Wl,-z,muldefs -xsapphirerapids -O3 -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-L/opt/intel/oneapi/compiler/2024.1/lib -lqkmalloc
```

Fortran benchmarks:

```
-w -m64 -Wl,-z,muldefs -xsapphirerapids -O3 -ffast-math -flto
-mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-nostandard-realloc-lhs -align array32byte -auto
-L/opt/intel/oneapi/compiler/2024.1/lib -lqkmalloc
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/Intel-ic2024-official-linux64.html>

<http://www.spec.org/cpu2017/flags/Fujitsu-Platform-Settings-V1.0-EMR-RevD.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/Intel-ic2024-official-linux64.xml>

<http://www.spec.org/cpu2017/flags/Fujitsu-Platform-Settings-V1.0-EMR-RevD.xml>

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU®2017 v1.1.9 on 2026-01-05 19:50:16-0500.

Report generated on 2026-03-02 20:49:12 by CPU2017 PDF formatter v6716.

Originally published on 2026-03-02.