



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfra Co., Ltd.  
QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087


Test Sponsor: Maginfra Co., Ltd.

Tested by: Maginfra Co., Ltd.

Test Date: Jun-2026

Hardware Availability: Dec-2025

Software Availability: Feb-2025



## Hardware

CPU Name: Intel Xeon 6507P  
Max MHz: 4300  
Nominal: 3500  
Enabled: 16 cores, 2 chips, 2 threads/core  
Orderable: 1,2 chips  
Cache L1: 64 KB I + 48 KB D on chip per core  
L2: 2 MB I+D on chip per core  
L3: 48 MB I+D on chip per chip  
Other: None  
Memory: 1 TB (16 x 64 GB 2Rx4 PC5-6400B-R)  
Storage: 1 x 1 TB NVMe SSD  
Other: CPU Cooling: Air

## Software

OS: SUSE Linux Enterprise Server 15 SP6  
6.4.0-150600.21-default  
Compiler: C/C++: Version 2025.2 of Intel oneAPI DPC++/C++  
Compiler for Linux;  
Fortran: Version 2025.2 of Intel Fortran Compiler  
for Linux;  
C/C++: Version 2024.2 of Intel oneAPI DPC++/C++  
Compiler for Linux;  
Parallel: No  
Firmware: Version 04.01.00 released Dec-2025  
File System: xfs  
System State: Run level 3 (multi-user)  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other: jemalloc memory allocator V5.0.1  
Power Management: BIOS and OS set to prefer performance  
at the cost of additional power usage.



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfra Co., Ltd.

QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087

Test Sponsor: Maginfra Co., Ltd.

Tested by: Maginfra Co., Ltd.

Test Date: Jun-2026

Hardware Availability: Dec-2025

Software Availability: Feb-2025

## Results Table

| Benchmark       | Base   |                   |                    |                   |                   |                   |                   | Peak   |                   |                    |                   |                   |                   |                   |
|-----------------|--------|-------------------|--------------------|-------------------|-------------------|-------------------|-------------------|--------|-------------------|--------------------|-------------------|-------------------|-------------------|-------------------|
|                 | Copies | Seconds           | Ratio              | Seconds           | Ratio             | Seconds           | Ratio             | Copies | Seconds           | Ratio              | Seconds           | Ratio             | Seconds           | Ratio             |
| 500.perlbench_r | 32     | <b><u>304</u></b> | <b><u>168</u></b>  | 303               | 168               | 305               | 167               | 32     | 285               | 179                | <b><u>284</u></b> | <b><u>179</u></b> | 284               | 179               |
| 502.gcc_r       | 32     | 249               | 182                | <b><u>248</u></b> | <b><u>183</u></b> | 246               | 184               | 32     | 204               | 222                | 205               | 221               | <b><u>205</u></b> | <b><u>222</u></b> |
| 505.mcf_r       | 32     | 150               | 344                | 150               | 346               | <b><u>150</u></b> | <b><u>345</u></b> | 32     | 150               | 344                | 150               | 346               | <b><u>150</u></b> | <b><u>345</u></b> |
| 520.omnetpp_r   | 32     | 336               | 125                | 335               | 125               | <b><u>335</u></b> | <b><u>125</u></b> | 32     | 336               | 125                | 335               | 125               | <b><u>335</u></b> | <b><u>125</u></b> |
| 523.xalancbmk_r | 32     | <b><u>116</u></b> | <b><u>292</u></b>  | 116               | 291               | 116               | 292               | 32     | <b><u>116</u></b> | <b><u>292</u></b>  | 116               | 291               | 116               | 292               |
| 525.x264_r      | 32     | <b><u>116</u></b> | <b><u>483</u></b>  | 116               | 482               | 116               | 483               | 32     | 112               | 501                | <b><u>112</u></b> | <b><u>501</u></b> | 112               | 500               |
| 531.deepsjeng_r | 32     | 210               | 174                | <b><u>210</u></b> | <b><u>174</u></b> | 210               | 174               | 32     | 210               | 174                | <b><u>210</u></b> | <b><u>174</u></b> | 210               | 174               |
| 541.leela_r     | 32     | 350               | 151                | 350               | 152               | <b><u>350</u></b> | <b><u>152</u></b> | 32     | 350               | 151                | 350               | 152               | <b><u>350</u></b> | <b><u>152</u></b> |
| 548.exchange2_r | 32     | 177               | 475                | 176               | 475               | <b><u>176</u></b> | <b><u>475</u></b> | 32     | 177               | 475                | 176               | 475               | <b><u>176</u></b> | <b><u>475</u></b> |
| 557.xz_r        | 32     | <b><u>388</u></b> | <b><u>89.0</u></b> | 387               | 89.3              | 392               | 88.3              | 32     | <b><u>388</u></b> | <b><u>89.0</u></b> | 387               | 89.3              | 392               | 88.3              |

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Environment Variables Notes

Environment variables set by runcpu before the start of the run:  
LD\_LIBRARY\_PATH = "/home/CPU2017/lib/intel64:/home/CPU2017/lib/ia32:/home/CPU2017/je5.0.1-32"  
MALLOC\_CONF = "retain:true"

## General Notes

Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM  
memory using Red Hat Enterprise Linux 8.4  
Transparent Huge Pages enabled by default  
Prior to runcpu invocation  
Filesystem page cache synced and cleared with:  
sync; echo 3> /proc/sys/vm/drop\_caches  
runcpu command invoked through numactl i.e.:  
numactl --interleave=all runcpu <etc>  
jemalloc, a general purpose malloc implementation  
built with the RedHat Enterprise 7.5, and the system compiler gcc 4.8.5  
sources available from jemalloc.net or <https://github.com/jemalloc/jemalloc/releases>



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfra Co., Ltd.  
QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087

Test Sponsor: Maginfra Co., Ltd.

Tested by: Maginfra Co., Ltd.

Test Date: Jun-2026

Hardware Availability: Dec-2025

Software Availability: Feb-2025

## Platform Notes

BIOS configuration:  
ENERGY\_PERF\_BIAS\_CFG mode = Performance  
SNC = Enable  
Latency Optimized Mode = Enable

Sysinfo program /home/CPU2017/bin/sysinfo  
Rev: r6732 of 2022-11-07 fe91c89b7ed5c36ae2c92cc097bec197  
running on localhost Tue Jun 16 18:12:05 2026

SUT (System Under Test) info as seen by some common utilities.

### Table of contents

1. uname -a
2. w
3. Username
4. ulimit -a
5. sysinfo process ancestry
6. /proc/cpuinfo
7. lscpu
8. numactl --hardware
9. /proc/meminfo
10. who -r
11. Systemd service manager version: systemd 254 (254.10+suse.84.ge8d77af424)
12. Services, from systemctl list-unit-files
13. Linux kernel boot-time arguments, from /proc/cmdline
14. cpupower frequency-info
15. tuned-adm active
16. sysctl
17. /sys/kernel/mm/transparent\_hugepage
18. /sys/kernel/mm/transparent\_hugepage/khugepaged
19. OS release
20. Disk information
21. /sys/devices/virtual/dmi/id
22. dmidecode
23. BIOS

1. uname -a  
Linux localhost 6.4.0-150600.21-default #1 SMP PREEMPT\_DYNAMIC Thu May 16 11:09:22 UTC 2024 (36c1e09)  
x86\_64 x86\_64 x86\_64 GNU/Linux

2. w  
18:12:05 up 2 min, 1 user, load average: 0.21, 0.14, 0.05  
USER TTY FROM LOGIN@ IDLE JCPU PCPU WHAT  
root tty1 - 18:10 13.00s 0.81s 0.01s -bash

3. Username  
From environment variable \$USER: root

4. ulimit -a  
core file size (blocks, -c) unlimited  
data seg size (kbytes, -d) unlimited  
scheduling priority (-e) 0  
file size (blocks, -f) unlimited

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfra Co., Ltd.  
QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087

Test Sponsor: Maginfra Co., Ltd.

Tested by: Maginfra Co., Ltd.

Test Date: Jun-2026

Hardware Availability: Dec-2025

Software Availability: Feb-2025

## Platform Notes (Continued)

```
pending signals          (-i) 4126481
max locked memory        (kbytes, -l) 8192
max memory size          (kbytes, -m) unlimited
open files               (-n) 1024
pipe size                (512 bytes, -p) 8
POSIX message queues     (bytes, -q) 819200
real-time priority       (-r) 0
stack size               (kbytes, -s) unlimited
cpu time                 (seconds, -t) unlimited
max user processes       (-u) 4126481
virtual memory           (kbytes, -v) unlimited
file locks               (-x) unlimited
```

### 5. sysinfo process ancestry

```
/usr/lib/systemd/systemd --switched-root --system --deserialize=42
login -- root
-bash
-bash
runcpu --nobuild --action validate --define default-platform-flags --define numcopies=32 -c
ic2025.2-lin-graniterapids-rate-20250605.cfg --define smt-on --define cores=16 --define physicalfirst
--define invoke_with_interleave --define drop_caches --tune base,peak -o all intrate
runcpu --nobuild --action validate --define default-platform-flags --define numcopies=32 --configfile
ic2025.2-lin-graniterapids-rate-20250605.cfg --define smt-on --define cores=16 --define physicalfirst
--define invoke_with_interleave --define drop_caches --tune base,peak --output_format all --nopower
--runmode rate --tune base:peak --size refrate intrate --nopreenv --note-preenv --logfile
$SPEC/tmp/CPU2017.038/temlogs/preenv.intrate.038.0.log --lognum 038.0 --from_runcpu 2
specperl $SPEC/bin/sysinfo
$SPEC = /home/CPU2017
```

### 6. /proc/cpuinfo

```
model name      : Intel(R) Xeon(R) 6507P
vendor_id      : GenuineIntel
cpu family     : 6
model          : 173
stepping       : 1
microcode      : 0x10003d0
bugs           : spectre_v1 spectre_v2 spec_store_bypass swapgs bhi
cpu cores      : 8
siblings       : 16
2 physical ids (chips)
32 processors (hardware threads)
physical id 0: core ids 0-7
physical id 1: core ids 0-7
physical id 0: apicids 0-15
physical id 1: apicids 128-143
```

Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for virtualized systems. Use the above data carefully.

### 7. lscpu

From lscpu from util-linux 2.39.3:

```
Architecture:      x86_64
CPU op-mode(s):    32-bit, 64-bit
Address sizes:      52 bits physical, 57 bits virtual
Byte Order:         Little Endian
CPU(s):             32
On-line CPU(s) list: 0-31
```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfraco., Ltd.  
QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087

Test Sponsor: Maginfraco., Ltd.

Tested by: Maginfraco., Ltd.

Test Date: Jun-2026

Hardware Availability: Dec-2025

Software Availability: Feb-2025

## Platform Notes (Continued)

Vendor ID: GenuineIntel  
BIOS Vendor ID: Intel(R) Corporation  
Model name: Intel(R) Xeon(R) 6507P  
BIOS Model name: Intel(R) Xeon(R) 6507P CPU @ 3.5GHz  
BIOS CPU family: 179  
CPU family: 6  
Model: 173  
Thread(s) per core: 2  
Core(s) per socket: 8  
Socket(s): 2  
Stepping: 1  
CPU(s) scaling MHz: 59%  
CPU max MHz: 4300.0000  
CPU min MHz: 800.0000  
BogoMIPS: 7000.00  
Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp lm constant\_tsc art arch\_perfmon pebs bts rep\_good nopl xtopology nonstop\_tsc cpuid aperfmperf tsc\_known\_freq pni pclmulqdq dtes64 ds\_cpl smx est tm2 ssse3 sdbg fma cx16 xtpr pdcm pcid dca sse4\_1 sse4\_2 x2apic movbe popcnt tsc\_deadline\_timer aes xsave avx f16c rdrand lahf\_lm abm 3dnowprefetch cpuid\_fault epb cat\_l3 cat\_l2 cdp\_l3 intel\_ppin cdp\_l2 ssbd mba ibrs ibpb stibp ibrs\_enhanced fsgsbase tsc\_adjust bmi1 hle avx2 smep bmi2 erms invpcid rtm cqm rdt\_a avx512f avx512dq rdseed adx smap avx512ifma clflushopt clwb intel\_pt avx512cd sha\_ni avx512bw avx512vl xsaveopt xsavec xgetbv1 xsave cqm\_llc cqm\_occup\_llc cqm\_mbm\_total cqm\_mbm\_local split\_lock\_detect user\_shstk avx\_vnni avx512\_bf16 wbnoinvd dtherm ida arat pln pts hwp hwp\_act\_window hwp\_epp hwp\_pkg\_req avx512vbmi umip pku ospke waitpkg avx512\_vbmi2 gfni vaes vpclmulqdq avx512\_vnni avx512\_bitalg tme avx512\_vpopcntdq la57 rdpid bus\_lock\_detect cldemote movdiri movdir64b enqcmd fsrm md\_clear serialize tsxldtrk pconfig arch\_lbr ibt amx\_bf16 avx512\_fp16 amx\_tile amx\_int8 flush\_l1d arch\_capabilities  
L1d cache: 768 KiB (16 instances)  
L1i cache: 1 MiB (16 instances)  
L2 cache: 32 MiB (16 instances)  
L3 cache: 96 MiB (2 instances)  
NUMA node(s): 2  
NUMA node0 CPU(s): 0-7,16-23  
NUMA node1 CPU(s): 8-15,24-31  
Vulnerability Gather data sampling: Not affected  
Vulnerability Itlb multihit: Not affected  
Vulnerability L1tf: Not affected  
Vulnerability Mds: Not affected  
Vulnerability Meltdown: Not affected  
Vulnerability Mmio stale data: Not affected  
Vulnerability Reg file data sampling: Not affected  
Vulnerability Retbleed: Not affected  
Vulnerability Spec rstack overflow: Not affected  
Vulnerability Spec store bypass: Mitigation; Speculative Store Bypass disabled via prctl  
Vulnerability Spectre v1: Mitigation; usercopy/swapgs barriers and \_\_user pointer sanitization  
Vulnerability Spectre v2: Mitigation; Enhanced / Automatic IBRS; IBPB conditional; RSB filling; PBRSE-IBRS Not affected; BHI BHI\_DIS\_S  
Vulnerability Srbds: Not affected  
Vulnerability Tsx async abort: Not affected

From lscpu --cache:

| NAME | ONE-SIZE | ALL-SIZE | WAYS | TYPE | LEVEL | SETS | PHY-LINE | COHERENCY-SIZE |
|------|----------|----------|------|------|-------|------|----------|----------------|
| L1d  | 48K      | 768K     | 12   | Data | 1     | 64   | 1        | 64             |

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfra Co., Ltd.  
QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087

Test Sponsor: Maginfra Co., Ltd.

Tested by: Maginfra Co., Ltd.

Test Date: Jun-2026

Hardware Availability: Dec-2025

Software Availability: Feb-2025

## Platform Notes (Continued)

|     |     |     |                |   |       |   |    |
|-----|-----|-----|----------------|---|-------|---|----|
| L1i | 64K | 1M  | 16 Instruction | 1 | 64    | 1 | 64 |
| L2  | 2M  | 32M | 16 Unified     | 2 | 2048  | 1 | 64 |
| L3  | 48M | 96M | 16 Unified     | 3 | 49152 | 1 | 64 |

### 8. numactl --hardware

NOTE: a numactl 'node' might or might not correspond to a physical chip.

```
available: 2 nodes (0-1)
node 0 cpus: 0-7,16-23
node 0 size: 515608 MB
node 0 free: 514735 MB
node 1 cpus: 8-15,24-31
node 1 size: 516037 MB
node 1 free: 515275 MB
node distances:
node  0  1
  0: 10  21
  1: 21  10
```

### 9. /proc/meminfo

MemTotal: 1056406144 kB

### 10. who -r

run-level 3 Jun 16 18:10

### 11. Systemd service manager version: systemd 254 (254.10+suse.84.ge8d77af424)

|                |         |
|----------------|---------|
| Default Target | Status  |
| multi-user     | running |

### 12. Services, from systemctl list-unit-files

| STATE           | UNIT FILES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| enabled         | YaST2-Firstboot YaST2-Second-Stage auditd cron display-manager getty@ irqbalance<br>issue-generator kbdsettings klog lvm2-monitor nsd nvme-fc-boot-connections<br>nvmf-autoconnect postfix purge-kernels rollback rsyslog smartd sshd systemd-pstore wicked<br>wickedd-auto4 wickedd-dhcp4 wickedd-dhcp6 wickedd-nanny                                                                                                                                                                                                                                                            |
| enabled-runtime | systemd-remount-fs                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| disabled        | apparmor autofs autoyast-initscripts blk-availability boot-sysctl ca-certificates<br>chrony-wait chronyd console-getty cups cups-browsed debug-shell ebttables<br>exchange-bmc-os-info firewalld fsidd gpm grub2-once haveged ipmi ipmievdev<br>issue-add-ssh-keys kexec-load lunmask man-db-create multipathd nfs nfs-blkmap rpcbind<br>rpmconfigcheck rsyncd serial-getty@ smartd-generate_opts snmpd snmptrapd<br>systemd-boot-check-no-failures systemd-confext systemd-network-generator systemd-sysext<br>systemd-time-wait-sync systemd-timesyncd tuned udisks2 vncserver@ |
| indirect        | systemd-userdbd wickedd                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

### 13. Linux kernel boot-time arguments, from /proc/cmdline

```
BOOT_IMAGE=/boot/vmlinuz-6.4.0-150600.21-default
root=UUID=9a795dfb-1ba6-4802-bd8a-006ca90ba081
splash=silent
mitigations=auto
quiet
```

### 14. cpupower frequency-info

analyzing CPU 3:

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfra Co., Ltd.  
QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087

Test Sponsor: Maginfra Co., Ltd.

Tested by: Maginfra Co., Ltd.

Test Date: Jun-2026

Hardware Availability: Dec-2025

Software Availability: Feb-2025

## Platform Notes (Continued)

current policy: frequency should be within 800 MHz and 4.30 GHz.  
The governor "performance" may decide which speed to use within this range.

boost state support:

Supported: yes

Active: yes

### 15. tuned-adm active

It seems that tuned daemon is not running, preset profile is not activated.  
Preset profile: throughput-performance

### 16. sysctl

|                              |       |
|------------------------------|-------|
| kernel.numa_balancing        | 1     |
| kernel.randomize_va_space    | 2     |
| vm.compaction_proactiveness  | 20    |
| vm.dirty_background_bytes    | 0     |
| vm.dirty_background_ratio    | 10    |
| vm.dirty_bytes               | 0     |
| vm.dirty_expire_centisecs    | 3000  |
| vm.dirty_ratio               | 20    |
| vm.dirty_writeback_centisecs | 500   |
| vm.dirtytime_expire_seconds  | 43200 |
| vm.extfrag_threshold         | 500   |
| vm.min_unmapped_ratio        | 1     |
| vm.nr_hugepages              | 0     |
| vm.nr_hugepages_mempolicy    | 0     |
| vm.nr_overcommit_hugepages   | 0     |
| vm.swappiness                | 60    |
| vm.watermark_boost_factor    | 15000 |
| vm.watermark_scale_factor    | 10    |
| vm.zone_reclaim_mode         | 0     |

### 17. /sys/kernel/mm/transparent\_hugepage

|                |          |             |               |           |            |
|----------------|----------|-------------|---------------|-----------|------------|
| defrag         | always   | defer       | defer+madvise | [madvise] | never      |
| enabled        | [always] | madvise     | never         |           |            |
| hpage_pmd_size | 2097152  |             |               |           |            |
| shmem_enabled  | always   | within_size | advise        | [never]   | deny force |

### 18. /sys/kernel/mm/transparent\_hugepage/khugepaged

|                       |       |
|-----------------------|-------|
| alloc_sleep_millisecs | 60000 |
| defrag                | 1     |
| max_ptes_none         | 511   |
| max_ptes_shared       | 256   |
| max_ptes_swap         | 64    |
| pages_to_scan         | 4096  |
| scan_sleep_millisecs  | 10000 |

### 19. OS release

From /etc/\*-release /etc/\*-version  
os-release SUSE Linux Enterprise Server 15 SP6

### 20. Disk information

SPEC is set to: /home/CPU2017

| Filesystem | Type | Size | Used | Avail | Use% | Mounted on |
|------------|------|------|------|-------|------|------------|
|------------|------|------|------|-------|------|------------|

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfra Co., Ltd.  
QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215  
SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087  
Test Sponsor: Maginfra Co., Ltd.  
Tested by: Maginfra Co., Ltd.

Test Date: Jun-2026  
Hardware Availability: Dec-2025  
Software Availability: Feb-2025

## Platform Notes (Continued)

/dev/nvme0n1p2 xfs 929G 89G 841G 10% /

21. /sys/devices/virtual/dmi/id  
Vendor: Maginfra  
Product: QR8228-T3  
Product Family: Not specified  
Serial: 00000000

22. dmidecode  
Additional information from dmidecode 3.4 follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.  
Memory:  
4x Samsung M321R8GA0PB1-CCPQC 64 GB 2 rank 6400  
9x Samsung M321R8GA0PB2-CCPEC 64 GB 2 rank 6400  
3x Samsung M321R8GA0PB2-CCPWC 64 GB 2 rank 6400

23. BIOS  
(This section combines info from /sys/devices and dmidecode.)  
BIOS Vendor: American Megatrends International, LLC.  
BIOS Version: 04.01.00  
BIOS Date: 12/17/2025

## Compiler Version Notes

```
=====
C      | 502.gcc_r(peak)
-----
Intel(R) oneAPI DPC++/C++ Compiler for applications running on IA-32, Version 2024.2.1 Build 20240711
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.
-----

=====
C      | 500.perlbench_r(base, peak) 502.gcc_r(base) 505.mcf_r(base, peak) 525.x264_r(base, peak)
      | 557.xz_r(base, peak)
-----
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.
-----

=====
C      | 502.gcc_r(peak)
-----
Intel(R) oneAPI DPC++/C++ Compiler for applications running on IA-32, Version 2024.2.1 Build 20240711
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.
-----

=====
C      | 500.perlbench_r(base, peak) 502.gcc_r(base) 505.mcf_r(base, peak) 525.x264_r(base, peak)
      | 557.xz_r(base, peak)
-----
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.
-----
```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfra Co., Ltd.  
QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087

Test Sponsor: Maginfra Co., Ltd.

Tested by: Maginfra Co., Ltd.

Test Date: Jun-2026

Hardware Availability: Dec-2025

Software Availability: Feb-2025

## Compiler Version Notes (Continued)

```
=====
C++      | 520.omnetpp_r(base, peak) 523.xalancbmk_r(base, peak) 531.deepsjeng_r(base, peak)
          | 541.leela_r(base, peak)
-----
```

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605  
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.

```
=====
Fortran  | 548.exchange2_r(base, peak)
-----
```

Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605  
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.

## Base Compiler Invocation

C benchmarks:

icx

C++ benchmarks:

icpx

Fortran benchmarks:

ifx

## Base Portability Flags

```
500.perlbench_r: -DSPEC_LP64 -DSPEC_LINUX_X64
502.gcc_r: -DSPEC_LP64
505.mcf_r: -DSPEC_LP64
520.omnetpp_r: -DSPEC_LP64
523.xalancbmk_r: -DSPEC_LP64 -DSPEC_LINUX
525.x264_r: -DSPEC_LP64
531.deepsjeng_r: -DSPEC_LP64
541.leela_r: -DSPEC_LP64
548.exchange2_r: -DSPEC_LP64
557.xz_r: -DSPEC_LP64
```

## Base Optimization Flags

C benchmarks:

```
-w -std=c11 -m64 -Wl,-z,muldefs -xgraniterapids -O3 -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfra Co., Ltd.

QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087

Test Sponsor: Maginfra Co., Ltd.

Tested by: Maginfra Co., Ltd.

Test Date: Jun-2026

Hardware Availability: Dec-2025

Software Availability: Feb-2025

## Base Optimization Flags (Continued)

C benchmarks (continued):

-L/home/specdev/intel-compilers/compiler/2025.2/lib -lqkmallo

C++ benchmarks:

-w -std=c++14 -m64 -Wl,-z,muldefs -xgraniterapids -O3 -ffast-math

-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4

-fdelayed-template-parsing

-L/home/specdev/intel-compilers/compiler/2025.2/lib -lqkmallo

Fortran benchmarks:

-w -m64 -Wl,-z,muldefs -xgraniterapids -O3 -ffast-math -flto

-mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4

-nostandard-realloc-lhs -align array32byte -auto

-L/home/specdev/intel-compilers/compiler/2025.2/lib -lqkmallo

## Peak Compiler Invocation

C benchmarks (except as noted below):

icx

502.gcc\_r: icx

C++ benchmarks:

icpx

Fortran benchmarks:

ifx

## Peak Portability Flags

500.perlbench\_r: -DSPEC\_LP64 -DSPEC\_LINUX\_X64

502.gcc\_r: -D\_FILE\_OFFSET\_BITS=64

505.mcf\_r: -DSPEC\_LP64

520.omnetpp\_r: -DSPEC\_LP64

523.xalancbmk\_r: -DSPEC\_LP64 -DSPEC\_LINUX

525.x264\_r: -DSPEC\_LP64

531.deepsjeng\_r: -DSPEC\_LP64

541.leela\_r: -DSPEC\_LP64

548.exchange2\_r: -DSPEC\_LP64

557.xz\_r: -DSPEC\_LP64



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfra Co., Ltd.

QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087

Test Sponsor: Maginfra Co., Ltd.

Tested by: Maginfra Co., Ltd.

Test Date: Jun-2026

Hardware Availability: Dec-2025

Software Availability: Feb-2025

## Peak Optimization Flags

C benchmarks:

```
500.perlbench_r: -w -std=c11 -m64 -Wl, -z, muldefs
-fprofile-generate(pass 1)
-fprofile-use=default.profddata(pass 2) -xCORE-AVX2(pass 1)
-flto -Ofast -xCORE-AVX512 -ffast-math -mfpmath=sse
-funroll-loops -qopt-mem-layout-trans=4
-fno-strict-overflow -fno-strict-aliasing
-L/home/specdev/intel-compilers/compiler/2025.2/lib
-lqkmallocc

502.gcc_r: -m32 -L/home/specdev/intel-compilers/compiler/2024.2/lib32
-std=gnu89 -Wl, -z, muldefs -fprofile-generate(pass 1)
-fprofile-use=default.profddata(pass 2) -xCORE-AVX2(pass 1)
-flto -Ofast -xCORE-AVX512 -ffast-math -mfpmath=sse
-funroll-loops -qopt-mem-layout-trans=4
-L/usr/local/jemalloc32-5.0.1/lib -ljemalloc

505.mcf_r: basepeak = yes

525.x264_r: -w -std=c11 -m64 -Wl, -z, muldefs -xgraniterapids -Ofast
-ffast-math -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -fno-alias
-L/home/specdev/intel-compilers/compiler/2025.2/lib
-lqkmallocc

557.xz_r: basepeak = yes
```

C++ benchmarks:

```
520.omnetpp_r: basepeak = yes

523.xalancbmk_r: basepeak = yes

531.deepsjeng_r: basepeak = yes

541.leela_r: basepeak = yes
```

Fortran benchmarks:

```
548.exchange2_r: basepeak = yes
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/Intel-ic2025-official-linux64.html>

<http://www.spec.org/cpu2017/flags/Maginfra-Platform-Settings-intel-V1.0.html>



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Maginfra Co., Ltd.

QR8228-T3 (Intel Xeon 6507P)

SPECrate®2017\_int\_base = 215

SPECrate®2017\_int\_peak = 221

CPU2017 License: 9087

Test Sponsor: Maginfra Co., Ltd.

Tested by: Maginfra Co., Ltd.

Test Date: Jun-2026

Hardware Availability: Dec-2025

Software Availability: Feb-2025

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/Intel-ic2025-official-linux64.xml>

<http://www.spec.org/cpu2017/flags/Maginfra-Platform-Settings-intel-V1.0.xml>

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU®2017 v1.1.9 on 2026-06-16 18:12:04-0400.

Report generated on 2026-07-14 17:26:17 by CPU2017 PDF formatter v6716.

Originally published on 2026-07-14.