



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**  
(Test Sponsor: Intel Corporation)


SPECrate®2026\_int\_base = 926

**Hyper SuperServer SYS-222HA-TN**

SPECrate®2026\_int\_peak = 984

**CPU2026 License:** 13  
**Test Sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test Date:** Feb-2026  
**Hardware Availability:** Jun-2025  
**Software Availability:** Nov-2025



## Hardware

CPU Name: Intel Xeon 6980P  
 Max MHz: 3900  
 Nominal: 2000  
 Enabled: 256 cores, 2 chips, 2 threads/core  
 Orderable: 1,2 chips  
 Cache L1: 64 KB I + 48 KB D on chip per core  
 L2: 2 MB I+D on chip per core  
 L3: 504 MB I+D on chip per chip  
 Other: None  
 Memory: 1536 GB (24 x 64 GB 2Rx4 PC5-88/56B-M)  
 Storage: 1 x 3.5 TB PCIe NVMe SSD  
 Cooling: Air  
 Other: None

## Software

OS: Ubuntu 24.04.3 LTS  
 6.8.0-90-generic  
 Compiler: C/C++: Version 2025.3 of Intel oneAPI DPC++/C++ Compiler for Linux;  
 Fortran: Version 2025.3 of Intel Fortran Compiler for Linux  
 Compiler Category: Vendor  
 Firmware: Version 5.35 released Jul-2025  
 File System: ext4  
 System State: Run level 5 (Multiuser with networking)  
 Base Pointers: 64-bit  
 Peak Pointers: 64-bit  
 Other: None  
 Power Management: BIOS set to prefer performance at the cost of additional power usage.



SPEC

# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**  
(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

**Hyper SuperServer SYS-222HA-TN**

SPECrate®2026\_int\_peak = 984

**CPU2026 License:** 13  
**Test Sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test Date:** Feb-2026  
**Hardware Availability:** Jun-2025  
**Software Availability:** Nov-2025

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
706.stockfish_r	512	<b>335</b>	<b>1930</b>	334	1930			512	<b>338</b>	<b>1910</b>	338	1910		
707.ntest_r	512	<b>297</b>	<b>1020</b>	296	1020			512	<b>297</b>	<b>1020</b>	296	1020		
708.sqlite_r	512	387	699	<b>389</b>	<b>694</b>			512	<b>349</b>	<b>775</b>	348	777		
710.omnetpp_r	512	<b>256</b>	<b>970</b>	256	971			512	<b>227</b>	<b>1100</b>	227	1100		
714.cpython_r	512	220	1110	<b>221</b>	<b>1110</b>			512	<b>174</b>	<b>1410</b>	174	1410		
721.gcc_r	512	<b>469</b>	<b>748</b>	468	750			512	<b>469</b>	<b>748</b>	468	750		
723.llvm_r	512	<b>298</b>	<b>870</b>	293	885			512	<b>256</b>	<b>1010</b>	256	1010		
727.cppcheck_r	512	228	806	<b>229</b>	<b>803</b>			512	228	806	<b>229</b>	<b>803</b>		
729.abc_r	512	<b>308</b>	<b>762</b>	307	765			512	<b>308</b>	<b>762</b>	307	765		
734.vpr_r	512	263	899	<b>263</b>	<b>898</b>			512	263	899	<b>263</b>	<b>898</b>		
735.gem5_r	512	239	1040	<b>240</b>	<b>1040</b>			512	<b>223</b>	<b>1120</b>	222	1120		
750.sealcrypto_r	512	<b>374</b>	<b>734</b>	370	742			512	<b>374</b>	<b>734</b>	370	742		
753.ns3_r	512	<b>224</b>	<b>1400</b>	221	1420			512	<b>196</b>	<b>1600</b>	196	1600		
777.zstd_r	512	<b>543</b>	<b>607</b>	541	610			512	<b>526</b>	<b>626</b>	526	626		

SPECrate®2026\_int\_base = **926**

SPECrate®2026\_int\_peak = **984**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Environment Variables Notes

Environment variables set by runcpu before the start of the run:  
LD\_LIBRARY\_PATH = "/root/cpu2026-0.902.0/lib"  
MALLOC\_CONF = "retain:true"

## General Notes

Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM memory using CentOS Stream 9.  
Transparent Huge Pages enabled by default  
Prior to runcpu invocation

(Continued on next page)



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

## Supermicro

(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

## Hyper SuperServer SYS-222HA-TN

SPECrate®2026\_int\_peak = 984

CPU2026 License: 13

Test Sponsor: Intel Corporation

Tested by: Intel Corporation

Test Date: Feb-2026

Hardware Availability: Jun-2025

Software Availability: Nov-2025

### General Notes (Continued)

Filesystem page cache synced and cleared with:  
sync; echo 3> /proc/sys/vm/drop\_caches  
runcpu command invoked through numactl i.e.:  
numactl --interleave=all runcpu <etc>

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

### Platform Notes

BIOS Configuration :  
Workload Profile set to Disabled  
Power Performance Tuning set to BIOS Controls EPB  
Energy Perf Bias CFG mode set to Extreme Performance  
Sub NUMA Clustering (SNC) set to Enabled  
KTI Prefetch set to Enabled  
Stale AtoS set to Disabled  
LLC Dead Line Alloc set to Disabled  
BMC Configuration:  
System Fan speed is set to full speed

Sysinfo program /root/cpu2026-0.902.0/bin/sysinfo  
Rev: 069f95da7e7f5d81b2ce48a82150e54f  
running on smc-gnr-ap6-ubuntu Mon Feb 2 21:39:17 2026

SUT (System Under Test) info as seen by some common utilities.

-----  
Table of contents  
-----

1. uname -srvm
2. w
3. Username
4. ulimit -a
5. sysinfo process ancestry
6. /proc/cpuinfo
7. lscpu
8. numactl --hardware
9. /proc/meminfo
10. who -r
11. Systemd service manager version: systemd 255 (255.4-lubuntu8.12)

(Continued on next page)



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**  
(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

**Hyper SuperServer SYS-222HA-TN**

SPECrate®2026\_int\_peak = 984

**CPU2026 License:** 13  
**Test Sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test Date:** Feb-2026  
**Hardware Availability:** Jun-2025  
**Software Availability:** Nov-2025

## Platform Notes (Continued)

- 12. Failed units, from `systemctl list-units --state=failed`
- 13. Services, from `systemctl list-unit-files`
- 14. Linux kernel boot-time arguments, from `/proc/cmdline`
- 15. `cpupower frequency-info`
- 16. `sysctl`
- 17. `/sys/kernel/mm/transparent_hugepage`
- 18. `/sys/kernel/mm/transparent_hugepage/khugepaged`
- 19. OS release
- 20. Disk information
- 21. `/sys/devices/virtual/dmi/id`
- 22. `dmidecode`
- 23. BIOS

```
-----
1. uname -srvm
Linux 6.8.0-90-generic #91-Ubuntu SMP PREEMPT_DYNAMIC Tue Nov 18 14:14:30 UTC 2025 x86_64
-----
```

```
-----
2. w
21:39:17 up 2 days, 23:16, 3 users, load average: 0.01, 30.52, 53.45
USER      TTY      FROM          LOGIN@      IDLE        JCPU      PCPU      WHAT
root      pts/0    10.241.241.138 21:07      6:39        0.00s     0.03s     sshd: root@notty
root      pts/0    10.241.241.138 21:07      6:39        0.00s     0.15s     sshd: root@pts/0
-----
```

```
-----
3. Username
From environment variable $USER: root
-----
```

```
-----
4. ulimit -a
time(seconds)      unlimited
file(blocks)       unlimited
data(kbytes)       unlimited
stack(kbytes)      unlimited
coredump(blocks)   0
memory(kbytes)     unlimited
locked memory(kbytes) 198086480
process            6189882
nofiles            1024
vmemory(kbytes)    unlimited
locks              unlimited
rtprio             0
-----
```

```
-----
5. sysinfo process ancestry
/sbin/init
-----
```

(Continued on next page)



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**

(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

**Hyper SuperServer SYS-222HA-TN**

SPECrate®2026\_int\_peak = 984

**CPU2026 License:** 13

**Test Sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test Date:** Feb-2026

**Hardware Availability:** Jun-2025

**Software Availability:** Nov-2025

## Platform Notes (Continued)

```

tmux new -s spec
-bash
-bash
runcpu --nobuild --reportable --action validate --define default-platform-flags --copies 512 -c
ic2025.3-sapphirerapids-cpu2026-0.902-rate-20260121.cfg --define smt-on --define cores=256 --define
physicalfirst --define invoke_with_interleave --define drop_caches --tune base,peak -o all intrate
runcpu --nobuild --reportable --action validate --define default-platform-flags --copies 512 --configfile
ic2025.3-sapphirerapids-cpu2026-0.902-rate-20260121.cfg --define smt-on --define cores=256 --define
physicalfirst --define invoke_with_interleave --define drop_caches --tune base,peak --output_format all
--nopower --runmode rate --tune base:peak --size refrate intrate --nopreenv --note-preenv --logfile
$SPEC/tmp/CPU2026.011/templots/preenv.intrate.011.0.log --lognum 011.0 --from_runcpu 2
specperl $SPEC/bin/sysinfo
$SPEC = /root/cpu2026-0.902.0

```

### 6. /proc/cpuinfo

```

model name      : Intel(R) Xeon(R) 6980P
vendor_id      : GenuineIntel
cpu family     : 6
model          : 173
stepping       : 1
microcode      : 0x10003d0
bugs           : spectre_v1 spectre_v2 spec_store_bypass swapgs bhi vmscape
cpu cores      : 128
siblings       : 256
2 physical ids (chips)
512 processors (hardware threads)
physical id 0: core ids 0-42,64-106,128-169
physical id 1: core ids 0-42,64-106,128-169
physical id 0: apicids 0-85,128-213,256-339
physical id 1: apicids 512-597,640-725,768-851

```

Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for virtualized systems. Use the above data carefully.

### 7. lscpu

From lscpu from util-linux 2.39.3:

```

Architecture:      x86_64
CPU op-mode(s):    32-bit, 64-bit
Address sizes:     52 bits physical, 57 bits virtual
Byte Order:        Little Endian
CPU(s):            512
On-line CPU(s) list: 0-511
Vendor ID:         GenuineIntel
BIOS Vendor ID:    Intel(R) Corporation
Model name:        Intel(R) Xeon(R) 6980P

```

(Continued on next page)



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**  
(Test Sponsor: Intel Corporation)

**SPECrate®2026\_int\_base = 926**

**Hyper SuperServer SYS-222HA-TN**

**SPECrate®2026\_int\_peak = 984**

**CPU2026 License:** 13  
**Test Sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test Date:** Feb-2026  
**Hardware Availability:** Jun-2025  
**Software Availability:** Nov-2025

## Platform Notes (Continued)

```

BIOS Model name: Intel(R) Xeon(R) 6980P CPU @ 2.0GHz
BIOS CPU family: 179
CPU family: 6
Model: 173
Thread(s) per core: 2
Core(s) per socket: 128
Socket(s): 2
Stepping: 1
BogoMIPS: 4000.00
Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
pdpe1gb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good
nopl xtopology nonstop_tsc cpuid aperfperf tsc_known_freq pni
pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg fma cx16
xtpr pdcm pcid dca sse4_1 sse4_2 x2apic movbe popcnt
tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm
3dnowprefetch cpuid_fault epb cat_l3 cat_l2 cdp_l3 intel_ppin cdp_l2
ssbd mba ibrs ibpb stibp ibrs_enhanced tpr_shadow flexpriority ept
vpid ept_ad fsgsbase tsc_adjust bmi1 avx2 smep bmi2 erms invpcid cqm
rdt_a avx512f avx512dq rdseed adx smap avx512ifma clflushopt clwb
intel_pt avx512cd sha_ni avx512bw avx512vl xsaveopt xsavec xgetbv1
xsaves cqm_llc cqm_occup_llc cqm_mbm_total cqm_mbm_local
split_lock_detect user_shstk avx_vnni avx512_bf16 wbnoinvd dtherm ida
arat pln pts vnmi avx512vbmi umip pku ospke waitpkg avx512_vbmi2 gfni
vaes vpclmulqdq avx512_vnni avx512_bitalg tme avx512_vpopcntdq la57
rdpid bus_lock_detect cldemote movdiri movdir64b enqcmd fsrm md_clear
serialize tsxldtrk pconfig arch_lbr ibt amx_bf16 avx512_fp16 amx_tile
amx_int8 flush_lld arch_capabilities ibpb_exit_to_user

Virtualization: VT-x
L1d cache: 12 MiB (256 instances)
L1i cache: 16 MiB (256 instances)
L2 cache: 512 MiB (256 instances)
L3 cache: 1008 MiB (2 instances)
NUMA node(s): 6
NUMA node0 CPU(s): 0-42,256-298
NUMA node1 CPU(s): 43-85,299-341
NUMA node2 CPU(s): 86-127,342-383
NUMA node3 CPU(s): 128-170,384-426
NUMA node4 CPU(s): 171-213,427-469
NUMA node5 CPU(s): 214-255,470-511
Vulnerability Gather data sampling: Not affected
Vulnerability Itlb multihit: Not affected
Vulnerability L1tf: Not affected
Vulnerability Mds: Not affected
Vulnerability Meltdown: Not affected
Vulnerability Mmio stale data: Not affected
Vulnerability Reg file data sampling: Not affected

```

(Continued on next page)



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**  
(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

**Hyper SuperServer SYS-222HA-TN**

SPECrate®2026\_int\_peak = 984

**CPU2026 License:** 13  
**Test Sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test Date:** Feb-2026  
**Hardware Availability:** Jun-2025  
**Software Availability:** Nov-2025

## Platform Notes (Continued)

Vulnerability Retbleed: Not affected  
 Vulnerability Spec rstack overflow: Not affected  
 Vulnerability Spec store bypass: Mitigation; Speculative Store Bypass disabled via prctl  
 Vulnerability Spectre v1: Mitigation; usercopy/swapgs barriers and \_\_user pointer sanitization  
 Vulnerability Spectre v2: Mitigation; Enhanced / Automatic IBRS; IBPB conditional; RSB filling; PRRSB-eIBRS Not affected; BHI BHI\_DIS\_S  
 Vulnerability Srbds: Not affected  
 Vulnerability Tsx async abort: Not affected  
 Vulnerability Vmscape: Mitigation; IBPB before exit to userspace

From lscpu --cache:

NAME	ONE-SIZE	ALL-SIZE	WAYS	TYPE	LEVEL	SETS	PHY-LINE	COHERENCY-SIZE
L1d	48K	12M	12	Data	1	64	1	64
L1i	64K	16M	16	Instruction	1	64	1	64
L2	2M	512M	16	Unified	2	2048	1	64
L3	504M	1008M	16	Unified	3	516096	1	64

8. numactl --hardware

NOTE: a numactl 'node' might or might not correspond to a physical chip.

```

available: 6 nodes (0-5)
node 0 cpus: 0-42,256-298
node 0 size: 257526 MB
node 0 free: 245927 MB
node 1 cpus: 43-85,299-341
node 1 size: 258018 MB
node 1 free: 247902 MB
node 2 cpus: 86-127,342-383
node 2 size: 257976 MB
node 2 free: 248735 MB
node 3 cpus: 128-170,384-426
node 3 size: 258018 MB
node 3 free: 249107 MB
node 4 cpus: 171-213,427-469
node 4 size: 258018 MB
node 4 free: 248664 MB
node 5 cpus: 214-255,470-511
node 5 size: 257991 MB
node 5 free: 249208 MB
node distances:
node  0  1  2  3  4  5
 0:  10 15 17 21 28 26
 1:  15 10 15 23 26 23
 2:  17 15 10 26 23 21
 3:  21 28 26 10 15 17
 4:  23 26 23 15 10 15
 5:  26 23 21 17 15 10

```

(Continued on next page)



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**  
(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

**Hyper SuperServer SYS-222HA-TN**

SPECrate®2026\_int\_peak = 984

**CPU2026 License:** 13  
**Test Sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test Date:** Feb-2026  
**Hardware Availability:** Jun-2025  
**Software Availability:** Nov-2025

## Platform Notes (Continued)

-----  
9. /proc/meminfo  
MemTotal: 1584691864 kB

-----  
10. who -r  
run-level 5 Jan 30 22:23

-----  
11. Systemd service manager version: systemd 255 (255.4-1ubuntu8.12)  
Default Target Status  
graphical degraded

-----  
12. Failed units, from systemctl list-units --state=failed  
UNIT LOAD ACTIVE SUB DESCRIPTION  
\* fwupd-refresh.service loaded failed failed Refresh fwupd metadata and update motd  
Legend: LOAD -> Reflects whether the unit definition was properly loaded.  
ACTIVE -> The high-level unit activation state, i.e. generalization of SUB.  
SUB -> The low-level unit activation state, values depend on unit type.  
1 loaded units listed.

-----  
13. Services, from systemctl list-unit-files  
STATE UNIT FILES  
enabled ModemManager apparmor apport blk-availability cloud-config cloud-final cloud-init  
cloud-init-local console-setup cron dmesg e2scrub\_reap finalrd getty@ gpu-manager  
grub-common grub-initrd-fallback keyboard-setup lvm2-monitor multipathd  
networkd-dispatcher nvme-fc-boot-connections nvme-autoconnect open-iscsi open-vm-tools  
pollinate rsyslog secureboot-db setvtrgb snapd sysstat systemd-networkd  
systemd-networkd-wait-online systemd-pstore systemd-resolved systemd-timesyncd thermald  
ua-reboot-cmds ubuntu-advantage udisks2 ufw unattended-upgrades vgauth  
enabled-runtime netplan-ovs-cleanup systemd-fsck-root systemd-remount-fs  
disabled console-getty debug-shell ipmievd iscsid nftables rsync serial-getty@ ssh  
systemd-boot-check-no-failures systemd-confext systemd-network-generator  
systemd-networkd-wait-online@ systemd-pcrlock-file-system systemd-pcrlock-firmware-code  
systemd-pcrlock-firmware-config systemd-pcrlock-machine-id systemd-pcrlock-make-policy  
systemd-pcrlock-secureboot-authority systemd-pcrlock-secureboot-policy systemd-sysext  
systemd-time-wait-sync upower  
generated openipmi  
indirect systemd-sysupdate systemd-sysupdate-reboot uuuid  
masked cryptdisks cryptdisks-early hwclock multipath-tools-boot screen-cleanup sudo x11-common

-----  
14. Linux kernel boot-time arguments, from /proc/cmdline  
BOOT\_IMAGE=/boot/vmlinuz-6.8.0-90-generic

(Continued on next page)



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**  
(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

**Hyper SuperServer SYS-222HA-TN**

SPECrate®2026\_int\_peak = 984

**CPU2026 License:** 13  
**Test Sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test Date:** Feb-2026  
**Hardware Availability:** Jun-2025  
**Software Availability:** Nov-2025

## Platform Notes (Continued)

```
root=UUID=1125c027-be85-444c-a0e0-9873f7e7f358
ro
```

```
-----
15. cpupower frequency-info
analyzing CPU 273:
  Unable to determine current policy
  boost state support:
    Supported: yes
    Active: yes
-----
```

```
-----
16. sysctl
kernel.numa_balancing          1
kernel.randomize_va_space      2
vm.compaction_proactiveness    20
vm.dirty_background_bytes      0
vm.dirty_background_ratio      10
vm.dirty_bytes                  0
vm.dirty_expire_centisecs      3000
vm.dirty_ratio                  20
vm.dirty_writeback_centisecs   500
vm.dirtytime_expire_seconds    43200
vm.extfrag_threshold           500
vm.min_unmapped_ratio          1
vm.nr_hugepages                 0
vm.nr_hugepages_mempolicy      0
vm.nr_overcommit_hugepages     0
vm.swappiness                   60
vm.watermark_boost_factor      15000
vm.watermark_scale_factor      10
vm.zone_reclaim_mode           0
-----
```

```
-----
17. /sys/kernel/mm/transparent_hugepage
defrag          always defer defer+madvice [madvice] never
enabled         always [madvice] never
hpage_pmd_size 2097152
shmem_enabled   always within_size advise [never] deny force
-----
```

```
-----
18. /sys/kernel/mm/transparent_hugepage/khugepaged
alloc_sleep_millisecs  60000
defrag                  1
max_ptes_none          511
max_ptes_shared        256
max_ptes_swap          64
-----
```

(Continued on next page)



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**  
(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

**Hyper SuperServer SYS-222HA-TN**

SPECrate®2026\_int\_peak = 984

**CPU2026 License:** 13  
**Test Sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test Date:** Feb-2026  
**Hardware Availability:** Jun-2025  
**Software Availability:** Nov-2025

## Platform Notes (Continued)

pages\_to\_scan 4096  
scan\_sleep\_millisecs 10000

-----  
19. OS release  
From /etc/\*-release /etc/\*-version  
os-release Ubuntu 24.04.3 LTS

-----  
20. Disk information  
SPEC is set to: /root/cpu2026-0.902.0  
Filesystem Type Size Used Avail Use% Mounted on  
/dev/nvme1nlp2 ext4 3.5T 826G 2.5T 25% /

-----  
21. /sys/devices/virtual/dmi/id  
Vendor: Supermicro  
Product: SYS-222HA-TN  
Product Family: Family  
Serial: S928613X4614557

-----  
22. dmidecode  
Additional information from dmidecode 3.5 follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.  
Memory:  
1x Micron Technology MTC40F2046S1HC88XDX WCCCC 64 GB 1 rank 8800  
2x Micron Technology MTC40F2046S1HC88XDX WFFFG 64 GB 1 rank 8800  
21x Micron Technology MTC40F2046S1HC88XDY WCCCC 64 GB 1 rank 8800

-----  
23. BIOS  
(This section combines info from /sys/devices and dmidecode.)  
BIOS Vendor: American Megatrends International, LLC.  
BIOS Version: 1.4  
BIOS Date: 07/24/2025  
BIOS Revision: 5.35

## Compiler Version Notes

=====  
C | 708.sqlite\_r(base, peak) 714.cpython\_r(base, peak) 777.zstd\_r(base,  
| peak)

(Continued on next page)



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

## Supermicro

(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

## Hyper SuperServer SYS-222HA-TN

SPECrate®2026\_int\_peak = 984

CPU2026 License: 13

Test Sponsor: Intel Corporation

Tested by: Intel Corporation

Test Date: Feb-2026

Hardware Availability: Jun-2025

Software Availability: Nov-2025

### Compiler Version Notes (Continued)

```
-----
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
Version 2025.3.0 Build 20251010
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.
-----
```

```
=====
C++      | 706.stockfish_r(base, peak) 707.ntest_r(base, peak)
          | 727.cppcheck_r(base, peak) 753.ns3_r(base, peak)
-----
```

```
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
Version 2025.3.0 Build 20251010
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.
-----
```

```
=====
C++, C   | 710.omnetpp_r(base, peak) 721.gcc_r(base, peak) 723.llvm_r(base,
          | peak) 729.abc_r(base, peak) 734.vpr_r(base, peak) 735.gem5_r(base,
          | peak) 750.sealcrypto_r(base, peak)
-----
```

```
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
Version 2025.3.0 Build 20251010
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.
-----
```

### Base Compiler Invocation

C benchmarks:

icx

C++ benchmarks:

icpx

Benchmarks using both C and C++:

icpx icx

### Base Portability Flags

```
706.stockfish_r: -DSPEC_LP64
707.ntest_r: -DSPEC_LP64
708.sqlite_r: -DSPEC_LP64
710.omnetpp_r: -DSPEC_LP64
714.cpython_r: -DSPEC_LP64
```

(Continued on next page)



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**  
(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

**Hyper SuperServer SYS-222HA-TN**

SPECrate®2026\_int\_peak = 984

**CPU2026 License:** 13  
**Test Sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test Date:** Feb-2026  
**Hardware Availability:** Jun-2025  
**Software Availability:** Nov-2025

## Base Portability Flags (Continued)

721.gcc\_r: -DSPEC\_LP64  
723.llvm\_r: -DSPEC\_LP64  
727.cppcheck\_r: -DSPEC\_LP64  
729.abc\_r: -DSPEC\_LP64  
734.vpr\_r: -DSPEC\_LP64  
735.gem5\_r: -DSPEC\_LP64  
750.sealcrypto\_r: -DSPEC\_LP64  
753.ns3\_r: -DSPEC\_LP64  
777.zstd\_r: -DSPEC\_LP64

## Base Optimization Flags

C benchmarks:

-m64 -std=c18 -Wl,-z,muldefs -xsapphirerapids  
-mprefer-vector-width=512 -O3 -ffp-model=fast -flto -mfpmath=sse  
-funroll-loops -qopt-mem-layout-trans=4  
-L/opt/intel/oneapi/compiler/2025.3/lib -lqkmalloc

C++ benchmarks:

-m64 -std=c++17 -Wl,-z,muldefs -xsapphirerapids  
-mprefer-vector-width=512 -O3 -ffp-model=fast -flto -mfpmath=sse  
-funroll-loops -qopt-mem-layout-trans=4  
-L/opt/intel/oneapi/compiler/2025.3/lib -lqkmalloc

Benchmarks using both C and C++:

-m64 -std=c++17 -std=c18 -Wl,-z,muldefs -xsapphirerapids  
-mprefer-vector-width=512 -O3 -ffp-model=fast -flto -mfpmath=sse  
-funroll-loops -qopt-mem-layout-trans=4  
-L/opt/intel/oneapi/compiler/2025.3/lib -lqkmalloc

## Peak Compiler Invocation

C benchmarks:

icx

C++ benchmarks:

icpx

Benchmarks using both C and C++:

icpx icx



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**

(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

**Hyper SuperServer SYS-222HA-TN**

SPECrate®2026\_int\_peak = 984

**CPU2026 License:** 13

**Test Sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test Date:** Feb-2026

**Hardware Availability:** Jun-2025

**Software Availability:** Nov-2025

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
-m64 -std=c18 -Wl,-z,muldefs -fprofile-generate(pass 1)
-fprofile-use=default.profdata(pass 2) -xHost(pass 1) -ffp-model=fast
-xsapphirerapids(pass 2) -flto -mprefer-vector-width=512
-qopt-mem-layout-trans=4 -O3 -mfpmath=sse -funroll-loops
-L/opt/intel/oneapi/compiler/2025.3/lib -lqkmalloc
```

C++ benchmarks:

```
706.stockfish_r: -m64 -std=c++17 -Wl,-z,muldefs
-fprofile-generate(pass 1)
-fprofile-use=default.profdata(pass 2) -xHost(pass 1)
-ffp-model=fast -xsapphirerapids(pass 2) -flto
-mprefer-vector-width=512 -qopt-mem-layout-trans=4 -O3
-mfpmath=sse -funroll-loops
-L/opt/intel/oneapi/compiler/2025.3/lib -lqkmalloc
```

707.ntest\_r: basepeak = yes

727.cppcheck\_r: basepeak = yes

753.ns3\_r: Same as 706.stockfish\_r

Benchmarks using both C and C++:

```
710.omnetpp_r: -m64 -std=c++17 -std=c18 -Wl,-z,muldefs
-fprofile-generate(pass 1)
-fprofile-use=default.profdata(pass 2) -xHost(pass 1)
-ffp-model=fast -xsapphirerapids(pass 2) -flto
-mprefer-vector-width=512 -qopt-mem-layout-trans=4 -O3
-mfpmath=sse -funroll-loops
-L/opt/intel/oneapi/compiler/2025.3/lib -lqkmalloc
```

721.gcc\_r: basepeak = yes

723.llvm\_r: Same as 710.omnetpp\_r

729.abc\_r: basepeak = yes

(Continued on next page)



# SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

**Supermicro**  
(Test Sponsor: Intel Corporation)

SPECrate®2026\_int\_base = 926

**Hyper SuperServer SYS-222HA-TN**

SPECrate®2026\_int\_peak = 984

**CPU2026 License:** 13  
**Test Sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test Date:** Feb-2026  
**Hardware Availability:** Jun-2025  
**Software Availability:** Nov-2025

## Peak Optimization Flags (Continued)

734.vpr\_r: basepeak = yes

735.gem5\_r: Same as 710.omnetpp\_r

750.sealcrypto\_r: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2026/results/flags/Intel-ic2025-official-linux64-cpu2026-0.902.html>

<http://www.spec.org/cpu2026/results/flags/Intel-Platform-Settings-standard-v1.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2026/results/flags/Intel-ic2025-official-linux64-cpu2026-0.902.xml>

<http://www.spec.org/cpu2026/results/flags/Intel-Platform-Settings-standard-v1.xml>

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU®2026 v0.902.0 on 2026-02-02 16:39:17-0500.  
Report generated on 2026-05-11 16:38:21 by CPU2026 PDF formatter (unknown).  
Originally published on 2026-05-05.