



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857


Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026



Hardware

CPU Name: AMD EPYC 9755
Max MHz: 4100
Nominal: 2700
Enabled: 256 cores, 2 chips, 2 threads/core
Orderable: 1,2 chips
Cache L1: 32 KB I + 48 KB D on chip per core
L2: 1 MB I+D on chip per core
L3: 512 MB I+D on chip per chip, 32 MB shared / 8 cores
Other: None
Memory: 1536 GB (24 x 64 GB 2Rx8 PC5-6400B-R)

Storage: 1x3.84TB M.2 NVMe SSD
Cooling: Air
Other: None

Software

OS: SUSE Linux Enterprise Server 15 SP7
kernel version 6.4.0-150700.51-default
Compiler: C/C++/Fortran: Version 5.2.0 of AOCC
Compiler Category: Vendor
Firmware: American Megatrends Version 10.28.00 released Jan-2026
File System: btrfs
System State: Run level 3 (multi-user)
Base Pointers: 64-bit
Peak Pointers: 64-bit
Other: jemalloc: jemalloc memory allocator library v5.3.1
Power Management: BIOS and OS set to prefer performance at the cost of additional power usage



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
706.stockfish_r	512	264	2450	264	2440	264	2440	512	264	2450	264	2440	264	2440
707.ntest_r	512	261	1160	262	1160	261	1160	512	261	1160	262	1160	261	1160
708.sqlite_r	512	356	760	356	760	356	759	512	356	760	356	760	356	759
710.omnetpp_r	512	211	1180	212	1170	212	1180	512	211	1180	212	1170	212	1180
714.cpython_r	512	221	1110	221	1110	221	1110	512	221	1110	221	1110	221	1110
721.gcc_r	512	470	747	470	747	469	748	512	470	747	470	747	469	748
723.llvm_r	512	258	1000	259	1000	258	1010	512	258	1000	259	1000	258	1010
727.cppcheck_r	512	201	913	201	916	200	918	512	201	913	201	916	200	918
729.abc_r	512	303	775	303	776	303	776	512	303	775	303	776	303	776
734.vpr_r	512	252	937	250	943	250	943	512	252	937	250	943	250	943
735.gem5_r	512	175	1430	175	1420	175	1420	512	175	1430	175	1420	175	1420
750.sealcrypto_r	512	242	1140	241	1140	242	1130	512	242	1140	241	1140	242	1130
753.ns3_r	512	157	2000	156	2010	156	2010	512	157	2000	156	2010	156	2010
777.zstd_r	512	496	664	496	665	496	664	512	496	664	496	665	496	664

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Notes

The AMD64 AOCC Compiler Suite is available at
<http://developer.amd.com/amd-aocc/>

Submit Notes

The config file option 'submit' was used.
'numactl' was used to bind copies to the cores.
See the configuration file for details.

Operating System Notes

'ulimit -s unlimited' was used to set environment stack size limit
'ulimit -l 2097152' was used to set environment locked pages in memory limit

runcpu command invoked through numactl i.e.:
numactl --interleave=all runcpu <etc>

To limit dirty cache to 8% of memory, 'sysctl -w vm.dirty_ratio=8' run as root.
To limit swap usage to minimum necessary, 'sysctl -w vm.swappiness=1' run as root.

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Operating System Notes (Continued)

To free node-local memory and avoid remote memory usage,
'sysctl -w vm.zone_reclaim_mode=1' run as root.
To clear filesystem caches, 'sync; sysctl -w vm.drop_caches=3' run as root.
To disable address space layout randomization (ASLR) to reduce run-to-run
variability, 'sysctl -w kernel.randomize_va_space=0' run as root.
To enable Transparent Hugepages (THP) for all allocations,
'echo always > /sys/kernel/mm/transparent_hugepage/enabled' and
'echo always > /sys/kernel/mm/transparent_hugepage/defrag' run as root.

Environment Variables Notes

Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH =
"/cpu2026/amd_rate_aocc520_znver5_A_lib/lib:/cpu2026/amd_rate_aocc520_zn
ver5_A_lib/lib32:"
MALLOC_CONF = "retain:true"

General Notes

Binaries were compiled on a system with 2x AMD EPYC Venice256 CPU + 2TiB Memory using Ubuntu 24.04
jemalloc: configured and built with GCC v15.2.0 in Ubuntu 24.04 (No options specified)
jemalloc 5.3.1 is available here:
<https://github.com/jemalloc/jemalloc/releases/tag/5.3.1>

Platform Notes

BIOS settings:
TDP: 500
Determinism Enable: Power
PPT: 500
NUMA Nodes Per Socket: NPS4
SMT Control : Enable
Power Profile Selection : High Performance Mode
ACPI CST C2 Latency : 18
DF Cstates: Disable
DRAM Scrub Time: Disable
Global C-state Control: Disable
SVM mode: Disable
SMEE: disable
GMI Folding: Disable

Sysinfo program /cpu2026/bin/sysinfo

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Platform Notes (Continued)

Rev: 779ab21020787073335a329f3a45e2cd
running on localhost Wed Aug 12 23:48:40 2026

SUT (System Under Test) info as seen by some common utilities.

Table of contents

1. uname -srvm
2. w
3. Username
4. ulimit -a
5. sysinfo process ancestry
6. /proc/cpuinfo
7. lscpu
8. numactl --hardware
9. /proc/meminfo
10. who -r
11. Systemd service manager version: systemd 254 (254.24+suse.148.g83b9060b6e)
12. Failed units, from systemctl list-units --state=failed
13. Services, from systemctl list-unit-files
14. Linux kernel boot-time arguments, from /proc/cmdline
15. cpupower frequency-info
16. sysctl
17. /sys/kernel/mm/transparent_hugepage
18. /sys/kernel/mm/transparent_hugepage/khugepaged
19. OS release
20. Disk information
21. /sys/devices/virtual/dmi/id
22. dmidecode
23. BIOS

1. uname -srvm
Linux 6.4.0-150700.51-default #1 SMP PREEMPT_DYNAMIC Wed Apr 30 21:35:43 UTC 2025 (6930611) x86_64

2. w
23:48:40 up 5 min, 2 users, load average: 0.61, 0.18, 0.06
USER TTY FROM LOGIN@ IDLE JCPU PCPU WHAT
root pts/0 192.168.68.2 23:45 43.00s 16.26s 15.20s python3 ./run_amd_rate_aocc520_znver5_A1.py

3. Username
From environment variable \$USER: root

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Platform Notes (Continued)

4. ulimit -a

```
core file size          (blocks, -c) unlimited
data seg size           (kbytes, -d) unlimited
scheduling priority     (-e) 0
file size               (blocks, -f) unlimited
pending signals         (-i) 6189424
max locked memory       (kbytes, -l) 2048
max memory size         (kbytes, -m) unlimited
open files              (-n) 1024
pipe size               (512 bytes, -p) 8
POSIX message queues    (bytes, -q) 819200
real-time priority      (-r) 0
stack size              (kbytes, -s) unlimited
cpu time                (seconds, -t) unlimited
max user processes      (-u) 6189424
virtual memory          (kbytes, -v) unlimited
file locks              (-x) unlimited
```

5. sysinfo process ancestry

```
/usr/lib/systemd/systemd --switched-root --system --deserialize=42
sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups
sshd: root [priv]
sshd: root@pts/0
-bash
python3 ./run_amd_rate_aocc520_znver5_A1.py
runcpu --config amd_rate_aocc520_znver5_A1.cfg --tune base --reportable --iterations 3 intrate
runcpu --configfile amd_rate_aocc520_znver5_A1.cfg --tune base --reportable --iterations 3 --nopower
--runmode rate --tune base --size test:train:refrate intrate --nopreenv --note-preenv --logfile
$SPEC/tmp/CPU2026.001/templogs/preenv.intrate.001.0.log --lognum 001.0 --from_runcpu 2
specperl $SPEC/bin/sysinfo
$SPEC = /cpu2026
```

6. /proc/cpuinfo

```
model name      : AMD EPYC 9755 128-Core Processor
vendor_id       : AuthenticAMD
cpu family      : 26
model           : 2
stepping        : 1
microcode       : 0xb00215a
bugs            : sysret_ss_attrs spectre_v1 spectre_v2 spec_store_bypass srso
TLB size        : 192 4K pages
cpu cores       : 128
siblings        : 256
2 physical ids (chips)
```

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Platform Notes (Continued)

512 processors (hardware threads)

physical id 0: core ids 0-127

physical id 1: core ids 0-127

physical id 0: apicids 0-255

physical id 1: apicids 256-511

Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for virtualized systems. Use the above data carefully.

7. lscpu

From lscpu from util-linux 2.40.4:

Architecture: x86_64
CPU op-mode(s): 32-bit, 64-bit
Address sizes: 52 bits physical, 57 bits virtual
Byte Order: Little Endian
CPU(s): 512
On-line CPU(s) list: 0-511
Vendor ID: AuthenticAMD
Model name: AMD EPYC 9755 128-Core Processor
CPU family: 26
Model: 2
Thread(s) per core: 2
Core(s) per socket: 128
Socket(s): 2
Stepping: 1
Frequency boost: enabled
CPU(s) scaling MHz: 100%
CPU max MHz: 4121.0000
CPU min MHz: 1200.0000
BogoMIPS: 5391.91

Flags:

fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
pse36 clflush mmx fxsr sse sse2 ht syscall nx mmxext fxsr_opt pdpe1gb
rdtscp lm constant_tsc rep_good amd_lbr_v2 nopl nonstop_tsc cpuid
extd_apicid aperfmperf rapl pni pclmulqdq monitor ssse3 fma cx16 pcid
sse4_1 sse4_2 x2apic movbe popcnt aes xsave avx f16c rdrand lahf_lm
cmp_legacy extapic cr8_legacy abm sse4a misalignsse 3dnowprefetch
osvw ibs skinit wdt tce topoext perfctr_core perfctr_nb bpext
perfctr_llc mwaitx cpb cat_l3 cdp_l3 hw_pstate ssbd mba perfmon_v2
ibrs ibpb stibp ibrs_enhanced vmmcall fsgsbase tsc_adjust bmi1 avx2
smep bmi2 erms invpcid cqm rdt_a avx512f avx512dq rdseed adx smap
avx512ifma clflushopt clwb avx512cd sha_ni avx512bw avx512vl xsaveopt
xsavec xgetbv1 xsaves cqm_llc cqm_occup_llc cqm_mbm_total
cqm_mbm_local user_shstk avx_vnni avx512_bf16 clzero irperf
xsaveerptr rdpru wbnoinvd amd_ppin cppc amd_ibpb_ret arat npt lbrv
svm_lock nrip_save tsc_scale vmcb_clean flushbyasid decodeassists
pausefilter pfthreshold avic v_vmsave_vmload vgif x2avic v_spec_ctrl

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Platform Notes (Continued)

vnmi avx512vbmi umip pku ospke avx512_vbmi2 gfni vaes vpclmulqdq
avx512_vnni avx512_bitalg avx512_vpopcntdq la57 rdpid bus_lock_detect
movdiri movdir64b overflow_recov succor smca fsrm avx512_vp2intersect
flush_l1d debug_swap hv_inuse_wr_allowed srso_user_kernel_no
amd_lbr_pmc_freeze

L1d cache: 12 MiB (256 instances)
L1i cache: 8 MiB (256 instances)
L2 cache: 256 MiB (256 instances)
L3 cache: 1 GiB (32 instances)

NUMA node(s): 8
NUMA node0 CPU(s): 0-31, 256-287
NUMA node1 CPU(s): 32-63, 288-319
NUMA node2 CPU(s): 64-95, 320-351
NUMA node3 CPU(s): 96-127, 352-383
NUMA node4 CPU(s): 128-159, 384-415
NUMA node5 CPU(s): 160-191, 416-447
NUMA node6 CPU(s): 192-223, 448-479
NUMA node7 CPU(s): 224-255, 480-511

Vulnerability Gather data sampling: Not affected
Vulnerability Itlb multihit: Not affected
Vulnerability L1tf: Not affected
Vulnerability Mds: Not affected
Vulnerability Meltdown: Not affected
Vulnerability Mmio stale data: Not affected
Vulnerability Reg file data sampling: Not affected
Vulnerability Retbleed: Not affected
Vulnerability Spec rstack overflow: Mitigation; IBPB on VMEXIT only
Vulnerability Spec store bypass: Mitigation; Speculative Store Bypass disabled via prctl
Vulnerability Spectre v1: Mitigation; usercopy/swapgs barriers and __user pointer sanitization
Vulnerability Spectre v2: Mitigation; Enhanced / Automatic IBRS; IBPB conditional; STIBP
always-on; RSB filling; PBRSE-eIBRS Not affected; BHI Not affected
Vulnerability Srbds: Not affected
Vulnerability Tsx async abort: Not affected

From lscpu --cache:

NAME	ONE-SIZE	ALL-SIZE	WAYS	TYPE	LEVEL	SETS	PHY-LINE	COHERENCY-SIZE
L1d	48K	12M	12	Data	1	64	1	64
L1i	32K	8M	8	Instruction	1	64	1	64
L2	1M	256M	16	Unified	2	1024	1	64
L3	32M	1G	16	Unified	3	32768	1	64

8. numactl --hardware

NOTE: a numactl 'node' might or might not correspond to a physical chip.

available: 8 nodes (0-7)
node 0 cpus: 0-31, 256-287
node 0 size: 192977 MB

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Platform Notes (Continued)

```
node 0 free: 192394 MB
node 1 cpus: 32-63,288-319
node 1 size: 193518 MB
node 1 free: 192982 MB
node 2 cpus: 64-95,320-351
node 2 size: 193518 MB
node 2 free: 192958 MB
node 3 cpus: 96-127,352-383
node 3 size: 193518 MB
node 3 free: 192809 MB
node 4 cpus: 128-159,384-415
node 4 size: 193518 MB
node 4 free: 193061 MB
node 5 cpus: 160-191,416-447
node 5 size: 193518 MB
node 5 free: 193064 MB
node 6 cpus: 192-223,448-479
node 6 size: 193518 MB
node 6 free: 191686 MB
node 7 cpus: 224-255,480-511
node 7 size: 193292 MB
node 7 free: 192829 MB
node distances:
node  0  1  2  3  4  5  6  7
  0: 10 12 12 12 32 32 32 32
  1: 12 10 12 12 32 32 32 32
  2: 12 12 10 12 32 32 32 32
  3: 12 12 12 10 32 32 32 32
  4: 32 32 32 32 10 12 12 12
  5: 32 32 32 32 12 10 12 12
  6: 32 32 32 32 12 12 10 12
  7: 32 32 32 32 12 12 12 10
```

9. /proc/meminfo

MemTotal: 1584521528 kB

10. who -r

run-level 3 Aug 12 23:43

11. Systemd service manager version: systemd 254 (254.24+suse.148.g83b9060b6e)

Default Target Status
multi-user degraded

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Platform Notes (Continued)

12. Failed units, from systemctl list-units --state=failed

UNIT	LOAD	ACTIVE	SUB	DESCRIPTION
* firewall.service	loaded	failed	failed	firewalld - dynamic firewall daemon
* kdump-early.service	loaded	failed	failed	Load kdump kernel early on startup
* kdump.service	loaded	failed	failed	Load kdump kernel and initrd
* NetworkManager-wait-online.service	loaded	failed	failed	Network Manager Wait Online

13. Services, from systemctl list-unit-files

STATE	UNIT FILES
enabled	ModemManager NetworkManager NetworkManager-dispatcher NetworkManager-wait-online YaST2-Firstboot YaST2-Second-Stage apparmor appstream-sync-cache auditd bluetooth chronyd cron display-manager firewalld getty@ irqbalance issue-generator kbdsettings kdump kdump-early kdump-notify klog lvm2-monitor nsd nvme-fc-boot-connections nvme-f-autoconnect postfix purge-kernels rollback rsyslog smartd sshd systemd-pstore wpa_supplicant
enabled-runtime	systemd-remount-fs
disabled	accounts-daemon autofs autoyast-initscripts blk-availability bluetooth-mesh boot-sysctl ca-certificates chrony-wait console-getty cups cups-browsed debug-shell dnsmasq ebttables exchange-bmc-os-info fsidd gpm grub2-once haveged hwloc-dump-hwdata ipmi ipmievd issue-add-ssh-keys kexec-load ksm kvm_stat lunmask man-db-create mariadb mariadb@ multipathd munge nfs nfs-blkmap nmb ntp-wait ntpd ostree-remount ostree-state-overlay@ rpcbind rpmconfigcheck rsyncd rtkit-daemon salt-minion samba-bgqd serial-getty@ slurmd smartd_generate_opts smb snmpd snmptrapd speech-dispatcherd svnserv systemd-boot-check-no-failures systemd-confext systemd-network-generator systemd-sysext systemd-time-wait-sync systemd-timesyncd udisks2 update-system-flatpaks upower vncserver@ wicked wickedd-auto4 wickedd-dhcp4 wickedd-dhcp6 wickedd-nanny wpa_supplicant@ ypbind
indirect	systemd-userdbd wickedd
masked	packagekit

14. Linux kernel boot-time arguments, from /proc/cmdline

BOOT_IMAGE=/boot/vmlinuz-6.4.0-150700.51-default
root=UUID=03f2994f-ee68-4440-b1db-7d3f781cf8b4
splash=silent
mitigations=auto
quiet
security=apparmor
crashkernel=380M,high
crashkernel=72M,low,
amd_pstate=passive

15. cpupower frequency-info

analyzing CPU 479:
current policy: frequency should be within 1.20 GHz and 4.12 GHz.
The governor "performance" may decide which speed to use
within this range.

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Platform Notes (Continued)

boost state support:

Supported: yes

Active: yes

16. sysctl

kernel.numa_balancing	1
kernel.randomize_va_space	0
vm.compaction_proactiveness	20
vm.dirty_background_bytes	0
vm.dirty_background_ratio	10
vm.dirty_bytes	0
vm.dirty_expire_centisecs	3000
vm.dirty_ratio	8
vm.dirty_writeback_centisecs	500
vm.dirtytime_expire_seconds	43200
vm.extfrag_threshold	500
vm.min_unmapped_ratio	1
vm.nr_hugepages	0
vm.nr_hugepages_mempolicy	0
vm.nr_overcommit_hugepages	0
vm.swappiness	1
vm.watermark_boost_factor	15000
vm.watermark_scale_factor	10
vm.zone_reclaim_mode	1

17. /sys/kernel/mm/transparent_hugepage

defrag	[always]	defer	defer+madvise	madvise	never
enabled	[always]	madvise	never		
hpage_pmd_size	2097152				
shmem_enabled	always	within_size	advise	[never]	deny force

18. /sys/kernel/mm/transparent_hugepage/khugepaged

alloc_sleep_millisecs	60000
defrag	1
max_ptes_none	511
max_ptes_shared	256
max_ptes_swap	64
pages_to_scan	4096
scan_sleep_millisecs	10000

19. OS release

From /etc/*-release /etc/*-version
os-release SUSE Linux Enterprise Server 15 SP7

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Platform Notes (Continued)

20. Disk information

SPEC is set to: /cpu2026

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/nvme0n1p2	btrfs	1.0T	68G	955G	7%	/

21. /sys/devices/virtual/dmi/id

Vendor: COMPAL
Product: COMPAL SERVER
Product Family: COMPAL
Serial: 7901567500001

22. dmidecode

Additional information from dmidecode 3.7 follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

Memory:

24x Unknown A5-RE1BH64M64-RP1R4R 64 GIB 2 rank 6400

23. BIOS

(This section combines info from /sys/devices and dmidecode.)

BIOS Vendor: American Megatrends International, LLC.
BIOS Version: 10.28.00
BIOS Date: 01/29/2026
BIOS Revision: 5.35
Firmware Revision: 5.35

Compiler Version Notes

C | 708.sqlite_r(base) 714.cpython_r(base) 777.zstd_r(base)

AMD clang version 17.0.6 (CLANG: AOCC_5.2.0-Build#2035 2026_04_10)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-5.2.0-4925-2035/bin

C++ | 706.stockfish_r(base) 707.ntest_r(base) 727.cppcheck_r(base)

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Compiler Version Notes (Continued)

| 753.ns3_r(base)

AMD clang version 17.0.6 (CLANG: AOCC_5.2.0-Build#2035 2026_04_10)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-5.2.0-4925-2035/bin

=====
C++, C | 710.omnetpp_r(base) 721.gcc_r(base) 723.llvm_r(base) 729.abc_r(base)
734.vpr_r(base) 735.gem5_r(base) 750.sealcrypto_r(base)

AMD clang version 17.0.6 (CLANG: AOCC_5.2.0-Build#2035 2026_04_10)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-5.2.0-4925-2035/bin

Base Compiler Invocation

C benchmarks:

clang

C++ benchmarks:

clang++

Benchmarks using both C and C++:

clang++ clang

Base Optimization Flags

C benchmarks:

-std=c18 -no-pie -Wl,-mllvm -Wl,-inline-threshold=1500 -fstrip-mining
-O3 -march=znver5 -fveclib=AMDLIBM -flto -fno-PIE -fno-plt
-fremap-arrays -mllvm -inline-threshold=1500 -ljemalloc -lamdlibm

C++ benchmarks:

-std=c++17 -no-pie -Wl,-mllvm -Wl,-inline-threshold=1500 -O3
-march=znver5 -fveclib=AMDLIBM -flto -fno-PIE -fno-plt
-fvirtual-function-elimination -fvisibility=hidden
-mllvm -inline-threshold=1500 -stdlib=libc++ -ljemalloc -lamdlibm

Benchmarks using both C and C++:

-std=c++17 -std=c18 -no-pie -Wl,-mllvm -Wl,-inline-threshold=1500 -O3

(Continued on next page)



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A
AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

Base Optimization Flags (Continued)

Benchmarks using both C and C++ (continued):

-march=znver5 -fveclib=AMDLIBM -flt0 -fno-PIE -fno-plt
-fremap-arrays -mllvm -inline-threshold=1500
-fvirtual-function-elimination -fvisibility=hidden -stdlib=libc++
-ljemalloc -lamdlibm

Peak Optimization Flags

C benchmarks:

708.sqlite_r: basepeak = yes

714.cpython_r: basepeak = yes

777.zstd_r: basepeak = yes

C++ benchmarks:

706.stockfish_r: basepeak = yes

707.ntest_r: basepeak = yes

727.cppcheck_r: basepeak = yes

753.ns3_r: basepeak = yes

Benchmarks using both C and C++:

710.omnetpp_r: basepeak = yes

721.gcc_r: basepeak = yes

723.llvm_r: basepeak = yes

729.abc_r: basepeak = yes

734.vpr_r: basepeak = yes

735.gem5_r: basepeak = yes

750.sealcrypto_r: basepeak = yes



SPEC CPU®2026 Integer Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Compal Electronics, Inc.

SR224-2A

AMD EPYC 9755

SPECrate®2026_int_base = 1080

SPECrate®2026_int_peak = 1080

CPU2026 License: 6857

Test Sponsor: Compal Electronics, Inc.

Tested by: Compal Electronics, Inc.

Test Date: Aug-2026

Hardware Availability: Jul-2025

Software Availability: May-2026

The flags files that were used to format this result can be browsed at

http://www.spec.org/cpu2026/results/flags/Compal-Platform-Flags-Linux-AMD_V1.7.html

<http://www.spec.org/cpu2026/results/flags/aocc-flags.2026-08-11.html>

You can also download the XML flags sources by saving the following links:

http://www.spec.org/cpu2026/results/flags/Compal-Platform-Flags-Linux-AMD_V1.7.xml

<http://www.spec.org/cpu2026/results/flags/aocc-flags.2026-08-11.xml>

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2026 v1.0.1 on 2026-08-12 11:48:40-0400.

Report generated on 2026-09-08 18:11:04 by CPU2026 PDF formatter (unknown).

Originally published on 2026-09-08.