



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

xFusion


xFusion FusionServer 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_sml_base = 1.77

SPEChpc 2021_sml_peak = 1.77

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Dec-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023



Results Table

Benchmark	Base								Peak									
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
605.lbm_s	MPI	240	1	671	2.31	656	2.36	644	2.41	MPI	240	1	671	2.31	656	2.36	644	2.41
613.soma_s	MPI	240	1	765	2.09	766	2.09	766	2.09	MPI	240	1	765	2.09	766	2.09	766	2.09
618.tealeaf_s	MPI	240	1	2099	0.977	2096	0.978	2098	0.977	MPI	240	1	2099	0.977	2096	0.978	2098	0.977
619.clvleaf_s	MPI	240	1	1531	1.08	1532	1.08	1531	1.08	MPI	240	1	1531	1.08	1532	1.08	1531	1.08
621.miniswp_s	MPI	240	1	399	2.76	399	2.76	399	2.75	MPI	240	1	399	2.76	399	2.76	399	2.75
628.pot3d_s	MPI	240	1	1800	0.930	1803	0.929	1802	0.930	MPI	240	1	1800	0.930	1803	0.929	1802	0.930
632.sph_exa_s	MPI	240	1	438	5.25	436	5.27	439	5.24	MPI	240	1	438	5.25	436	5.27	439	5.24
634.hpgmgfv_s	MPI	240	1	935	1.04	936	1.04	935	1.04	MPI	240	1	935	1.04	936	1.04	935	1.04
635.weather_s	MPI	240	1	1133	2.29	1135	2.29	1134	2.29	MPI	240	1	1133	2.29	1135	2.29	1134	2.29

SPEChpc 2021_sml_base = 1.77

SPEChpc 2021_sml_peak = 1.77

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

xFusion

xFusion FusionServer 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_sml_base = 1.77

SPEChpc 2021_sml_peak = 1.77

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Dec-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Hardware Summary

Type of System: Homogenous Cluster
Compute Node: xFusion FusionServer 2288H V7
Interconnect: Mellanox HDR
Node Node: xFusion FusionServer 2288H V7
Compute Nodes Used: 2
Total Chips: 4
Total Cores: 240
Total Threads: 240
Total Memory: 1 TB
Max. Peak Threads: 1

Software Summary

Compiler: Intel oneAPI Compiler 2023.0.0
MPI Library: Intel MPI Library 2021.8 for Linux OS
Other MPI Info: None
Other Software: None
Base Parallel Model: MPI
Base Ranks Run: 240
Base Threads Run: 1
Peak Parallel Models: MPI
Minimum Peak Ranks: 240
Maximum Peak Ranks: 240
Max. Peak Threads: 1
Min. Peak Threads: 1

Node Description: xFusion FusionServer 2288H V7

Hardware

Number of nodes: 2
Uses of the node: Compute Node
Vendor: xFusion
Model: xFusion FusionServer 2288H V7
CPU Name: Intel Xeon Platinum 8490H
CPU(s) orderable: 1, 2 chips
Chips enabled: 2
Cores enabled: 120
Cores per chip: 60
Threads per core: 1
CPU Characteristics: Turbo Boost Technology up to 3.5 GHz
CPU MHz: 1900
Primary Cache: 32 KB I + 48 KB D on chip per core
Secondary Cache: 2 MB I+D on chip per core
L3 Cache: 112.5 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (16 x 32 GB 2Rx8 PC5-4800B-R)
Disk Subsystem: 1 x 7.68 TB NVMe SSD
Other Hardware: None
Accel Count: 0
Accel Model: None
Accel Vendor: None
Accel Type: None
Accel Connection: None
Accel ECC enabled: None
Accel Description: None
Adapter: MCX653105A-EFAT
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 100 Gb/s
Ports Used: 1
Interconnect Type: Mellanox HDR

Software

Accelerator Driver: None
Adapter: MCX653105A-EFAT
Adapter Driver: 5.4-3.1.0
Adapter Firmware: 20.32.1010
Operating System: Rocky Linux release 8.7 (Green Obsidian) 4.18.0-425.3.1.el8.x86_64
Local File System: xfs
Shared File System: NFS
System State: Multi-user, run level 3
Other Software: N/A



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

xFusion

xFusion FusionServer 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_sml_base = 1.77

SPEChpc 2021_sml_peak = 1.77

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Dec-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Interconnect Description: Mellanox HDR

Hardware

Software

Vendor: Mellanox
Model: Mellanox HDR
Switch Model: Mellanox MQM8790-HS2F InfiniBand Switch
Number of Switches: 1
Number of Ports: 40
Data Rate: 200 Gbit/s
Firmware: 27.2010.1202
Topology: Mesh
Primary Use: MPI

: --

Submit Notes

The config file option 'submit' was used.

Compiler Version Notes

=====
CXXC 632.sph_exa_s(base)

Intel(R) oneAPI DPC++/C++ Compiler 2023.0.0 (2023.0.0.20221201)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /share/app/intel/2023.0.0/compiler/latest/linux/bin-llvm
Configuration file:
/share/app/intel/2023.0.0/compiler/latest/linux/bin-llvm/./bin/icpx.cfg

=====
CC 605.lbm_s(base) 613.soma_s(base) 618.tealeaf_s(base) 621.miniswp_s(base)
634.hpgmgfv_s(base)

Intel(R) oneAPI DPC++/C++ Compiler 2023.0.0 (2023.0.0.20221201)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /share/app/intel/2023.0.0/compiler/latest/linux/bin-llvm
Configuration file:
/share/app/intel/2023.0.0/compiler/latest/linux/bin-llvm/./bin/icx.cfg

=====
FC 619.clvleaf_s(base) 628.pot3d_s(base) 635.weather_s(base)

ifx (IFORT) 2023.0.0 20221201

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

xFusion

xFusion FusionServer 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_sml_base = 1.77

SPEChpc 2021_sml_peak = 1.77

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Dec-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Compiler Version Notes (Continued)

Copyright (C) 1985-2022 Intel Corporation. All rights reserved.

Base Compiler Invocation

C benchmarks:

```
mpiicc -cc=icx
```

C++ benchmarks:

```
mpiicpc -cxx=icpx
```

Fortran benchmarks:

```
mpiifort -fc=ifx
```

Base Portability Flags

```
605.lbm_s: -lstdc++ -std=c++14  
613.soma_s: -lstdc++ -std=c++14  
618.tealeaf_s: -lstdc++ -std=c++14  
621.miniswp_s: -lstdc++ -std=c++14  
634.hpgmgfv_s: -lstdc++ -std=c++14
```

Base Optimization Flags

C benchmarks:

```
-O3 -Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -ffast-math -flto  
-funroll-loops
```

C++ benchmarks:

```
-O3 -Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -ffast-math -flto  
-funroll-loops
```

Fortran benchmarks:

```
-O3 -Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -ffast-math -flto  
-funroll-loops -nostandard-realloc-lhs -align array64byte
```



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

xFusion

xFusion FusionServer 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_sml_base = 1.77

SPEChpc 2021_sml_peak = 1.77

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Dec-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Base Other Flags

C benchmarks:
-Wno-incompatible-function-pointer-types

Peak Optimization Flags

C benchmarks:
605.lbm_s: basepeak = yes
613.soma_s: basepeak = yes
618.tealeaf_s: basepeak = yes
621.miniswp_s: basepeak = yes
634.hpgmgfv_s: basepeak = yes
C++ benchmarks:
632.sph_exa_s: basepeak = yes
Fortran benchmarks:
619.clvleaf_s: basepeak = yes
628.pot3d_s: basepeak = yes
635.weather_s: basepeak = yes

The flags file that was used to format this result can be browsed at
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.8 on 2023-12-13 04:59:24-0500.
Report generated on 2024-01-10 17:34:39 by hpc2021 PDF formatter v1.0.3.
Originally published on 2024-01-10.