



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel


Endeavour: Intel Server D50DNP1SBB (Intel Xeon Platinum 8592+)

SPEChpc 2021_tny_base = 19.2

SPEChpc 2021_tny_peak = 20.5

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2024
Hardware Availability: Dec-2023
Software Availability: Mar-2024



Results Table

Benchmark	Base										Peak							
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
505.lbm_t	OMP	8	32	98.2	22.9	103	21.9	103	21.8	OMP	8	32	98.2	22.9	103	21.9	103	21.8
513.soma_t	OMP	8	32	142	26.1	142	26.1	148	25.0	OMP	8	32	142	26.1	142	26.0	142	26.1
518.tealeaf_t	OMP	8	32	87.4	18.9	87.1	19.0	87.2	18.9	OMP	8	32	86.9	19.0	87.6	18.8	87.1	18.9
519.clvleaf_t	OMP	8	32	154	10.7	154	10.7	154	10.7	OMP	8	32	145	11.3	145	11.4	145	11.4
521.miniswp_t	OMP	8	32	94.2	17.0	94.1	17.0	94.3	17.0	OMP	8	32	94.2	17.0	94.1	17.0	94.3	17.0
528.pot3d_t	OMP	8	32	178	12.0	177	12.0	177	12.0	OMP	32	8	144	14.8	143	14.8	143	14.8
532.sph_exa_t	OMP	8	32	96.0	20.3	96.8	20.1	95.5	20.4	OMP	8	32	96.0	20.3	96.8	20.1	95.5	20.4
534.hpgmgfv_t	OMP	8	32	101	11.7	101	11.7	100	11.7	OMP	8	32	101	11.7	101	11.7	100	11.7
535.weather_t	OMP	8	32	50.0	64.4	49.9	64.6	49.9	64.6	OMP	128	2	37.2	86.7	37.7	85.6	37.2	86.7

SPEChpc 2021_tny_base = 19.2

SPEChpc 2021_tny_peak = 20.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP1SBB (Intel Xeon Platinum 8592+)

SPEChpc 2021_tny_base = 19.2

SPEChpc 2021_tny_peak = 20.5

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2024
Hardware Availability: Dec-2023
Software Availability: Mar-2024

Hardware Summary

Type of System: Homogenous Cluster
Compute Node: Intel Server D50DNP1SBB (Xeon 8592+)
Interconnect: Mellanox HDR
Compute Nodes Used: 1
Total Chips: 2
Total Cores: 128
Total Threads: 256
Total Memory: 512 GB
Max. Peak Threads: 32

Software Summary

Compiler: Intel oneAPI Compiler 2024.1.0
MPI Library: Intel MPI Library 2021.12 for Linux OS
Other MPI Info: None
Other Software: None
Base Parallel Model: OMP
Base Ranks Run: 8
Base Threads Run: 32
Peak Parallel Models: OMP
Minimum Peak Ranks: 8
Maximum Peak Ranks: 128
Max. Peak Threads: 32
Min. Peak Threads: 2

Node Description: Intel Server D50DNP1SBB (Xeon 8592+)

Hardware

Number of nodes: 1
Uses of the node: Compute
Vendor: Intel
Model: Intel Server D50DNP1SBB (Xeon 8592+)
CPU Name: Intel Xeon Platinum 8592+
CPU(s) orderable: 1, 2 chips
Chips enabled: 2
Cores enabled: 128
Cores per chip: 64
Threads per core: 2
CPU Characteristics: Turbo Boost Technology up to 3.9 GHz
CPU MHz: 1900
Primary Cache: 32 KB I + 48 KB D on chip per core
Secondary Cache: 2 MB I+D on chip per core
L3 Cache: 320 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (16 x 32 GB 2Rx8 PC5-5600B-R)
Disk Subsystem: 1 x 1 TB NVMe U.2 2.5" SSD
Other Hardware: None
Accel Count: None
Accel Model: None
Accel Vendor: None
Accel Type: None
Accel Connection: None
Accel ECC enabled: None
Accel Description: None
Adapter: Mellanox ConnectX-6 HDR
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 200Gbit/s
Ports Used: 1
Interconnect Type: Mellanox HDR

Software

Accelerator Driver: None
Adapter: Mellanox ConnectX-6 HDR
Adapter Driver: 23.04-0.5.3
Adapter Firmware: 20.37.1014
Operating System: Rocky Linux 8.8 (Green Obsidian)
4.18.0-477.15.1.el8_8.x86_64
Local File System: xfs
Shared File System: PANASAS FS
System State: Run level 5
Other Software: None



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP1SBB (Intel Xeon Platinum 8592+)

SPEChpc 2021_tny_base = 19.2

SPEChpc 2021_tny_peak = 20.5

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2024
Hardware Availability: Dec-2023
Software Availability: Mar-2024

Interconnect Description: Mellanox HDR

Hardware

Software

Vendor: Mellanox
Model: Mellanox HDR
Switch Model: Mellanox MQM8790-HS2F Quantum HDR InfiniBand Switch
Number of Switches: 18
Number of Ports: 40
Data Rate: 200 Gbit/s
Firmware: 20.36.1010
Topology: Fat-tree
Primary Use: MPI Traffic

: --

Submit Notes

The config file option 'submit' was used.

General Notes

The PANASAS filesystem as described on this result page was formerly generally available. At the time of this publication, it may not be shipping, and/or may not be supported, and/or may fail to meet other tests of General Availability described in the SPEC HPG Policy document, <http://www.spec.org/hpg/policy.html>

Compiler Version Notes

=====
CXXC 532.sph_exa_t(base, peak)

Intel(R) oneAPI DPC++/C++ Compiler 2024.1.0 (2024.1.0.20240308)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir:
/global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler
Configuration file:
/global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler/./icpx.cfg

=====
CC 505.lbm_t(base, peak) 513.soma_t(base, peak) 518.tealeaf_t(base, peak)
521.miniswp_t(base, peak) 534.hpgmgfv_t(base, peak)

Intel(R) oneAPI DPC++/C++ Compiler 2024.1.0 (2024.1.0.20240308)
Target: x86_64-unknown-linux-gnu

(Continued on next page)



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP1SBB (Intel Xeon Platinum 8592+)

SPEChpc 2021_tny_base = 19.2

SPEChpc 2021_tny_peak = 20.5

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2024
Hardware Availability: Dec-2023
Software Availability: Mar-2024

Compiler Version Notes (Continued)

```

Thread model: posix
InstalledDir:
  /global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler
Configuration file:
  /global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler/./icx.cfg
-----

=====
FC 519.clvleaf_t(base, peak) 528.pot3d_t(base, peak) 535.weather_t(base,
  peak)
-----

ifx (IFX) 2024.1.0 20240308
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.
-----

```

Base Compiler Invocation

```

C benchmarks:
mpiicc -cc=icx

C++ benchmarks:
mpiicpc -cxx=icpx

Fortran benchmarks:
mpiifort -fc=ifx

```

Base Portability Flags

```

505.lbm_t: -lstdc++ -std=c++14
513.soma_t: -lstdc++ -std=c++14
518.tealeaf_t: -lstdc++ -std=c++14
521.miniswp_t: -lstdc++ -std=c++14
534.hpgmgfv_t: -lstdc++ -std=c++14

```

Base Optimization Flags

```

C benchmarks:
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto
-funroll-loops

```

(Continued on next page)



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP1SBB (Intel Xeon Platinum 8592+)

SPEChpc 2021_tny_base = 19.2

SPEChpc 2021_tny_peak = 20.5

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2024
Hardware Availability: Dec-2023
Software Availability: Mar-2024

Base Optimization Flags (Continued)

C++ benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto  
-funroll-loops
```

Fortran benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto  
-funroll-loops -nostandard-realloc-lhs -align array64byte
```

Base Other Flags

C benchmarks:

```
-Wno-incompatible-function-pointer-types
```

Peak Compiler Invocation

C benchmarks:

```
mpiicc -cc=icx
```

C++ benchmarks:

```
mpiicpc -cxx=icpx
```

Fortran benchmarks:

```
mpiifort -fc=ifx
```

Peak Portability Flags

```
505.lbm_t: -lstdc++ -std=c++14  
513.soma_t: -lstdc++ -std=c++14  
518.tealeaf_t: -lstdc++ -std=c++14  
521.miniswp_t: -lstdc++ -std=c++14  
534.hpgmgfv_t: -lstdc++ -std=c++14
```



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP1SBB (Intel Xeon Platinum 8592+)

SPEChpc 2021_tny_base = 19.2

SPEChpc 2021_tny_peak = 20.5

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2024
Hardware Availability: Dec-2023
Software Availability: Mar-2024

Peak Optimization Flags

C benchmarks:

505.lbm_t: basepeak = yes

513.soma_t: -O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp
-ffast-math -flto -funroll-loops

518.tealeaf_t: Same as 513.soma_t

521.miniswp_t: basepeak = yes

534.hpgmgfv_t: basepeak = yes

C++ benchmarks:

532.sph_exa_t: basepeak = yes

Fortran benchmarks:

519.clvleaf_t: -O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp
-ffast-math -flto -funroll-loops
-qopt-streaming-stores=always -nostandard-realloc-lhs
-align array64byte

528.pot3d_t: -O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp
-ffast-math -flto -funroll-loops -nostandard-realloc-lhs
-align array64byte

535.weather_t: Same as 528.pot3d_t

Peak Other Flags

C benchmarks:

-Wno-incompatible-function-pointer-types

The flags file that was used to format this result can be browsed at

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2024-12-11.html



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP1SBB (Intel Xeon Platinum 8592+)

SPEChpc 2021_tny_base = 19.2

SPEChpc 2021_tny_peak = 20.5

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2024
Hardware Availability: Dec-2023
Software Availability: Mar-2024

You can also download the XML flags source by saving the following link:

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2024-12-11.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.8 on 2024-04-18 06:41:27-0400.
Report generated on 2024-12-31 10:29:46 by hpc2021 PDF formatter v1.0.3.
Originally published on 2024-12-25.