



# SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

## Intel

SPEChpc 2021\_tny\_base = 12.1

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021\_tny\_peak = 12.4

hpc2021 License: 13


Test Date: Apr-2024

Test Sponsor: Intel

Hardware Availability: Jan-2023

Tested by: Intel

Software Availability: Mar-2024



## Results Table

Benchmark	Base								Peak									
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
505.lbm_t	OMP	8	14	<b>178</b>	<b>12.7</b>	171	13.1	178	12.6	OMP	8	14	<b>178</b>	<b>12.7</b>	171	13.1	178	12.6
513.soma_t	OMP	8	14	339	10.9	339	10.9	<b>339</b>	<b>10.9</b>	OMP	8	14	339	10.9	339	10.9	<b>339</b>	<b>10.9</b>
518.tealeaf_t	OMP	8	14	130	12.7	<b>131</b>	<b>12.6</b>	132	12.5	OMP	8	14	130	12.7	<b>131</b>	<b>12.6</b>	132	12.5
519.civleaf_t	OMP	8	14	139	11.9	140	11.8	<b>139</b>	<b>11.9</b>	OMP	8	14	139	11.9	140	11.8	<b>139</b>	<b>11.9</b>
521.miniswp_t	OMP	8	14	159	10.1	<b>159</b>	<b>10.1</b>	159	10.1	OMP	8	14	159	10.1	<b>159</b>	<b>10.1</b>	159	10.1
528.pot3d_t	OMP	8	14	<b>190</b>	<b>11.2</b>	190	11.2	190	11.2	OMP	56	2	<b>181</b>	<b>11.7</b>	181	11.7	181	11.8
532.sph_exa_t	OMP	8	14	180	10.8	<b>179</b>	<b>10.9</b>	179	10.9	OMP	112	1	160	12.1	161	12.1	<b>161</b>	<b>12.1</b>
534.hpgmgfv_t	OMP	8	14	163	7.20	163	7.22	<b>163</b>	<b>7.20</b>	OMP	56	2	161	7.28	161	7.30	<b>161</b>	<b>7.29</b>
535.weather_t	OMP	8	14	102	31.6	106	30.6	<b>102</b>	<b>31.6</b>	OMP	16	7	102	31.7	108	29.9	<b>102</b>	<b>31.6</b>

SPEChpc 2021\_tny\_base = 12.1

SPEChpc 2021\_tny\_peak = 12.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



# SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

## Intel

SPEChpc 2021\_tny\_base = 12.1

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021\_tny\_peak = 12.4

**hpc2021 License:** 13  
**Test Sponsor:** Intel  
**Tested by:** Intel

**Test Date:** Apr-2024  
**Hardware Availability:** Jan-2023  
**Software Availability:** Mar-2024

### Hardware Summary

Type of System: Homogenous Cluster  
Compute Node: Intel Server D50DNP1SBB (Xeon Max 9480)  
Interconnect: Mellanox HDR  
Compute Nodes Used: 1  
Total Chips: 2  
Total Cores: 112  
Total Threads: 224  
Total Memory: 128 GB  
Max. Peak Threads: 14

### Software Summary

Compiler: Intel oneAPI Compiler 2024.1.0  
MPI Library: Intel MPI Library 2021.12 for Linux OS  
Other MPI Info: None  
Other Software: None  
Base Parallel Model: OMP  
Base Ranks Run: 8  
Base Threads Run: 14  
Peak Parallel Models: OMP  
Minimum Peak Ranks: 8  
Maximum Peak Ranks: 112  
Max. Peak Threads: 14  
Min. Peak Threads: 1

### Node Description: Intel Server D50DNP1SBB (Xeon Max 9480)

#### Hardware

Number of nodes: 1  
Uses of the node: Compute  
Vendor: Intel  
Model: Intel Server D50DNP1SBB (Xeon Max 9480)  
CPU Name: Intel Xeon Max 9480  
CPU(s) orderable: 1, 2 chips  
Chips enabled: 2  
Cores enabled: 112  
Cores per chip: 56  
Threads per core: 2  
CPU Characteristics: Turbo Boost Technology up to 3.5 GHz  
CPU MHz: 1900  
Primary Cache: 32 KB I + 48 KB D on chip per core  
Secondary Cache: 2 MB I+D on chip per core  
L3 Cache: 112.5 MB I+D on chip per chip  
Other Cache: None  
Memory: 128 GB (8 x 16GB HBM2 3200 MT/s)  
Disk Subsystem: 1 x 1 TB NVMe U.2 2.5" SSD  
Other Hardware: None  
Accel Count: None  
Accel Model: None  
Accel Vendor: None  
Accel Type: None  
Accel Connection: None  
Accel ECC enabled: None  
Accel Description: None  
Adapter: Mellanox ConnectX-6 HDR  
Number of Adapters: 1  
Slot Type: PCI-Express 4.0 x16  
Data Rate: 200Gbit/s  
Ports Used: 1  
Interconnect Type: Mellanox HDR

#### Software

Accelerator Driver: None  
Adapter: Mellanox ConnectX-6 HDR  
Adapter Driver: 23.04-0.5.3  
Adapter Firmware: 20.37.1014  
Operating System: Rocky Linux 8.8 (Green Obsidian)  
4.18.0-477.15.1.el8\_8.x86\_64  
Local File System: xfs  
Shared File System: PANASAS FS  
System State: Run level 5  
Other Software: None



# SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

## Intel

SPEChpc 2021\_tny\_base = 12.1

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021\_tny\_peak = 12.4

**hpc2021 License:** 13  
**Test Sponsor:** Intel  
**Tested by:** Intel

**Test Date:** Apr-2024  
**Hardware Availability:** Jan-2023  
**Software Availability:** Mar-2024

## Interconnect Description: Mellanox HDR

### Hardware

### Software

Vendor: Mellanox  
Model: Mellanox HDR  
Switch Model: Mellanox MQM8790-HS2F Quantum HDR InfiniBand Switch  
Number of Switches: 18  
Number of Ports: 40  
Data Rate: 200 Gbit/s  
Firmware: 20.36.1010  
Topology: Fat-tree  
Primary Use: MPI Traffic

: --

## Submit Notes

The config file option 'submit' was used.

## General Notes

The PANASAS filesystem as described on this result page was formerly generally available. At the time of this publication, it may not be shipping, and/or may not be supported, and/or may fail to meet other tests of General Availability described in the SPEC HPG Policy document, <http://www.spec.org/hpg/policy.html>

HBM is configured as HBM-only mode.

## Compiler Version Notes

=====  
CXXC 532.sph\_exa\_t(base, peak)  
-----

Intel(R) oneAPI DPC++/C++ Compiler 2024.1.0 (2024.1.0.20240308)  
Target: x86\_64-unknown-linux-gnu  
Thread model: posix  
InstalledDir:  
  /global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler  
Configuration file:  
  /global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler/./icpx.cfg  
-----

=====  
CC 505.lbm\_t(base, peak) 513.soma\_t(base, peak) 518.tealeaf\_t(base, peak)  
  521.miniswp\_t(base, peak) 534.hpgmgfv\_t(base, peak)  
-----

(Continued on next page)



# SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021\_tny\_base = 12.1

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021\_tny\_peak = 12.4

**hpc2021 License:** 13  
**Test Sponsor:** Intel  
**Tested by:** Intel

**Test Date:** Apr-2024  
**Hardware Availability:** Jan-2023  
**Software Availability:** Mar-2024

## Compiler Version Notes (Continued)

```

Intel(R) oneAPI DPC++/C++ Compiler 2024.1.0 (2024.1.0.20240308)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir:
  /global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler
Configuration file:
  /global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler/./icx.cfg
-----

=====
FC 519.clvleaf_t(base, peak) 528.pot3d_t(base, peak) 535.weather_t(base,
  peak)
-----

ifx (IFX) 2024.1.0 20240308
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.
-----

```

## Base Compiler Invocation

```

C benchmarks:
mpiicc -cc=icx

C++ benchmarks:
mpicpc -cxx=icpx

Fortran benchmarks:
mpiifort -fc=ifx

```

## Base Portability Flags

```

505.lbm_t: -lstdc++ -std=c++14
513.soma_t: -lstdc++ -std=c++14
518.tealeaf_t: -lstdc++ -std=c++14
521.miniswp_t: -lstdc++ -std=c++14
534.hpgmgfv_t: -lstdc++ -std=c++14

```

## Base Optimization Flags

```

C benchmarks:
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto

```

(Continued on next page)



# SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021\_tny\_base = 12.1

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021\_tny\_peak = 12.4

**hpc2021 License:** 13  
**Test Sponsor:** Intel  
**Tested by:** Intel

**Test Date:** Apr-2024  
**Hardware Availability:** Jan-2023  
**Software Availability:** Mar-2024

## Base Optimization Flags (Continued)

C benchmarks (continued):

-funroll-loops

C++ benchmarks:

-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto  
-funroll-loops

Fortran benchmarks:

-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto  
-funroll-loops -nostandard-realloc-lhs -align array64byte

## Base Other Flags

C benchmarks:

-Wno-incompatible-function-pointer-types

## Peak Compiler Invocation

C benchmarks:

mpiicc -cc=icx

C++ benchmarks:

mpicpc -cxx=icpx

Fortran benchmarks:

mpiifort -fc=ifx

## Peak Portability Flags

505.lbm\_t: -lstdc++ -std=c++14  
513.soma\_t: -lstdc++ -std=c++14  
518.tealeaf\_t: -lstdc++ -std=c++14  
521.miniswp\_t: -lstdc++ -std=c++14  
534.hpgmgfv\_t: -lstdc++ -std=c++14



# SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021\_tny\_base = 12.1

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021\_tny\_peak = 12.4

**hpc2021 License:** 13  
**Test Sponsor:** Intel  
**Tested by:** Intel

**Test Date:** Apr-2024  
**Hardware Availability:** Jan-2023  
**Software Availability:** Mar-2024

## Peak Optimization Flags

C benchmarks:

505.lbm\_t: basepeak = yes

513.soma\_t: basepeak = yes

518.tealeaf\_t: basepeak = yes

521.miniswp\_t: basepeak = yes

534.hpgmgfv\_t: -O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp  
-ffast-math -flto -funroll-loops

C++ benchmarks:

-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto  
-funroll-loops

Fortran benchmarks:

519.clvleaf\_t: basepeak = yes

528.pot3d\_t: -O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp  
-ffast-math -flto -funroll-loops -nonstandard-realloc-lhs  
-align array64byte

535.weather\_t: Same as 528.pot3d\_t

## Peak Other Flags

C benchmarks:

-Wno-incompatible-function-pointer-types

The flags files that were used to format this result can be browsed at

<http://www.spec.org/hpc2021/flags/HBM.html>

[http://www.spec.org/hpc2021/flags/Intel\\_compiler\\_flags.2024-12-11.html](http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2024-12-11.html)

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/hpc2021/flags/HBM.xml>

[http://www.spec.org/hpc2021/flags/Intel\\_compiler\\_flags.2024-12-11.xml](http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2024-12-11.xml)



# SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

## Intel

SPEChpc 2021\_tny\_base = 12.1

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021\_tny\_peak = 12.4

**hpc2021 License:** 13  
**Test Sponsor:** Intel  
**Tested by:** Intel

**Test Date:** Apr-2024  
**Hardware Availability:** Jan-2023  
**Software Availability:** Mar-2024

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEChpc2021 v1.1.8 on 2024-04-06 04:18:55-0400.  
Report generated on 2024-12-31 10:30:43 by hpc2021 PDF formatter v1.0.3.  
Originally published on 2024-12-25.