SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Indiana University

Mason (Intel Xeon L7555, base frequency 1.87 GHz,
PC3-10600R, ECC, running at 1066 MHz and CL9,
Turbo on,
Max Turbo Frequency 2.53 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.01

MPI2007 license: 3440
Test sponsor: Indiana University
Tested by: Huian Li

Test date: Dec-2011
Hardware Availability: Jun-2010
Software Availability: Jan-2011



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	64	**232**	**6.74**	233	6.72	231	6.76							
107.leslie3d	64	835	6.25	832	6.27	**834**	**6.26**							
113.GemsFDTD	64	553	11.4	620	10.2	**557**	**11.3**							
115.fds4	64	295	6.62	**293**	**6.67**	287	6.81							
121.pop2	64	**1424**	**2.90**	1427	2.89	1345	3.07							
122.tachyon	64	**504**	**5.55**	505	5.54	503	5.56							
126.lammps	64	581	5.02	**565**	**5.16**	560	5.21							
127.wrf2	64	**646**	**12.1**	645	12.1	651	12.0							
128.GAPgeofem	64	259	7.98	**261**	**7.90**	262	7.88							
129.tera_tf	64	443	6.25	**444**	**6.24**	444	6.23							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Indiana University

Mason (Intel Xeon L7555, base frequency 1.87 GHz, PC3-10600R, ECC, running at 1066 MHz and CL9, Turbo on, Max Turbo Frequency 2.53 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.01

MPI2007 license: 3440
Test sponsor: Indiana University
Tested by: Huian Li

Test date: Dec-2011
Hardware Availability: Jun-2010
Software Availability: Jan-2011

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	64	446	8.55	**441**	**8.65**	434	8.80							
132.zeusmp2	64	**421**	**7.38**	421	7.38	446	6.96							
137.lu	64	375	9.80	**370**	**9.94**	357	10.3							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Mason Node
Interconnects:	10Gigabit Ethernet Gigabit Ethernet
File Server Node:	HOME
Total Compute Nodes:	2
Total Chips:	8
Total Cores:	64
Total Threads:	64
Total Memory:	1 TB
Base Ranks Run:	64
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C Composer XE 2011 for Linux Version 12.0, Build 20110112
C++ Compiler:	Intel C++ Composer XE 2011 for Linux Version 12.0, Build 20110112
Fortran Compiler:	Intel Fortran Composer XE 2011 for Linux Version 12.0, Build 20110112
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	OpenMPI-1.4.3
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

Node Description: Mason Node

Hardware

Number of nodes:	2
Uses of the node:	compute
Vendor:	HP
Model:	Proliant DL580 G7 Server Series
CPU Name:	Intel Xeon L7555
CPU(s) orderable:	1-4 chips
Chips enabled:	4
Cores enabled:	32
Cores per chip:	8
Threads per core:	1
CPU Characteristics:	Intel Turbo Boost Technology enabled, 5.86 GT/s QPI
CPU MHz:	1866
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	24 MB I+D on chip per chip, 24 MB shared / 8 cores
Other Cache:	None
Memory:	512 GB (64 x 8 GB 2Rx4 PC3-10600R, ECC running at 1066 MHz and CL9)
Disk Subsystem:	Two 500 GB 7200 RPM 2.5" SAS hard drives,in RAID 1 mirror
Other Hardware:	None
Adapter:	HP NC375i 1G w/NC524SFP 10G Module
Number of Adapters:	1

Continued on next page

Software

Adapter:	HP NC375i 1G w/NC524SFP 10G Module
Adapter Driver:	netxen_nic v 4.0.75
Adapter Firmware:	4.0.544
Adapter:	HP NC375i 1G
Adapter Driver:	netxen_nic v 4.0.75
Adapter Firmware:	4.0.544
Operating System:	RHEL6.0 (x86_64) 2.6.32-71.14.1.el6 Kernel 2.6.32-71.14.1.el6
Local File System:	Linux/ext2
Shared File System:	NFS
System State:	Multi-User
Other Software:	TORQUE-2.5.7

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Indiana University

Mason (Intel Xeon L7555, base frequency 1.87 GHz, PC3-10600R, ECC, running at 1066 MHz and CL9, Turbo on, Max Turbo Frequency 2.53 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.01

MPI2007 license: 3440
Test sponsor: Indiana University
Tested by: Huian Li

Test date: Dec-2011
Hardware Availability: Jun-2010
Software Availability: Jan-2011

Node Description: Mason Node

Slot Type:	PCIe x8 Gen2
Data Rate:	10Gbps
Ports Used:	1
Interconnect Type:	10 Gigabit Ethernet
Adapter:	HP NC375i 1G
Number of Adapters:	1
Slot Type:	PCIe x8 Gen2
Data Rate:	1Gbps
Ports Used:	1
Interconnect Type:	1 Gigabit Ethernet

Node Description: HOME

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	IBM
Model:	IBM N5500 NAS
CPU Name:	Intel Xeon CPU
CPU(s) orderable:	1-4 chips
Chips enabled:	4
Cores enabled:	32
Cores per chip:	8
Threads per core:	1
CPU Characteristics:	--
CPU MHz:	1866
Primary Cache:	32 KB I + 32 KB D on chip per chip
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	None
Other Cache:	None
Memory:	6 GB
Disk Subsystem:	10 disks, 320GB/disk, 2.6TB total
Other Hardware:	None
Adapter:	Intel 82546GB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	1
Interconnect Type:	Ethernet

Software

Adapter:	Intel 82546GB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000
Adapter Firmware:	N/A
Operating System:	RedHat EL 4 Update 4
Local File System:	None
Shared File System:	NFS
System State:	Multi-User
Other Software:	None

Copyright 2006-2010 Standard Performance Evaluation Corporation

Indiana University

Mason (Intel Xeon L7555, base frequency 1.87 GHz, PC3-10600R, ECC, running at 1066 MHz and CL9, Turbo on, Max Turbo Frequency 2.53 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.01

MPI2007 license: 3440
Test sponsor: Indiana University
Tested by: Huian Li

Test date: Dec-2011
Hardware Availability: Jun-2010
Software Availability: Jan-2011

Interconnect Description: 10Gigabit Ethernet

Hardware		Software
Vendor:	HP	
Model:	HP NC375i 1G w/NC524SFP 10G Module	
Switch Model:	Cisco 7018 (Line card module: N7K-M132XP-12)	
Number of Switches:	1	
Number of Ports:	16	
Data Rate:	10 Gbps Ethernet	
Firmware:	EPLD 5.0.2	
Topology:	switched	
Primary Use:	MPI traffic and NFS traffic	

Interconnect Description: Gigabit Ethernet

Hardware		Software
Vendor:	HP	
Model:	Cisco SGE2010	
Switch Model:	Cisco SGE2010	
Number of Switches:	1	
Number of Ports:	48	
Data Rate:	1 Gbps Ethernet	
Firmware:	3.0.0.18	
Topology:	switched	
Primary Use:	Network management	

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
MPI startup command:
  mpirun command was used to start MPI jobs.
  eth0 (10 GigE) was specified at the mpirun command line for MPI message passing
  eth3 (1 GigE) was specified for non-MPI communication.
BIOS settings:
  Intel Turbo Boost Technology (Turbo)  : Enabled (the default)
RAM configuration:
  Each compute node has 64x8-GB RDIMMs.
Network:
  Four compute nodes connect to one Cisco Nexus 7018 switch
  via 10 GigE port.
Job placement:
  Each MPI job was assigned to a topologically compact set of nodes, i.e.
  the minimal needed number of compute nodes was used for each job:
  1 compute node for 32 ranks, 2 for 64 ranks, 4 for 128 ranks, and 8 for 256 ranks
```

Continued on next page

General Notes (Continued)

PBS Pro was used for job submission. It has no impact on performance.
Can be found at: http://www.altair.com

Base Compiler Invocation

C benchmarks:
mpicc

C++ benchmarks:

126.lammps: mpicxx

Fortran benchmarks:
mpif90

Benchmarks using both Fortran and C:
mpicc mpif90

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG
126.lammps: -DMPICH_IGNORE_CXX_SEEK
127.wrf2: -DSPEC_MPI_LINUX -DSPEC_MPI_CASE_FLAG

Base Optimization Flags

C benchmarks:
-O3 -xSSE4.1 -no-prec-div

C++ benchmarks:

126.lammps: -O3 -xSSE4.1 -no-prec-div

Fortran benchmarks:
-O3 -xSSE4.1 -no-prec-div

Benchmarks using both Fortran and C:
-O3 -xSSE4.1 -no-prec-div

The flags file that was used to format this result can be browsed at
http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.20120720.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.20120720.xml

Copyright 2006-2010 Standard Performance Evaluation Corporation

Indiana University

Mason (Intel Xeon L7555, base frequency 1.87 GHz, PC3-10600R, ECC, running at 1066 MHz and CL9, Turbo on, Max Turbo Frequency 2.53 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.01

MPI2007 license: 3440
Test sponsor: Indiana University
Tested by: Huian Li

Test date: Dec-2011
Hardware Availability: Jun-2010
Software Availability: Jan-2011

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.
Report generated on Tue Jul 22 13:44:37 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 12 January 2012.