



OMPM2001 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V40z

SPECompMpeak2001 = 12434

SPECompMbase2001 = 11803

SPEC license #HPG0010 | Tested by: Sun Microsystems, Santa Clara | Test site: Menlo Park | Test date: Mar-2005 | Hardware Avail: Apr-2005 | Software Avail: Jan-2005

Notes/Tuning Information (Continued)

+MPSS mean setting the following environment variables:

```
ENV_MPSSHEAP=2m
ENV_MPSSSTACK=2m
ENV_LD_PRELOAD=mpss.so.1
```

Peak tuning:

ONESTEP=yes for all peak tests.

```
310.wupwise_m : -fast -xipo=2 -xarch=amd64 -xprefetch_level=3 -xvector=simd -xopenmp
312.swim_m     : -fast -xipo=2 -xarch=amd64 -xprefetch_level=3 -xvector=simd -xopenmp
314.mgrid_m   : -fast -xipo=2 -xprefetch_level=3 -xarch=amd64 -xopenmp
316.applu_m   : -fast -xipo=2 -xprefetch_level=3 -xarch=amd64
               -Qoption iropt -Aujam:inner=g -xopenmp +MPSS
318.galgel_m  : -fast -xipo=2 -qoption iropt -xprefetch_level=3 -xvector=simd
               -xarch=amd64 -xopenmp -xlic_lib=sunperf +FDO +MPSS
               RM_SOURCES=lapak.f90
320.quake_m   : -fast -xipo=2 -xalias_level=strong -xarch=amd64 -xopenmp
324.apsi_m    : -fast -xipo=2 -xprefetch_level=3 -xopenmp
326.gafort_m  : -fast -xipo=2 -xarch=amd64 -xprefetch_level=3 -xvector=simd
               : -xopenmp +MPSS
328.fma3d_m   : -fast -xipo=2 -xprefetch_level=3 -xarch=amd64 -xopenmp +FDO +MPSS
330.art_m     : -fast -xcrossfile -xarch=amd64 -xalias_level=std -xopenmp
               -lmtmalloc -lm +MPSS
332.ammp_m    : -fast -xipo=2 -xarch=amd64 -xalias_level=std -xopenmp -lmopt -lm +MPSS
```

Portability flags:

```
318.galgel_m : -e -fixed
330.art_m    : Extra Flag: -DINTS_PER_CACHELINE=16 -DDBLS_PER_CACHELINE=8
```

Alternate Source:

```
330.art_m    : Required srcalt purduel used for base and peak
310.wupwise_m : Approved srcalt ompl.32 used for peak
312.swim_m   : Approved srcalt ompl.32 used for peak
314.mgrid_m  : Approved srcalt ompl used for peak
320.quake_m  : Approved srcalt ompl.32 used for peak
324.apsi_m   : Approved srcalt ompl used for peak
```

Base and Peak User Environment:

```
export OMP_NUM_THREADS=4
export SUNW_MP_PROCBIND=TRUE
export SUNW_MP_THR_IDLE=SPIN
export OMP_NESTED=FALSE
export STACKSIZE=16384
export OMP_DYNAMIC=TRUE
ulimit -s unlimited
```

Patch-01 includes the following patches for Sun Studio 10 compiler:

```
117831-01 C++
117835-01 Fortran 90
117837-01 C
117841-01 Fortran Libraries
```

For a description of Sun Studio 10 Compiler flags, portability flags and system parameters used to generate this result, please refer to SUN-20050330-Studio-Solaris-opteron.txt file in the flags directory.



OMPM2001 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V40z

SPECompMpeak2001 = 12434

SPECompMbase2001 = 11803

SPEC license #HPG0010 | Tested by: Sun Microsystems, Santa Clara | Test site: Menlo Park | Test date: Mar-2005 | Hardware AvailApr-2005 | Software AvailJan-2005

Notes/Tuning Information (Continued)

Default BIOS settings used.