



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

Sun Microsystems Sun Fire 6800

SPECompMpeak2001 = 8322

SPECompMbase2001 = 7112

SPEC license #HPG0010 | Tested by: Sun Microsystems, Palo Alto | Test site: Sun Microsystems | Test date: Mar-2003 | Hardware Avail: Mar-2003 | Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio	
310.wupwise_m	6000	698	8594	666	9015	
312.swim_m	6000	959	6256	608	9868	
314.mgrid_m	7300	927	7878	858	8512	
316.applu_m	4000	411	9726	411	9731	
318.galgel_m	5100	543	9385	339	15055	
320.earthquake_m	2600	452	5757	352	7388	
324.apsi_m	3400	550	6180	535	6355	
326.gafort_m	8700	1261	6898	1219	7137	
328.fma3d_m	4600	1114	4129	913	5038	
330.art_m	6400	418	15310	353	18117	
332.ammp_m	7000	1784	3924	1792	3907	

Hardware

CPU: UltraSPARC III Cu
 CPU MHz: 1200
 FPU: Integrated
 CPU(s) enabled: 24
 CPU(s) orderable: 2-24
 Primary Cache: 32KBI+64KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: None
 Other Cache: None
 Memory: 48GB 16-way interleaved
 Disk Subsystem: 1X36GB
 550GB (4 9X18GB Sun StorEdge T3 arrays)
 Other Hardware: --

Software

OpenMP Threads: 8
 Parallel: OpenMP
 Operating System: Solaris 9 12/02
 Compiler: Sun ONE Studio 8 (pre-FCS build 3/9)
 Sun Performance Library 8 (pre-FCS build 3/9)
 File System: ufs with ufs logging
 System State: Multi-User

Notes/Tuning Information

Base Flags:

ONESTEP=yes for all benchmarks

C: -fast -xopenmp -xalias_level=std -xipo=2 -xprefetch_level=3
 -Xc -xprofile -lmtmalloc

f90: -fast -autopar -openmp -xipo=2 -xprefetch_level=3 -xprofile

Extra art Base Flags:

330.art_m: -DINTS_PER_CACHELINE=16 -DDBLS_PER_CACHELINE=8

Portability Flags:

318.galgel_m: -e -fixed

Peak Flags:

ONESTEP=yes for all benchmarks

310.wupwise_m: -fast -openmp -autopar -xipo=2 -Qoption iropt
 -Athr,-Ainline:inc=800:cp=1 -xprefetch_level=3
 -xpagesize=512k

312.swim_m: -fast -xautopar -xreduction -Qoption iropt
 -Ainline:cs=700,-Atile:skewp:b128 -xpad=common:3022



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire 6800

SPECompMpeak2001 = 8322

SPECompMbase2001 = 7112

SPEC license #HPG0010 | Tested by: Sun Microsystems, Palo Alto | Test site: Sun Microsystems | Test date: Mar-2003 | Hardware Avail: Mar-2003 | Software Avail: May-2003

Notes/Tuning Information (Continued)

```

-xprefetch=latx:1.6
314.mgrid_m: -fast -autopar -openmp -xipo=2 -xprefetch_level=3
              -xpagesize=64k
316.applu_m:  -fast -openmp -xipo=2 -Qoption iropt -Aujam:inner=g
318.galgel_m: -fast -xipo=2 -openmp -autopar -xarch=v8plusb
              -xlic_lib=sunperf
320.quake_m:  -fast -xopenmp -xrestrict -xalias_level=strong
              -W2,-Ainline:call_in_pragma -xpagesize=64k
              -xprefetch_level=3 -xprofile -lmtmalloc -lmopt -lm
324.apsi_m:   -fast -autopar -openmp -xipo=2 -xprofile
326.gafort_m: -fast -openmp -xprofile
328.fma3d_m:  -fast -openmp -Qoption iropt -Athr,-Apf:pdl=1
              -xipo=2 -xprofile -lmtmalloc
330.art_m:    -fast -xopenmp -xalias_level=std -xipo=2
              -xprefetch_level=3 -W2,-Apf:outer=0 -xprofile
              -lmtmalloc
332.ammp_m:   -fast -xopenmp -xalias_level=strong
              -xprefetch_level=3 -lmopt -lm -lmtmalloc

```

Alternate Source for Base:

```

ISO C and C++ compatible sources
Available as SPEC OMP Source: ompm2001-isoc-20020619.tar.gz
320.quake_m, 330.art_m, 332.ammp_m

```

Alternate Source for Peak:

```

Compatibility with LAPACK version 3, RM_SOURCES=lapak.f90
Available as SPEC OMP Source: ompm2001-galgel-20020117.tar.gz
318.galgel_m

```

```

SPEC OMPL2001 compatible source for 64-bit systems
Available as SPEC OMP Source: ompm2001-ompl64-20020925.tar.gz
320.quake_m, 324.apsi_m, 326.gafort_m

```

```

ISO C and C++ compatible sources
Available as SPEC OMP Source: ompm2001-isoc-20020619.tar.gz
330.art_m

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1:    -xprofile=collect:./feedback
PASS2:    -xprofile=use:./feedback

```

Base User Environment:

```

unlimit stacksize (in /bin/csh)
setenv STACKSIZE 2048
setenv OMP_DYNAMIC TRUE
setenv MT_BIND_PROCESSOR FALSE
setenv MPSSSTACK 4M
setenv MPSSHEAP 4M
setenv LD_PRELOAD mpss.so.1

```

Peak User Environment:

```

Same as base with the following exception
318.galgel: STACKSIZE=16384

```

Kernel Parameters (/etc/system):



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire 6800

SPECompMpeak2001 = 8322

SPECompMbase2001 = 7112

SPEC license #HPG0010 | Tested by: Sun Microsystems, Palo Alto | Test site: Sun Microsystems | Test date: Mar-2003 | Hardware Avail: Mar-2003 | Software Avail: May-2003

Notes/Tuning Information (Continued)

```
set autoup=900
set tune_t_fsflushr=1
set shmsys:shminfo_shmmax=0xffffffffffffffff
set shmsys:shminfo_shmseg=512
set shmsys:shminfo_shmmni=4096
```

Sun ONE Studio 8 (FCS) will ship May 2003

System configuration details located (as of Mar 2003) at
<http://www.sun.com/servers/midrange/sunfire6800>