



# OMP2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

## IBM Corporation

### IBM eServer pSeries 690 (1900 MHz, 32 CPU)

SPECompMpeak2001 = 43708

SPECompMbase2001 = 38278

SPEC license #HPG0005 | Tested by: IBM Corporation | Test site: IBM, Austin TX | Test date: Feb-2004 | Hardware Avail: Mar-2004 | Software Avail: Oct-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
310.wupwise_m	6000	102	58713	102	58713
312.swim_m	6000	151	39660	118	50959
314.mgrid_m	7300	197	37090	197	37090
316.applu_m	4000	96.9	41262	77.9	51363
318.galgel_m	5100	288	17678	194	26311
320.quake_m	2600	87.2	29831	77.8	33426
324.apsi_m	3400	61.4	55333	61.4	55333
326.gafort_m	8700	156	55882	153	56902
328.fma3d_m	4600	161	28660	161	28660
330.art_m	6400	74.5	85903	50.7	126253
332.ammp_m	7000	387	18067	359	19477

### Hardware

CPU: POWER4+  
 CPU MHz: 1900  
 FPU: Integrated  
 CPU(s) enabled: 32 cores, 16 chips, 2 cores/chip, 4 chips/MCM  
 CPU(s) orderable: 1,2,3,4 (order # of MCMs)  
 Primary Cache: 64KBI+32KBD (on chip) per core  
 Secondary Cache: 1536KB unified (on chip) per chip  
 L3 Cache: 32MB unified (off-chip) per MCM, 4 MCMs in SUT  
 Other Cache: None  
 Memory: 128 GB  
 Disk Subsystem: 1x36GB SCSI, 10K RPM  
 Other Hardware: None

### Software

OpenMP Threads: 32  
 Parallel: OpenMP  
 Operating System: AIX 5L V5.2  
 Compiler: IBM C for AIX, Version 6.0  
 XL FORTRAN for AIX, Version 8.1.1.0  
 Other Software: ESSL 4.1.0.0, PESSL 2.3.0.2, MASS 3.2.1  
 File System: AIX/JFS2  
 System State: Multi-user

## Notes/Tuning Information

Tested by IBM Corporation

Portability Flags & Environment Variables

-bmaxdata:0x80000000 used in all cases except 330.art\_m  
 -qfixed used in: 310.wupwise\_m, 312.swim\_m, 314.mgrid\_m, 316.applu\_m, 324.apsi\_m  
 -qfixed=80 used in: 318.galgel\_m  
 -qsuffix=f=f90 used in: 318.galgel\_m, 326.gafort\_m, 328.fma3d\_m  
 -bmaxdata:0xD0000000 used in 330.art\_m (for base and peak)

### Base Flags

C: -q64 -O5 -qalign=natural -qipa=partition=large -qmaxmem=-1 -qsmp=omp -w  
 FORTRAN:-O5 -qalign=natural -qipa=partition=large -qmaxmem=-1 -qsmp=omp -w

### Base & Peak User Environment:

ENV\_OMP\_NUM\_THREADS=32  
 ENV\_OMP\_DYNAMIC=FALSE  
 ENV\_XLSMPOPTS=SPINS=0:YIELDS=0:STACK=800000:SCHEDULE=STATIC  
 ENV\_MALLOCMULTIHEAP=1

### Peak Flags

-qsmp=omp used in all cases  
 310.wupwise\_m: basepeak=1  
 312.swim\_m: -O3 -qalign=natural -qtune=pwr4 -qarch=pwr4



# OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 690 (1900 MHz, 32 CPU)

SPECompMpeak2001 = 43708

SPECompMbase2001 = 38278

SPEC license #HPG0005 | Tested by: IBM Corporation | Test site: IBM, Austin TX | Test date: Feb-2004 | Hardware Avail: Mar-2004 | Software Avail: Oct-2003

## Notes/Tuning Information (Continued)

```

314.mgrid_m: basepeak=1
316.applu_m: -O3 -qalign=natural -qtune=pwr4 -qarch=pwr4
318.galgel_m: -O5 -qalign=natural -qhot=arraypad -qessl -qlibessl -lesslsmp
               -lpesslsmp -lblacssmp -lmass -qipa=partition=large -qmaxmem=-1
               ENV_OMP_NUM_THREADS=16
320.equake_m: fdpr -v -R3
               -O5 -qalign=natural -qhot=arraypad -Q -lmass
324.apsi_m: basepeak=1
326.gafort_m: -O5 -qalign=natural -qrsqrt -qhot=arraypad -qipa=partition=large
               -qmaxmem=-1
328.fma3d_m: basepeak=1
330.art_m: fdpr -v -R3
               -q64 -O5 -qlargepage -blpdata -qhot=arraypad -Q -lmass
               EXTRA_CFLAGS= -DINTS_PER_CACHELINE=32 -DDBLS_PER_CACHELINE=16
               EXTRA_LDFLAGS=-bmaxdata:0xD0000000 -blpdata
332.ammp_m: -O5 -qalign=natural -qhot=arraypad -Q -lmass

```

### Peak sources:

SPEC OMPL2001 source for 32bit systems modified for SPEC OMPM2001 used with 312.swim\_m, 316.applu\_m, 320.equake\_m, 326.gafort\_m.

MCM: Acronym for "Multi-Chip Module"

SUT: Acronym for "System Under Test"

L3 Cache: 32MB x 4 = 128MB, shared by all processors

C: IBM VAC++ invoked as xlc\_r

Fortran 90: IBM XL Fortran for AIX invoked as xlf90\_r

Fixes APAR IY48265 were applied to AIX.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=4096 -o lpgg_size=16777216 -o memory_affinity=1
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -r
export MEMORY_AFFINITY=MCM

```