



OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX (Intel Xeon X5570, 2.93 GHz, DDR3-1333)

SPECompMpeak2001 = --

SPECompMbase2001 = 41372

SPEC license #HPG0014 Tested by: SGI Test site: SGI Test date: Mar-2009 Hardware Avail: Mar-2009 Software Avail: Jan-2009

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio	
310.wupwise_m	6000	80.0	74960			
312.swim_m	6000	160	37405			
314.mgrid_m	7300	212	34503			
316.applu_m	4000	139	28697			
318.galgel_m	5100	120	42511			
320.quake_m	2600	49.7	52286			
324.apsi_m	3400	91.0	37365			
326.gafort_m	8700	213	40757			
328.fma3d_m	4600	180	25502			
330.art_m	6400	54.9	116554			
332.ampm_m	7000	322	21758			

Hardware

CPU: Intel Xeon X5570
 CPU MHz: 2934
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip (HT on)
 CPU(s) orderable: 1-2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 8 MB I+D on chip per chip
 Other Cache: None
 Memory: 24 GB (6*4GB DDR3-1333 CL9 RDIMMs)
 Disk Subsystem: 7 TB RAID 5
 48 x 147 GB SAS (Seagate Cheetah 15000 rpm)
 Other Hardware: None

Software

OpenMP Threads: 8
 Parallel: OpenMP
 Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP2
 Kernel 2.6.16.60-0.30-smp
 Compiler: Intel C/C++ Compiler 11.0.074
 Intel Fortran Compiler 11.0.074
 File System: NFSv3 IPoIB
 System State: Multi-user, run level 3

Notes/Tuning Information

Portability Flags:

318.galgel_m: -FI -132

Extra Flags:

330.art_m: -DINTS_PER_CACHELINE=16 -DDBLS_PER_CACHELINE=8

Baseline optimization flags:

COPTIMIZE = -O3 -xSSE4.2 -ipo -openmp -ansi_alias (ONESTEP)

FOPTIMIZE = -O3 -xSSE4.2 -ipo -openmp (ONESTEP)

Software Environment:

```
setenv KMP_AFFINITY disabled
setenv KMP_STACKSIZE 31M
setenv KMP_SCHEDULE static,balanced
setenv KMP_LIBRARY turnaround
setenv OMP_DYNAMIC FALSE
setenv OMP_NUM_THREADS 8
limit stacksize unlimited
```

BIOS settings:

AMI BIOS version 8.15
 Hyper-Threading Technology enabled (default)
 Intel Turbo Boost Technology enabled (default)
 Intel Turbo Boost Technology activated in the OS via



OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX (Intel Xeon X5570, 2.93 GHz, DDR3-1333)

SPECompMpeak2001 = --

SPECompMbase2001 = 41372

SPEC license #HPG0014 | Tested by: | SGI | Test site: | SGI | Test date: Mar-2009 | Hardware Avail: Mar-2009 | Software Avail: Jan-2009

Notes/Tuning Information (Continued)

```
/etc/init.d/acpid start
/etc/init.d/powersaved start
powersave -f
```

For a description of SGI's compiler flags, portability flags, and system parameters used to generate this result, please refer to the SGI-20090327-Linux-Intel11.0-intel64.html file in the flags directory.