



OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

SGI

SGI Rackable C1001-G5 (AMD Opteron 6174, 2.20 GHz)

SPECompMpeak2001 = 52374

SPECompMbase2001 = 50410

SPEC license #HPG0014 Tested by: SGI Test site: SGI Test date: Jan-2011 Hardware Avail: Sep-2010 Software Avail: Nov-2010

| Benchmark | Reference Time | Base Runtime | Base Ratio | Peak Runtime | Peak Ratio |
|---------------|----------------|--------------|------------|--------------|------------|
| 310.wupwise_m | 6000 | 70.8 | 84732 | 69.7 | 86068 |
| 312.swim_m | 6000 | 134 | 44940 | 112 | 53601 |
| 314.mgrid_m | 7300 | 128 | 56942 | 128 | 56942 |
| 316.applu_m | 4000 | 109 | 36763 | 102 | 39107 |
| 318.galgel_m | 5100 | 163 | 31271 | 163 | 31271 |
| 320.quake_m | 2600 | 56.2 | 46282 | 47.5 | 54690 |
| 324.apsi_m | 3400 | 56.5 | 60158 | 56.5 | 60158 |
| 326.gafort_m | 8700 | 175 | 49671 | 175 | 49671 |
| 328.fma3d_m | 4600 | 133 | 34594 | 133 | 34594 |
| 330.art_m | 6400 | 41.0 | 156049 | 41.0 | 156049 |
| 332.ammp_m | 7000 | 244 | 28701 | 244 | 28701 |

Hardware

CPU: AMD Opteron(tm) Processor 6174
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 24 cores, 2 chips, 12 cores/chip
 CPU(s) orderable: 1-2 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core
 L3 Cache: 12 MB I+D on chip per chip, 6 MB shared / 6 cores
 Other Cache: None
 Memory: 64 GB (16 x 4 GB, 2Rx4 PC3-10600R-9, ECC)
 Disk Subsystem: 5.8 TB RAID 5
 20 x 146 GB + 40 x 73 GB FC (Seagate Cheetah 15K.4)
 Other Hardware: None

Software

OpenMP Threads: 24
 Parallel: OpenMP
 Operating System: SUSE Linux Enterprise Server 11 SP1 (x86_64),
 Kernel 2.6.32.13-0.4-default
 Compiler: Open64 Compiler Suite: Version 4.2.4
 File System: NFSv3 IPoIB
 System State: Run Level 3 (Multi-User)

Notes/Tuning Information

Base and Peak User Environment (bash):

```
export OMP_NUM_THREADS=24
export OMP_DYNAMIC=FALSE
export O64_OMP_SPIN_COUNT=1000000000
export O64_OMP_SPIN_USER_LOCK=TRUE
export O64_OMP_SET_AFFINITY=TRUE
export O64_OMP_AFFINITY_MAP=" 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23"
export OMP_SLAVE_STACK_SIZE=22M
ulimit -s unlimited
```

For Compiler/OpenMP flags description please refer:
 SGI-x86-open64-424-flags.html

Base tuning:

```
C : opencc -mp -Ofast -march=barcelona -mcmmodel=medium
Fortran : openf90 -mp -Ofast -march=barcelona -OPT:early_mp=on -mcmmodel=medium
ONESTEP=yes
```

Extra flags

```
330.art_m: -DINTS_PER_CACHELINE=16 -DDBLS_PER_CACHELINE=8
```

Portability flags:



OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

SGI

SGI Rackable C1001-G5 (AMD Opteron 6174, 2.20 GHz)

SPECompMpeak2001 = 52374

SPECompMbase2001 = 50410

SPEC license #HPG0014 Tested by: SGI Test site: SGI Test date: Jan-2011 Hardware Avail: Sep-2010 Software Avail: Nov-2010

Notes/Tuning Information (Continued)

318.galgel_m: -fixedform -col80

Peak tuning:

ONESTEP=yes for all benchmarks

310.wupwise_m: FOPTIMIZE= -mp -Ofast -msse3 -OPT:early_mp=on

-LNO:prefetch Ahead=5:prefetch=3 -march=barcelona -mcmodel=medium

-OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3

-IPA:linear=on:plimit=50000:callee_limit=5000 -INLINE:aggressive=on -CG:load_exe=0

312.swim_m: FOPTIMIZE= -mp -O3 -OPT:Ofast -m3dnow -mcmodel=medium -LNO:simd=0

314.mgrid_m: basepeak=yes

316.applu_m: FOPTIMIZE= -mp -Ofast -march=barcelona -OPT:early_mp=on -mcmodel=medium

318.galgel_m: basepeak=yes

320.quake_m: COPTIMIZE= -Ofast -mp -OPT:alias=disjoint -march=barcelona -mcmodel=medium

324.apsi_m: basepeak=yes

326.gafort_m: basepeak=yes

328.fma3d_m: basepeak=yes

330.art_m: basepeak=yes

332.ammp_m: basepeak=yes

Alternate Sources :

314.mgrid_m (base,peak): intel

312.swim_m (peak): ompl.32

316.applu_m (peak): ompl

320.quake_m (peak): ompl

Additional notes for disk subsystem:

The disk subsystem is mounted through NFS over IPoIB via 4x DDR

InfiniBand network. The local disk on the system is only for the OS.