



OMPL2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

SGI
SGI UV1000 (Intel Xeon X7542, 2.66GHz)

SPECompLpeak2001 = 1862732
SPECompLbase2001 = 1613862

SPEC license #HPG0014 Tested by: SGI Test site: SGI Test date: Jan-2011 Hardware Avail Dec-2010 Software Avail Nov-2010

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
311.wupwise_l	9200	46.5	3165207	46.5	3165207
313.swim_l	12500	58.8	3401079	58.8	3401079
315.mgrid_l	13500	164	1314895	146	1475285
317.applu_l	13500	152	1416538	149	1452279
321.quake_l	13000	346	600364	303	685741
325.apsi_l	10500	159	1055172	113	1493230
327.gafort_l	11000	265	664463	182	967185
329.fma3d_l	23500	195	1925073	168	2234218
331.art_l	25000	87.5	4570907	75.6	5290376

Hardware

CPU: Intel(R) Xeon(R) Processor X7542
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 384 cores, 64 chips, 6 cores/chip
 CPU(s) orderable: 2-256 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 18 MB I+D on chip
 Other Cache: N/A
 Memory: 2048 GB (512 x 4 GB Quad-rank DDR3-1066 CL7 DIMMs)
 Disk Subsystem: 60 x 1 TB SATA (HITACHI 7.2K)
 Other Hardware: Routed quad-plane fat tree topology

Software

OpenMP Threads: 384
 Parallel: OpenMP
 Operating System: SUSE Linux Enterprise Server 11 SP1, Kernel 2.6.32.24-0.2.1.2230.2.PTF-default
 Compiler: Intel(R) C++ Intel (R) 64 Compiler XE, version 12.0.1.107, Build 20101116
 Intel(R) Fortran Intel (R) 64 Compiler XE, version 12.0.1.107, Build 20101116
 File System: xfs
 System State: Multi-user, run level 3

Notes/Tuning Information

BIOS settings notes:

Intel Turbo Boost Technology (Turbo) : Enabled (Max 2.80GHz)

Extra Flags:

331.art_l: -DINTS_PER_CACHELINE=16 -DDBLS_PER_CACHELINE=8

General Notes and Environment variables

```
export KMP_LIBRARY=turnaround
export KMP_STACKSIZE=31M
export KMP_BLOCKTIME=infinite
export OMP_DYNAMIC=FALSE
ONESTEP=yes
ulimit -s unlimited
```

For compiler/openmp flags description please refer:

SGI-Linux-Intel12.0-intel64.html

Base optimization flags and environment variables:

Large:

```
OPTIMIZE = -O3 -xSSE4.2 -ipol -openmp -mcmmodel=medium -shared-intel
COPTIMIZE = -ansi-alias
export KMP_AFFINITY=scatter,1
```



OMPL2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

SGI
SGI UV1000 (Intel Xeon X7542, 2.66GHz)

SPECompLpeak2001 = 1862732
SPECompLbase2001 = 1613862

SPEC license #HPG0014 Tested by: SGI Test site: SGI Test date: Jan-2011 Hardware AvailDec-2010 Software AvailNov-2010

Notes/Tuning Information (Continued)

Peak optimization flags and environment variables:

Large:
OPTIMIZE = -O3 -xSSE4.2 -ipo1 -openmp -rcd
export KMP_AFFINITY=scatter,1

Peak per-benchmark optimization flags and environment variables:

311.wupwise_1
basepeak = yes

313.swim_1
basepeak = yes

315.mgrid_1
OPTIMIZE=-O3 -xSSE4.2 -ipo1 -openmp -rcd
export OMP_NUM_THREADS=264

317.applu_1
OPTIMIZE=-O3 -xSSE4.2 -ipo1 -openmp -rcd -mcmmodel=medium -shared-intel
export OMP_NUM_THREADS=360

321.equake_1
export OMP_NUM_THREADS=240

325.apsi_1
OPTIMIZE=-O3 -xSSE4.2 -ipo1 -openmp
export KMP_AFFINITY=scatter,0
export OMP_NUM_THREADS=240

327.gafort_1
OPTIMIZE=-O3 -xSSE4.2 -ipo1 -openmp -rcd -mcmmodel=medium -shared-intel
export KMP_AFFINITY=scatter,0
export OMP_NUM_THREADS=288

329.fma3d_1
FOPTIMIZE=-no-prec-sqrt -fp-model fast=2
export KMP_AFFINITY=scatter,0

331.art_1
COPTIMIZE=-ansi-alias
export OMP_NUM_THREADS=192