



# SPEC® OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

## Intel

SPECompG\_peak2012 = 17.3

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, DDR4-2666 Turbo OFF, SMT ON) Endeavour Node

SPECompG\_base2012 = 15.0

OMP2012 license:13


Test date: Jul-2017

Test sponsor: Intel

Hardware Availability: Jul-2017

Tested by: Intel

Software Availability: Sep-2017



SPECompG\_base2012 = 15.0

SPECompG\_peak2012 = 17.3

### Hardware

CPU Name: Intel Xeon Gold 6148  
 CPU Characteristics: Intel Turbo Boost Technology Disabled  
 CPU MHz: 2400  
 CPU MHz Maximum: 3700  
 FPU: Integrated  
 CPU(s) enabled: 40 cores, 2 chips, 20 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 Chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core  
 L3 Cache: 27.5 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 192 GB (12 x 16 GB 2Rx4 DDR4-2666 ECC Registered)  
 Disk Subsystem: Panasas ActiveStor 14 (Size 124TB)  
 Other Hardware: --  
 Base Threads Run: 80  
 Minimum Peak Threads: 40

Continued on next page

### Software

Operating System: Oracle Linux Server release 7.3  
 Compiler: C/C++/Fortran: Version 18.0.0.082 of Intel Compiler for Linux Beta Build 20170510  
 Auto Parallel: No  
 File System: Linux ext3  
 System State: Default  
 Base Pointers: 64-bit  
 Peak Pointers: 64-bit  
 Other Software: None



# SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

## Intel

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, DDR4-2666 Turbo OFF, SMT ON) Endeavour Node

SPECompG\_peak2012 = 17.3

SPECompG\_base2012 = 15.0

OMP2012 license:13

Test sponsor: Intel

Tested by: Intel

Test date: Jul-2017

Hardware Availability: Jul-2017

Software Availability: Sep-2017

Maximum Peak Threads: 80

## Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	80	67.6	68.5	<b><u>67.6</u></b>	<b><u>68.5</u></b>	68.2	67.8	80	68.5	67.6	<b><u>68.6</u></b>	<b><u>67.5</u></b>	69.1	67.0
351.bwaves	80	263	17.2	<b><u>263</u></b>	<b><u>17.2</u></b>	265	17.1	40	256	17.7	253	17.9	<b><u>253</u></b>	<b><u>17.9</u></b>
352.nab	80	356	10.9	358	10.9	<b><u>358</u></b>	<b><u>10.9</u></b>	80	349	11.2	<b><u>398</u></b>	<b><u>9.78</u></b>	399	9.76
357.bt331	80	258	18.4	<b><u>257</u></b>	<b><u>18.4</u></b>	256	18.5	80	258	18.4	<b><u>262</u></b>	<b><u>18.1</u></b>	263	18.0
358.botsalgn	80	392	11.1	394	11.0	<b><u>394</u></b>	<b><u>11.0</u></b>	80	394	11.0	481	9.04	<b><u>481</u></b>	<b><u>9.04</u></b>
359.botsspar	80	639	8.22	641	8.19	<b><u>640</u></b>	<b><u>8.21</u></b>	40	82.8	63.4	92.8	56.6	<b><u>92.7</u></b>	<b><u>56.6</u></b>
360.ilbdc	80	<b><u>308</u></b>	<b><u>11.5</u></b>	308	11.6	308	11.5	80	<b><u>313</u></b>	<b><u>11.4</u></b>	311	11.4	314	11.4
362.fma3d	80	<b><u>391</u></b>	<b><u>9.72</u></b>	395	9.62	389	9.78	80	<b><u>385</u></b>	<b><u>9.87</u></b>	379	10.0	388	9.80
363.swim	80	347	13.0	<b><u>347</u></b>	<b><u>13.0</u></b>	347	13.1	40	329	13.8	<b><u>328</u></b>	<b><u>13.8</u></b>	328	13.8
367.imagick	80	<b><u>458</u></b>	<b><u>15.4</u></b>	458	15.4	460	15.3	40	<b><u>413</u></b>	<b><u>17.0</u></b>	412	17.1	414	17.0
370.mgrid331	80	361	12.3	360	12.3	<b><u>360</u></b>	<b><u>12.3</u></b>	40	346	12.8	<b><u>345</u></b>	<b><u>12.8</u></b>	344	12.8
371.applu331	80	244	24.8	283	21.4	<b><u>258</u></b>	<b><u>23.5</u></b>	80	264	23.0	<b><u>261</u></b>	<b><u>23.2</u></b>	244	24.9
372.smithwa	80	<b><u>288</u></b>	<b><u>18.6</u></b>	287	18.6	293	18.3	40	228	23.5	226	23.7	<b><u>227</u></b>	<b><u>23.6</u></b>
376.kdtree	80	<b><u>411</u></b>	<b><u>11.0</u></b>	409	11.0	411	11.0	80	442	10.2	442	10.2	<b><u>442</u></b>	<b><u>10.2</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Platform Notes

Sysinfo program /global/panfs02/innl/aknyazel/OMP2012/1.1/Docs/sysinfo  
Revision 563 of 2016-06-10 (097295389cf6073d8c3b03fa376740a5)  
running on epb331 Tue Jul 4 08:09:28 2017

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/omp2012/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) Gold 6148 CPU @ 2.40GHz
 2 "physical id"s (chips)
 80 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 20
siblings : 40
physical 0: cores 0 1 2 3 4 8 9 10 11 12 16 17 18 19 20 24 25 26 27 28
physical 1: cores 0 1 2 3 4 8 9 10 11 12 16 17 18 19 20 24 25 26 27 28
cache size : 28160 KB
```

```
From /proc/meminfo
MemTotal: 196699188 kB
```

Continued on next page



# SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

## Intel

SPECompG\_peak2012 = 17.3

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, DDR4-2666 Turbo OFF, SMT ON) Endeavour Node

SPECompG\_base2012 = 15.0

OMP2012 license:13

Test date: Jul-2017

Test sponsor: Intel

Hardware Availability: Jul-2017

Tested by: Intel

Software Availability: Sep-2017

### Platform Notes (Continued)

HugePages\_Total: 0  
Hugepagesize: 2048 kB

From /etc/\*release\* /etc/\*version\*

```
oracle-release: Oracle Linux Server release 7.3
os-release:
  NAME="Oracle Linux Server"
  VERSION="7.3"
  ID="ol"
  VERSION_ID="7.3"
  PRETTY_NAME="Oracle Linux Server 7.3"
  ANSI_COLOR="0;31"
  CPE_NAME="cpe:/o:oracle:linux:7:3:server"
  HOME_URL="https://linux.oracle.com/"
redhat-release: Red Hat Enterprise Linux Server release 7.3 (Maipo)
system-release: Oracle Linux Server release 7.3
system-release-cpe: cpe:/o:oracle:linux:7:3:server
```

uname -a:

```
Linux epb331 3.10.0-514.6.2.0.1.el7.x86_64.knl1 #1 SMP Thu Mar 2 10:19:17 MST
2017 x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 Jun 30 10:26

SPEC is set to: /global/panfs02/innl/aknyazel/OMP2012/1.1

```
Filesystem      Type  Size  Used Avail Use% Mounted on
panfs://36.101.212.1/innl panfs 108T  40T   69T  37% /global/panfs02/innl
```

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

(End of data from sysinfo program)

### General Notes

=====  
Intel Turbo Boost Technology Disabled  
=====

General base OMP Library Settings  
ENV\_KMP\_AFFINITY=compact,0,verbose

=====  
General peak OMP Library Settings  
ENV\_KMP\_AFFINITY=compact,0,verbose

=====  
Per benchmark peak OMP Library Settings

Continued on next page



# SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

## Intel

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, DDR4-2666 Turbo OFF, SMT ON) Endeavour Node

SPECompG\_peak2012 = 17.3

SPECompG\_base2012 = 15.0

OMP2012 license:13

Test sponsor: Intel

Tested by: Intel

Test date: Jul-2017

Hardware Availability: Jul-2017

Software Availability: Sep-2017

## General Notes (Continued)

```

=====
System settings notes:
=====
General OMP Library Settings
  KMP_LIBRARY=turnaround
  KMP_STACKSIZE=292M
  KMP_BLOCKTIME=infinite
  OMP_DYNAMIC=FALSE
  OMP_NESTED=FALSE
  OMP_SCHEDULE=static
=====
351.bwaves:peak:
  ENV_KMP_AFFINITY=compact,1,verbose
=====
359.botsspar:peak:
  ENV_KMP_AFFINITY=compact,1,verbose
=====
363.swim:peak:
  ENV_KMP_AFFINITY=compact,1,verbose
=====
367.imagick:peak:
  ENV_KMP_AFFINITY=compact,1,verbose
=====
370.mgrid331:peak:
  ENV_KMP_AFFINITY=compact,1,verbose
=====
372.smithwa:peak:
  ENV_KMP_AFFINITY=compact,1,verbose
=====

```

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort



# SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

## Intel

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, DDR4-2666 Turbo OFF, SMT ON) Endeavour Node

SPECompG\_peak2012 = 17.3

SPECompG\_base2012 = 15.0

OMP2012 license:13

Test sponsor: Intel

Tested by: Intel

Test date: Jul-2017

Hardware Availability: Jul-2017

Software Availability: Sep-2017

## Base Portability Flags

350.md: -FR  
357.bt331: -mcmmodel=medium  
363.swim: -mcmmodel=medium  
367.imagick: -std=c99

## Base Optimization Flags

C benchmarks:

-O3 -qopenmp -xCORE-AVX512 -fp-model fast=2 -ansi-alias -no-prec-div  
-no-prec-sqrt

C++ benchmarks:

-O3 -qopenmp -xCORE-AVX512 -fp-model fast=2 -ansi-alias -no-prec-div  
-no-prec-sqrt

Fortran benchmarks:

-O3 -qopenmp -xCORE-AVX512 -fp-model fast=2 -ansi-alias -no-prec-div  
-no-prec-sqrt -align all

## Peak Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

## Peak Portability Flags

350.md: -FR  
357.bt331: -mcmmodel=medium  
363.swim: -mcmmodel=medium  
367.imagick: -std=c99

## Peak Optimization Flags

C benchmarks:

Continued on next page



# SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

## Intel

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, DDR4-2666 Turbo OFF, SMT ON) Endeavour Node

SPECompG\_peak2012 = 17.3

SPECompG\_base2012 = 15.0

OMP2012 license:13

Test sponsor: Intel

Tested by: Intel

Test date: Jul-2017

Hardware Availability: Jul-2017

Software Availability: Sep-2017

## Peak Optimization Flags (Continued)

352.nab: -O3 -qopenmp -xCORE-AVX512 -fp-model fast=2 -no-prec-div  
-no-prec-sqrt -fno-alias -qopt-malloc-options=1 -qopt-calloc

358.botsalgn: -O3 -qopenmp -xCORE-AVX512 -fp-model fast=2 -fno-alias  
-no-prec-div -no-prec-sqrt

359.botsspar: Same as 358.botsalgn

367.imagick: -O3 -qopenmp -xCORE-AVX2 -fp-model fast=2 -fno-alias  
-no-prec-div -no-prec-sqrt

372.smithwa: Same as 367.imagick

### C++ benchmarks:

-O3 -qopenmp -xCORE-AVX512 -fp-model fast=2 -fno-alias -no-prec-div  
-no-prec-sqrt

### Fortran benchmarks:

350.md: -O3 -qopenmp -xCORE-AVX512 -fp-model fast=2 -fno-alias  
-no-prec-div -no-prec-sqrt -align all

351.bwaves: -O3 -qopenmp -xCORE-AVX2 -fp-model fast=2 -fno-alias  
-no-prec-div -no-prec-sqrt -align all

357.bt331: Same as 350.md

360.ilbdc: -O3 -qopenmp -xCORE-AVX512 -fp-model fast=2 -ansi-alias  
-no-prec-div -no-prec-sqrt -align all

362.fma3d: Same as 350.md

363.swim: -O3 -qopenmp -xCORE-AVX2 -fp-model fast=2 -no-prec-div  
-no-prec-sqrt -fno-alias -qopt-malloc-options=3 -align all

370.mgrid331: Same as 363.swim

371.applu331: Same as 351.bwaves

The flags file that was used to format this result can be browsed at

<http://www.spec.org/omp2012/flags/Intel-ic13.0-linux64.20170722.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/omp2012/flags/Intel-ic13.0-linux64.20170722.xml>



# SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

## Intel

Intel Server System R2208WFTZS (Intel Xeon Gold 6148, DDR4-2666 Turbo OFF, SMT ON) Endeavour Node

SPECompG\_peak2012 = 17.3

SPECompG\_base2012 = 15.0

**OMP2012 license:**13

**Test sponsor:** Intel

**Tested by:** Intel

**Test date:** Jul-2017

**Hardware Availability:** Jul-2017

**Software Availability:** Sep-2017

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC OMP2012 v1.1.  
Report generated on Sat Jul 22 17:29:55 2017 by SPEC OMP2012 PS/PDF formatter v541.  
Originally published on 22 July 2017.