SPEC CINT95 Results

©Copyright 1995, Standard Performance Evaluation Corporation

HAL Computer Systems
Fujitsu HALstation 300

SPECint95 = 5.08

SPECint_base95 = 4.59

SPEC license # 27	Tested By: HAL Computer Systems	Test Date: Apr-96	Hardware Avail: Oct-95	Software Avail: Apr-96



Hardware/Software Configuration for:
Fujitsu HALstation 300

Hardware

Model Name:	350
CPU:	118 MHz SPARC64
FPU:	Integrated
Number of CPU(s):	1
Primary Cache:	128KBI,128KBD on chip
Secondary Cache:	None
Other Cache:	None
Memory:	128MB
Disk Subsystem:	1 x 2GB 1 x 2GB
Other Hardware:	Ethernet

Software

Operating System:	SPARC64/OS 2.4
Compiler:	Fujitsu C V2.0.3 Fujitsu Fortran90 V2.0.3
File System:	UFS
System State:	Multiple User
Kernel Extensions:	none

Benchmark # and Name	Reference Time	Base Run Time	Base SPEC Ratio	Run Time	SPEC Ratio
099.go	4600	781	5.89	740	6.22
124.m88ksim	1900	572	3.32	403	4.71
126.gcc	1700	310	5.49	300	5.66
129.compress	1800	509	3.53	490	3.68
130.li	1900	513	3.70	415	4.58
132.ijpeg	2400	429	5.60	411	5.84
134.perl	1900	380	5.00	350	5.44
147.vortex	2700	537	5.03	537	5.03
SPECint_base95 (G. Mean)			4.59		
		SPECint95 (G. Mean)			5.08

Notes/Tuning Information

```
Baseline flags were: -Kfast,gs,V8PLUS -dn
Nonbaseline flags were:
099: -Xa -Kfast,GREG,a4 -O4 -KV8PLUS -Kpopt -x- -dn
124: -Xa -Kfast,GREG,a4 -O4 -KV8PLUS -Kpopt -x10 -dn
126: -Xa -Kfast,GREG,a4 -O4 -KV8PLUS -Kpopt -x10 -Kgs -dn
129: -Xa -Kfast,GREG,a4 -O4 -KV8PLUS -x70 -dn
130: -Xa -Kfast,GREG,popt,a4 -O4 -KV8PLUS -x- -dn
132: -Xa -Kfast,GREG,a4,eval -O4 -KV8PLUS -Kpreload -x150 -Kgs -dn
134: -Xa -Kfast,GREG,a4 -O4 -KV8PLUS -Kpopt -x10 -Kgs -dn
147: -Xa -Kfast,GREG,a4 -O4 -KV8PLUS -Kpopt -x10 -Kgs -dn
Portability: 124, 132: -DSYSV
Portability: 126: -Dalloca=__builtin_alloca
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 22110
(703) 331-0180
info@specbench.org
http://www.specbench.org