

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Advanced Micro Devices: Asus A7M266-D/AMD Athlon MP
Microsoft: IIS 5.0

SPECweb99 = 1617

Test Date: Feb-2002
Tester: Advanced Micro Devices

Hardware Avail: Mar-2002 OS Avail: Feb-2000 HTTP Software Avail: Feb-2000 Sup. Software Avail: Feb-2000 SPEC license #: 49

Hardware

Vendor: Advanced Micro Devices
Model: Asus A7M266-D/AMD Athlon MP
Processor: Athlon MP 2000+, 1.67 Ghz
Processors: 2 cores, 2 chips, 1 core/chip
Primary Cache: 64KBI+64KBD on chip
Secondary Cache: 256KB
Other Cache: None
Memory: 3 GB pc2100 DDR
Disk Subsystem: 4 18GB 15K Ultra160 SCSI
Disk Controllers: AMI Elite 1600
Other Hardware: 1 Extreme Summit 7i Gigabit Switch

Software

Operating System: Windows 2000 Advanced Server
File System: NTFS
Other Software: SP2

HTTP Software

Vendor: Microsoft
HTTP Software: IIS 5.0
API: ISAPI
Server Cache: None
Log Mode: W3C Extended Log File Format

Test Sponsor

Test Date: Feb-2002
Tested By: Advanced Micro Devices
SPEC License: 49

Network

of Controllers: 1
Network Controllers: Intel Gigabit Pro 1000F
of Nets: 1
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 5
Model: Dell PE1400
Processor: Intel Pentium III 800MHz
of Processors: 2
Memory: 256MB
Network Controller: Intel Gigabit Pro 1000F
Operating System: Windows 2000 Professional
Compiler: Microsoft Visual C++ 6.0

Notes/Tuning Information

SUT Notes

IIS settings: maximum performance.
IIS Home Directory: Access for Read & Write, Scripts & Executables.
IIS Virtual Directory spec99 points back to web server root, low app protection.

Operating System Notes

Tuning parameters:
TCPIP/Parameters/NumTcbTablePartitions= 16, sets number of independent TCB table segments, default 4.
TCPIP/Parameters/MaxFreeTwTcbs= 400000, sets maximum number of Time_Wait tcbs to 400,000.
TCPIP/Parameters/TcpTimedWaitDelay= 60, sets TIME_WAIT parameter to 60 seconds(non-RFC1122), default 240.
TCPIP/Parameters/MaxHashTableSize= 0x2710, sets TCB hash table size to 10000 entries, default 512.
TCPIP/Parameters/TCPWindowSize= 17520, sets TCP send/receive window size, default 8192.
TCPIP/Parameters/MaxUserPort= 0xfffe, sets maximum open ports to 65534.
Inetinfo/Parameters/AcceptExTimeout= 1, sets time for accept ex socket to wait for receive, default 120.
Inetinfo/Parameters/LogFileFlushInterval= 60, forces flush every 60 seconds, default 300.
Inetinfo/Parameters/MaxPoolThreads= 20, maximum network request threads per processor, default 10.
Inetinfo/Parameters/ObjectCacheTTL= 0xffff, sets IIS object cache timeout, default 10 minutes.
Inetinfo/Parameters/ListenBackLog= 1000, default 25.
AFD/Parameters/TransmitWorker= 32, adjusts system default thread, default 16.
Control/FileSystem/NtfsDisableLastAccessUpdate= 1, prevents updating LastAccess time stamp on NTFS directories, default 0.
Control/SessionManager/MemoryManagement/IoPageLockLimit= 65536, increases I/O Pages limit to 64MB, default 512KB.
NDIS/Parameters/ProcessorAffinityMask= 0, forces processor that handled interrupt to also handle that DPC, default any processor.
Intel nic registry settings:
NumTxDescriptors= 768, Number of descriptors to send packets, default 256.
NumCoalesceBuffers= 768, Number of coalesce buffers for transmit acceleration, default 128.
ChecksumRxTcp= 1, offloads RX checksums to nic, default 0.
FlowControl= 0, Disables flow control default On (1).

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Hardware Notes

1 18GB 15Krpm disk for OS and logs,3 18GB 15Krpm disks for fileset.

Other Notes

SUT requires an Asus A7M266-D motherboard, an ATX 4 hd capable case and an NSpire ps Model NSP-420P4B. Intfltr to bind NIC IRQ to CPU0.