

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard: hp server rp8400
Zeus Technology Limited: Zeus 4.1r3

SPECweb99_SSL =4400

Test Date: Aug-2002
Tester: Hewlett-Packard Company

Hardware Avail: Aug-2002 OS Avail: Mar-2002 HTTPS Software Avail: Jul-2002 Sup. Software Avail: Aug-2002 SPEC license #: 3

Hardware

Vendor: Hewlett-Packard
Model: hp server rp8400
Processor: PA8700 875Mhz
Processors: 16 cores, 16 chips, 1 core/chip
Primary Cache: 768KBI+1536KBD on chip
Secondary Cache: None
Other Cache: None
Memory: 64 GB
Disk Subsystem: 8x18GB (15K rpm)
Disk Controllers: SCSI Ultra 2
Other Hardware: Surestore SC10 Disk Array

Software

Operating System: HP-UX 11i
File System: See SUT Notes
Other Software: B3913DB C.03.33.01 HP aC++ Compiler

HTTPS Software

Vendor: Zeus Technology Limited
HTTPS Software: Zeus 4.1r3
API: ISAPI
Server Cache: None
Log Mode: Binary Log Format

Test Sponsor

Test Date: Aug-2002
Tested By: Hewlett-Packard Company
SPEC License: 3

Network

of Controllers: 16
Network Controllers: HP A4926A PCI Gigabit Ethernet
of Nets: 16
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 157
Model: HP 9000/A180C
Processor: 180Mhz PA-7300LC
of Processors: 1
Memory: 128MByte
Network Controller: HP A5230A, PCI 100BaseT
Operating System: HPUX 11i
Compiler: B3901BA B.11.11.04 HP C/ANSI C

Notes/Tuning Information

SUT Notes

All filesystems are HP-UX HFS
1 (18 GB) disk used for OS
1 (HP Surestore SC10 Disk Array) used for fileset and logs
Bound each Zeus instance to the processor corresponding to its NIC
Processor binding is performed by: mpsched -c cpu# -p pid"
chattr +pd 64M +pi 64M on zeus.web binary to set page sizes
chattr +pd 4K +pi 4K on zeus.cgi binary to set page sizes

Operating System Notes

HP-UX Internet Operating Environment with following patches:
PHNE_26728 - Cumulative STREAMS Patch
PHNE_27063 - Cumulative ARPA Patch
PHKL_25388 - Cumulative LAN Products Patch
PHKL_25233 - select(2) and poll(2) hang
PHKL_25389 - Core PM, vPar, Psets Cumulative Patch
PHKL_27278 - mmap io, VM-JFS ddlock, thread perf, user limit
PHNE_26939 - 1000Base-SX/T B.11.11.14 cumulative patch
HP-UX Tunable Parameters:
dbc_max_pct=20 Max Buffer Cache Size as Percent of RAM (50)
dbc_min_pct=20 Min bufer Cache Size as Percent of RAM (5)
maxfiles=60000 Soft File Limit per Process (60)
maxfiles_lim=60000 Hard File Limit per Process (1024)
maxssiz_64bit=0x180000000 Max Stack Size for 64-Bit Procs (0x00800000)
maxswapchunks=16384 Max number of swap chunks (256)
maxuprc=512 Max number of user processes (75)

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Operating System Notes (Continued)

nfile=20000 Max number of open files (790)
ninode=320000 Max number of inodes (444)
nkthread=8000 Max number of kernel threads (499)
nproc=512 Max number of processes (276)
tcpshashsz=16384 Relative Scaling Factor for TCP & IP Int. Tables(2048)

HTTPS Software Notes

Zeus Global Parameters:

tuning!cache_files 356750
tuning!cache_max_bytes 0
tuning!cache_small_file 90000
tuning!cache_large_file 1048576
tuning!cache_stat_expire 86400
tuning!cache_flush_interval 86400
tuning!listen_queue_size 8192
tuning!multiple_accept yes
tuning!so_rbuff_size 0
tuning!so_wbuff_size 1048576
tuning!cbuff_size 65536
tuning!keepalive yes
tuning!keepalive_timeout 1200
tuning!keepalive_max -1
tuning!timeout 600
tuning!unique_bind yes
tuning!bind_any no
tuning!sendfile no
tuning!modules!cgi!cbuff_size 1048576
tuning!modules!cgi!cleansize 0
tuning!ssl_keepalive yes
tuning!ssl_diskcache no
tuning!ssl_sessioncache_size 251
tuning!softservers no
tuning!use_poll no
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
tuning!modules!isapi!enabled yes
tuning!cache_cooling_time 0
tuning!maxaccept 2048
security!enabled yes

HTTP API Notes

Zeus ISAPI interface used
Zeus PEPP Toolkit(0.8) used for SPECweb99_SSL dynamic content
./Configure --sendfile=no --checkconfig=yes --locking=semop --ssl=yes --64bit=yes

Network Notes

Networking Tunable Parameters:

tcp_xmit_hiwater_def=2000000 Max unsent data triggers flow control(32768)
tcp_conn_request_max=1024 Max outstanding connection reqs (20)
tcp_conn_strategy=1 Selects TCP connection strategy (0)

Client Notes

HP-UX Tunable Parameters:

max_thread_proc=800 Number of threads per process (64)

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Client Notes (Continued)

maxusers=256 Value of MAXUSERS macro (32)
ncallout=5000 Increase number of pending timeouts
nkthread=8000 Maximum number of system-wide threads

Other Notes

Tuning Disclosure: HP-20020723.txt
Dynamic API: HP-20020723-API.tar.gz